



# **Principles and Theory of Radar Interferometry**

Piyush S Agram

Jet Propulsion Laboratory

July 29, 2013 UNAVCO Short Course

Disclaimer: Large parts of this talk has been derived from UNAVCO's ROI\_PAC short course (2012) notes by Paul Rosen, JPL.





#### **Outline of Tutorial**

#### **MORNING SESSION**

- I. Fundamentals of Interferometry
  - A. Young's double slit experiment
  - B. Variations to Young's experiment
  - C. Extension to radar interferometry
- II. Radar Imaging Fundamentals
  - A. Basic Principles of Remote Sensing, Radar, and SAR
  - B. Range and Azimuth Compression
  - C. Doppler and its Implications





#### **Outline of Tutorial**

#### **AFTERNOON SESSION**


- I. Properties of radar images
- II. Geometric Aspects of Interferometry and Interferometric Phase
  - A. Interferometry for Topographic Mapping
  - B. Interferometry for Deformation Mapping
- III. Interferometric Correlation
  - A. SNR and Interferometric Correlation
  - B. Geometric, Temporal and Volumetric Decorrelation
  - C. Other Error Sources






# What is interferometry?

Interferometry is a family of techniques in which waves, usually electromagnetic, are superimposed in order to extract information about the relative change in wave properties.





Wave 2 Modified wave Waves typically modified by interaction with media, multiple reflections etc.






# **Wave Properties of Light**

propagating

Light waves are electromagnetic energy that propagates



Energy propagates


Amplitude "Phase" frequency 
$$E(x,y,z,t) = E_0 e^{j\phi(x,y,z,t)} = E_0 e^{j(\omega t - \vec{k} \cdot \vec{r})}$$





#### Young's double slit experiment

 In Young's experiment, a point source illuminates two separated vertical slits in an opaque screen. The slits are very narrow and act as line sources. For this case, the pattern of intensity variations on the observing screen is bright/dark banding.





#### **Interference Concept**



 Interference occurs when the phase of two different waves is not aligned. The observed intensity, I, is the time average of the sum of the wave fields





Fig. 7.1. Interference of two beams of equal intensity; variation of intensity with phase difference.





#### **Wave interference**




#### Band spacing depends on

- 1. wavelength
- 2. Spacing between the two slits





#### The math



L >> d => Lines from each slit to P are parallel

©: The scientificsentence.net. 2007.

$$l = d \cdot \frac{x}{L}$$

Path difference


$$l = d \cdot \frac{x}{L}$$
$$\Delta \phi = 2\pi \frac{l}{\lambda}$$

Phase difference





#### Baseline / slit separation



Animation demonstrating the relationship between baseline and phase difference.





#### Generalizing Young's interferometer

- Two slits ensure that the interfering waves have same wavelength (derived from one source).
- On the screen, we observe (amplitude) the sum of the two waves.
- Individual wave information is lost.
- Two waves should be of similar amplitude.

What if we can vary the experimental setup?





#### Variant 1: Hypothetical Phase detector

- What if phase could be directly estimated?
- Can we use only one source at a time?

$$A_1 \cdot e^{-j\vec{k}\cdot\vec{r_1}} + A_2 \cdot e^{-j\vec{k}\cdot\vec{r_2}}$$

Original interferometer

$$A_1 \cdot e^{-j\vec{k}\cdot\vec{r_1}} \times \operatorname{conj}(A_2 \cdot e^{-j\vec{k}\cdot\vec{r_2}})$$


If direct phase measurements were possible.

• No more dependence on <u>amplitude</u>





#### Phase difference image




- Both sources operated at different times.
- Fringes generated by combining phase later.



#### Radar Interferometry- I



- Radar Interferometry is a simple extension of the Young's interferometry concept
- Radar has a coherent source much like a laser
- The two radar (SAR) antennas act as coherent point sources
- SAR image is equivalent to a phase and amplitude detector.
- Two SAR images can then be used to generate interferograms.








#### Variant 2: Topography/Deformation

- What if the screen were not flat?
- What if the screen deformed between two images?



Animation
Observed place

Observed phase


Flat screen phase

as a function of screen topography



# Radar Interferometry- II






The surface topography modulates the interference pattern.





#### Variant 3: Coherent Imaging system

- Practical problem
  - we can't set up phase detectors everywhere.
- Possible solution



Screen / scattering surface





#### 2D imaging system

- Wavelength/ frequency needs to be constant for preserving phase information
- Source and receiver combination used to create a 2D image of the screen / scattering surface
- Often source and receiver are co-located

$$\Delta \phi(x, y) = \phi_1(x, y) - \phi_2(x, y)$$
  
$$\phi_i = \text{source} \rightarrow \text{pixel} + \text{pixel} \rightarrow \text{receiver}$$

Radar is one such coherent imaging system





#### Moving on to radar fundamentals

- We have used simple variants of Young's interferometer to motivate the use of radar as a coherent imaging system.
- Next section of talk will focus on fundamentals of radar imaging.
- Besides being a coherent imaging system, One of the main benefits of using radar: Remote Sensing





# What is Remote Sensing?

• In modern usage, **Remote sensing** generally refers to the use of aerial [or satellite] sensor technologies to detect and classify objects on Earth [or other planets] (both on the surface, and in the atmosphere and oceans) by means of propagated signals (e.g. electromagnetic radiation emitted from aircraft or satellites).

#### Active

Radar, sonar, lidar...

#### Passive

- Multi/hyperspectral, photometers, radiometers, gravity sensors, field detectors, seismometers...
- Technique and sensor choice depends on what information is desired and the required accuracy and resolution for that information.





#### What do we want to measure?

- Topography\*
- Geography\*
- Chemistry
  - Composition
  - Phase
- Dynamics
  - Thermo-
  - Hydro\*-
  - Geo\*-
  - Bio\*-








# Radar and Light Waves






$$\lambda = \frac{c}{f}$$

#### Common Radar Frequency Bands

Band	Ka	Ku	Χ	С	S	L	Р
Wavelength (cm)	1	2	3	6	12	24	75
Frequency (G-cycles/s)	30	15	10	5	2.5	1. 2	0.4

- Radars operate at microwave frequencies, an invisible part of the electromagnetic spectrum
- Microwaves have wavelengths in the millimeter to meter range
- Like lasers, radars are coherent and nearly a pure tone

The Electromagnetic Spectrum





mm's to m's 100's μm



#### The Radar Concept









- Much like sound waves, radar waves carry information that echoes from distant objects
- The time delay of the echo measures the distance to the object
- The changes of the message in the echo determines the object characteristics







#### A Note on Antennas


 Antennas direct the radiation into a desired angular region that depends on the size of the antenna and its wavelength.

 $\theta_{3dB} \approx k \frac{\lambda}{L}$ 













## Radar on a Moving Platform







- Pulses are transmitted from the radar platform as it moves along its flight path
- Each pulse has finite extent in time, illuminating a narrow strip of ground as it sweeps through the antenna beam
- Some of the energy from the ground is scattered back to the radar instrument

#### Antenna Beamwidth

$$\theta_{3dB} = \frac{\lambda}{L}$$

Footprint Size on Ground


$$\Delta X_{az} \approx \rho \theta_{3dB_{az}} = \frac{\rho \lambda}{L_{az}}$$

$$\Delta X_
ho \;\; pprox \;\; 
ho heta_{3dB_
ho} = rac{
ho \lambda}{L_
ho}$$



#### Achieving resolution in range






If possible, use a narrow pulse to resolve close targets



#### Achieving resolution in range












# Range and Range Resolution FYI



- Range is the distance between the radar and an object
  - Range resolution would normally be limited by the length of the emitted pulse.
  - Better resolution is achieved by transmitting coded waveforms. Most typical encoding is a chirp.







#### **Radar Imaging Geometry**



Quick detour: intro2radar.com

A VISUAL INTRODUCTION TO RADAR REMOTE SENSING


By Iain H Woodhouse



## Raw Signal of a Point Target



Range ----




This "image" shows a sequence of simulated pulse echoes from a single point target



# Range Compression of a Point Target; after Matched filtering

Range -----




This "image" shows the simulated pulse echoes after range compression matched filtering



## Targets after range compression JPL



- Squint determines which part of the range curve is sampled by the footprint.
- Doppler centroid is a measure of squint.







# **Doppler Shift**

- Objects moving relative to a radar experience a frequency shift called the Doppler shift.
- Objects moving toward the radar have higher frequencies
- Objects moving away from the radar have lower frequencies.

$$f_d = \frac{2\langle \vec{v}, \hat{\ell} \rangle}{\lambda} = \frac{2v \cos \theta_{sq}}{\lambda}$$



## Doppler in SAR Imaging

 $f_{D}(t)$ 



$$R(x) = \sqrt{R_0^2 + (x - x_0)^2}$$
  
 $\approx R_0 \left( 1 + \frac{(x - x_0)^2}{2R_0^2} \right)$ 
  
 $\approx R_0 + \frac{(x - x_0)^2}{2R_0}$ 

Target at  $(x_0,R_0)$ 

x is satellite position


#### Dropping the constant term


$$\phi(t) = -\frac{\pi}{F^2}v^2(t - t_0)^2$$

$$\omega(t) = -2\pi \frac{v^2}{F^2}(t - t_0)$$

$$f_D(t) = -\frac{v^2}{F^2}(t - t_0)$$

$$F^2 = \lambda R_0/2.$$








## **SAR Imaging Concept**








## Targets after range compression





Two targets at same range have different range curves.

Combining information from multiple pulses allows use to resolve the targets.





# **Nyquist Sampling Theorem**

- A consequence of the Nyquist Sampling Theorem is the the radar PRF must be twice the bandwidth of the received signal in order to avoid spectral aliasing of the signal.
- Using the expression from the previous viewgraph for the azimuth bandwidth we have that

$$PRF \ge \frac{2v}{L_{az}}\cos\theta_{az}$$

which for small squint angles,  $\theta_{\rm az}$  smaller than 25°, is often simplified to


$$PRF \ge \frac{2v}{L_{az}}$$

 Note that the required PRF is independent of wavelength and range and only depends on the platform velocity and the azimuth antenna dimension.





# **Azimuth Resolution from Aperture Synthesis**




- Azimuth Footprint,  $X_{iii} = \lambda R_0/L$
- Target is visible for 2\*Footprint at R<sub>0</sub>
  - Thus, length of synthetic aperture is 2 x Footprint.
- Equivalent azimuth resolution =  $(\lambda R_0/(2^*X_{iii}) = (L/2)$  is constant
- Aperture synthesis processing is very similar to matched filtering in range



# Range Compression of a Point Target; after Matched filtering


Range -----



This "image" shows the simulated pulse echoes after range compression matched filtering

# Point Target after Azimuth Compression Matched filtering

Range -----



This "image" shows the simulated pulse echoes after range compression matched filtering






# SEASAT – SAR in Space in 1978



SEASAT SAR image of Death Valley






#### **Conventional SAR modes**



- Strip-mode SAR
  - Standard SAR mode
  - Send a pulse of energy; receive echo; repeat
  - One pulse transmit and receive at a time
  - Swath width limited by radar ambiguities

#### ScanSAR


- Wider swath low resolution SAR mode
- Execute sequence as follows:
  - Send a pulse of energy; receive echo; repeat 50-100 times
  - Repoint the beam across-track to position 2 electrically (almost instantaneous)
  - Send a pulse of energy; receive echo; repeat 50-100 times
  - Repoint the beam across-track to position 3 electrically (almost instantaneous)
  - Send a pulse of energy; receive echo; repeat 50-100 times
- Again, one pulse transmit and receive at a time
- ScanSAR trades resolution (in along-track dimension) for swath: low impact on data rate
- Generally poorer ambiguity and radiometric performance than Strip SAR





#### **Conventional SAR modes**





Copyright: radartutorial.eu

# TOPSSAR

Copyright: DLR

#### Spotlight SAR

- Steers beam to focus on smaller area
- Higher resolution than Stripmap
- Doppler variation along track

#### TOPS SAR

- Wider swath low resolution SAR mode
- Steer the beam to cover a larger swath
- Trades resolution (in along-track dimension) for swath.
- Sentinel-I later this year





#### In the afternoon session:

- I. Properties of radar images
- II. Geometric Aspects of Interferometry and Interferometric Phase
- III. Interferometric Correlation
- IV. Interferometric Processing Workflow