




**RenewAire™**  
*Energy Recovery Ventilation*  
*Think Greener. Breathe Better.*

## COMMERCIAL PRODUCT CATALOG



Proyectos Rogo Del Norte, S.A. de C.V.  
Ave. Miguel Alemán #200 Local TR-23 , Col. Talaverna  
San Nicolas de los Garza, Nuevo León, C.P.66473  
Tels.- (81) 2133-8288

# ENERGY RECOVERY VENTILATION: THE PROVEN ADVANTAGES OF HEAT AND HUMIDITY TRANSFER

## *Improves Indoor Air Quality*

By providing simultaneous exhaust and fresh air supply, RenewAire reduces the concentration of harmful pollutants in indoor air - an absolute must in schools, offices and smoking environments.

## *Meets Ventilation Codes for Air Exchange*

Provides ample ventilation to meet ASHRAE 62 and the International Mechanical Code that now requires two to three more air exchanges than in the past.

## *Controls Excess Moisture*

Unlike conventional ventilation or basic heat exchangers, RenewAire moderates not only the temperature but the humidity content of incoming air, limiting humidity swings and associated biologic growths.

## *Optimum Cold Weather Performance*

Recaptures heat otherwise lost to exhaust air while controlling humidity extremes. This greatly reduces the demand on heating equipment - lowering both initial costs and energy bills. Also protects heating coils from freeze damage.

## *Optimum Warm Weather Performance*

Pre-cools and dehumidifies the fresh airstream by transfer of heat and humidity to the exhaust airstream. This greatly reduces air conditioning demand - lowering both initial costs and energy bills. On retrofits, the ventilation rate of existing A/C equipment can be as much as doubled.

## *Energy Saved = Dollars Saved*

RenewAire's all-weather performance can cut annual energy bills for heating, cooling and dehumidification of ventilation air by 50% or more.



*Indoor Air Quality Problems Solved!*




*Ideal for Hot or Cold Environments*

## *Catalog Page Reference*

2	Residential Products	36	EV450RT
4	BR70	38	HE1XRT
5	BR130	40	HE1XRTC
6	EV70	42	HE2XRT
7	EV130	44	HE2XRTC
8	EV200	46	HE3XRT
9	EV300	48	HE3XRTC
10	Commercial Indoor Products	50	HE4XRT
12	EV450IN	52	HE4XRTC
14	HE1XINH	54	HE6XRT
16	HE1XINV	56	HE8XRT
18	HE2XINH	58	Applied Products
20	HE2XINV	60	CA-Series
22	HE3XINH	62	PA-Series
24	HE3XINV	64	Commercial Controls
26	HE4XINH	66	HVI Certifie
28	HE4XINV	67	AHRI Certifie
30	HE6XIN	67	CA/PA Model Number Guide
32	HE8XIN	68	EV/HE Model Number Guide
34	Commercial Outdoor Products	69	Company History



# WHY RENEWAIRE?



## G5 Enhanced Humidity Transfer

*RenewAire is proud to introduce the fifth generation energy recovery ventilation (ERV) core.*

- Over 22% more humidity transfer at AHRI summer conditions
- reduced pressure drop - among the lowest for static-plate ERV

HE1X = 0.65" @ 750 SCFM  
EV450 = 0.6" @ 450 SCFM

Try RenewAire's  
**ERV Calculation Software**  
at [www.ervcalc.renewaire.com](http://www.ervcalc.renewaire.com)

RenewAire's remarkable performance is independently certified by



### ***The Static-Plate Core is the Key!***

Since the early 1980's, RenewAire has pioneered the use of the patented Lossnay (Registered trademark of Mitsubishi Electric Corporation) exchange core throughout the Americas. Listed below are some of the many reasons why this technology has become the ERV system preferred by leading HVAC professionals around the world.

### ***Positive Airstream Separation***

In the RenewAire core, fresh air never comes in contact with exhaust air passages. Hydroscopic resin plates separate the two airstreams so effectively that AHRI certifies zero exhaust air transfer at normal, balanced operating conditions. As a result, RenewAire is perfect for controlled exhaust applications such as toilet areas, as well as for food service and health care occupancies.

### ***No Condensate or Active Defrost***

Direct water vapor transfer, driven by vapor pressure, eliminates condensation - and frosting - in virtually all applications and climate zones. No condensation allows for closer plate spacing, resulting in higher efficiencies and easier installations. It also means no need for the dampers or electrical defrost elements that reduce ventilation and rob energy efficiency in competing technologies

### ***Maintenance - Nothing Could Be Easier***

The scheduled maintenance for RenewAire is so simple, it can be performed by any janitorial staff. No expensive service contracts are necessary because there is no wheel disassembly and washing, no seal or belt adjustments and no complex controls to calibrate. The result is the lowest maintenance cost of any ERV.

### ***The Unbeatable RenewAire Warranty***

An investment in RenewAire is protected by a 10-year core warranty (2 years on balance of the unit). This commitment - twice as long as coverage on the best wheel products - speaks volumes about RenewAire's reliability, durability and consistently high performance.


### ***Award-Winning Service and Support***

RenewAire's team of professionals knows ERV. And our nationwide network of Sales Reps and quality Distributors are ready to serve you locally. When you call our support number, you'll talk to a knowledgeable factory expert - someone who knows not only our product line, but the best ways to integrate RenewAire with your preferred lines of heating and air conditioning equipment.


# RESIDENTIAL/SMALL COMMERCIAL PRODUCTS

- Commercial quality, ducted equipment sized to meet required ventilation rates for homes and small commercial buildings.
- Static-plate technology makes total energy savings practical for small-capacity systems.
- May be mounted in any orientation.
- Quiet, powerful blowers eliminate the need for air balancing in most applications.
- Positive airstream separation that is critical for smoking environments and bathroom exhaust.
- No condensate pan or drain required.
- Easiest maintenance of any ERV.
- Performance certified by HVI
- Ten year core warranty.

## Central Exhaust - Use EV Series



## General Exhaust - EV Series (or BR Series mounted to furnace return air which requires furnace blower interconnect)



### PTL Control

- primary control for EV70, EV130, EV200 & EV300
- runs unit an adjustable amount of time each hour
- two wire, low voltage connection to ERV



### PBL Control

- push button control turns on unit from bathrooms or other intermittent exhaust locations
- 20 minute run-time with one touch
- push 2x for 40 or 3x for 60 minutes
- two wire, low voltage connection to PTL Control



### FM Control

- alternate primary control for EV70, EV130, EV200 & EV300
- wires to EV unit and either thermostat or furnace control to turn on furnace blower
- six wire, low voltage connection

# Residential Energy Recovery Ventilators: BR70, BR130, EV70, EV130, EV200 and EV300

## Part I - General

### A. Product Specification

1. Energy Recovery Ventilator (ERV) shall be a packaged unit as manufactured by RenewAire and shall transfer both heat and humidity using static plate core technology.

### B. Quality Assurance

1. The energy recovery ventilator shall be Certified by the Home Ventilating Institute (HVI) under CSA 439. Both a heating and a cooling test must be run to demonstrate year round energy recovery.

2. Manufacturer shall be able to provide evidence of independent testing of the core by Underwriters Laboratory (UL), verifying a maximum flame spread index (FSI) of 25 and a maximum smoke developed index (SDI) of 50 thereby meeting NFPA 90A and NFPA 90B requirements for materials in a compartment handling air intended for circulation through a duct system. The method of test shall be UL Standard 723.

3. Unit shall be Listed under UL 1812 Standard for Ducted Air to Air Heat Exchangers. The unit must pass commercial flammability requirements and shall not be labeled "For Residential Use Only".

4. The ERV core shall be warranted to be free of manufacturing defects and to retain its functional characteristics, under circumstances of normal use, for a period of ten years from the date of purchase. The balance-of-unit shall be warranted to be free of manufacturing defects and to retain its functional characteristics, under circumstances of normal use, for a period of two years from the date of purchase.

## Part II - Performance

### A. Energy Transfer

The ERV shall be capable of transferring both sensible and latent energy between airstreams. Latent energy transfer shall be accomplished by direct water vapor transfer from one airstream to the other, without exposing transfer media in succeeding cycles directly to the exhaust air and then to the fresh air.

### B. Passive Frost Control

The ERV core shall perform without condensing or frosting under normal operating conditions (defined as outside temperatures above -10°F and inside relative humidity below 40%). Occasional more extreme conditions shall not affect the usual function, performance or durability of the core. No condensate drains will be allowed.

### C. Continuous Ventilation

Unit shall have the capacity to operate continuously without the need for bypass, recirculation, pre-heaters or defrost cycles under normal operating conditions.

### D. Positive Airstream Separation

Water vapor transfer shall be through molecular transport by hydroscopic resin and shall not be accomplished by "porous plate" mechanisms. Exhaust and fresh airstreams shall travel at all times in separate passages and airstreams shall not mix.

### E. Laminar Flow

Airflow through the ERV core shall be laminar over the products entire operating airflow range, avoiding deposition of particulates on the interior of the energy exchange plate material.

## Part III - Product

### A. Construction

1. The energy recovery component shall be of fixed-plate cross-flow construction, with no moving parts.

2. No condensate drain pans or drains shall be allowed and unit shall be capable of operating in both winter and summer conditions without generating condensate.

3. The unit case shall be constructed of 24-gauge steel, with lapped corners and zinc plated screw fasteners. The case shall be finished with textured, powder coat paint.

4. Access doors shall provide easy access to blowers, ERV cores and filters. Doors shall have an airtight compression seal using closed cell foam gaskets.

5. Case walls and doors shall be fully insulated with 1 inch, expanded polystyrene foam insulation faced with a cleanable foil face on all exposed surfaces.

6. The ERV cores shall be protected by a MERV-8 rated, spun polyester, disposable filter in both airstreams

7. The unit shall have a line cord power connection and be supplied with an internal 24 VAC transformer and relay.

8. Standby power draw shall not exceed 1 Watt for the unit along with an optional automatic control.

### B. Options (Select options based on application requirements)

1. **For BR-Series:** Through the wall kit and duct collar kit (automatic control is built into the unit standard).

2. **For EV-Series:** Controls including proportional run time, push button and furnace interlock and a variety of weather hoods.

## Part IV - Installation

### A. Unit Location

1. Locate and orient unit to provide the shortest and most straight duct connections. Provide service clearances as indicated on the plans. Locate units distant from sound critical occupancies.

2. Use integral mounting flange and hanging bar system to mount the unit to a structurally suitable surface. The units may be mounted in any orientation.

### B. Vibration Isolation

1. Utilize factory supplied vibration isolation kit following instructions.

2. Provide flexible duct connections at unit duct flange

### C. Duct Design

1. All ductwork shall be designed, constructed, supported and sealed in accordance with SMACNA HVAC Duct Construction Standards and pressure classifications

2. At a minimum all duct runs to the outdoors shall be thermally insulated at levels appropriate to the local climate. A continuous vapor barrier shall also be provided on warm surface of the insulation.

### D. Sound Control

1. To control sound radiated from the unit:  
a. Provide acoustic treatment in mechanical room walls and ceilings.

2. To control sound associated with the two blower outlets:  
a. Utilize insulated, flexible duct  
b. In sound critical applications provide increased duct sizing and consider the use of sound attenuators.

### E. Test and Balancing


1. Test and Balancing may not begin until 100% of the installation is complete and fully functional.

2. Follow National Comfort Institute (NCI) air test and balance procedures specific to Heat Recovery Ventilator Balancing Procedure including standard reports to the owner's representative.

# BR70



## Indoor Unit



## G4 Performance


Airflow CF	ESP in H <sub>2</sub> O	Temp EFF%	Total EFF% Winter/Summer*
35	0.50	84	75/60
51	0.40	80	71/56
63	0.30	77	68/53
79	0.20	73	64/48
90	0.10	70	61/45

\* (See HVI certification report on page 66 for complete certified rating


## Specification

Ventilation Type: Static Plate, Heat and Humidity Transfer				
Typical Airflow Range: 40-70 CFM				
Number Motors: One, 0.08 hp				
V	Hz	Phase	Input Watts	FLA
120	60	Single	94 @ 69 CFM	0.9
Control Voltage: 24 VAC				
Filters: MERV 8, spun polyester media. 7 1/2" x 10 1/2" x 1"				
Weight: 39 lbs (unit), 50 lbs (in carton)				
Shipping Dimensions: 21 1/2"W x 29"L x 14 1/2"H				
Options: Thru-the-Wall Kit Duct Collar Kit				

## Dimensions



**EA:** Exhaust Air to outdoors  
**OA:** Outdoor Air intake  
**RA:** Room Air to be exhausted  
**FA:** Fresh Air to inside  
  
**TW:** Thru Wall  
**DH:** Duct Hung



# BR130

## Indoor Unit




## G4 Performance

Airflow CF	ESP in H <sub>2</sub> O	Temp EFF%	Total EFF% Winter/Summer*
52	0.70	83	75/60
69	0.60	80	72/57
94	0.50	76	67/52
113	0.40	73	64/48
132	0.30	70	60/44
141	0.20	68	59/43
148	0.10	67	57/41

\* (See HVI certification report on page 66 for complete certified rating

## Dimensions




## Specification

Ventilation Type:	Static Plate, Heat and Humidity Transfer			
Typical Airflow Range:	50-140 CFM			
Unit may be mounted in any orientation				
Number Motors:	One, 0.1 hp			
V	Hz	Phase	Input Watts	FLA
120	60	Single	121 @ 124 CFM	1.3
Control Voltage:	Built in proportional runtime control and switched terminals for furnace / AC interconnect			
Filters:	MERV 8, spun polyester media. 10 1/2" x 10 1/2" x 1"			
Weight:	49 lbs (unit), 60 lbs (in carton)			
Shipping Dimensions:	21" W x 32" L x 17 1/2" H			
Options:	Thru-the-Wall Kit Duct Collar Kit			

# EV70



## Indoor Unit



## G4 Performance


Airflow CF	ESP in H <sub>2</sub> O	Temp EFF%	Total EFF% Winter/Summer*
46	0.40	81	74/60
59	0.30	78	71/57
73	0.20	74	68/53
86	0.10	71	64/49

\* (See HVI certification report on page 66 for complete certified rating)



## Specification

Ventilation Type: Static Plate, Heat and Humidity Transfer				
Typical Airflow Range: 40-70 CF				
Unit may be mounted in any orientation				
Number Motors: One, 0.08 hp				
V	Hz	Phase	Input Watts	FLA
120	60	Single	94 @ 69 CFM	0.9
Control Voltage: 24 VAC				
Filters: MERV 8, spun polyester media. 7 1/2" x 10 1/2" x 1"				
Weight: 39 lbs (unit), 48 lbs (in carton)				
Shipping Dimensions: 21 1/2"W x 29"L x 14 1/2"H				
Options: PTL - Percentage Timer Control PBL - Push Button Point-of-Use Controls FM - Percentage Timer Control with Furnace Interlock DH24 - Dehumidistat Control Wall Caps				

## Dimensions



EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside



# EV130



## Indoor Unit




## G4 Performance

Airflow CF	ESP in H <sub>2</sub> O	Temp EFF%	Total EFF% Winter/Summer*
52	0.70	83	75/60
69	0.60	80	72/57
94	0.50	76	67/52
113	0.40	73	64/48
132	0.30	70	60/44
141	0.20	68	59/43
148	0.10	67	57/41


\* (See HVI certification report on page 66 for complete certified rating)

## Dimensions



# EV200

## Indoor Unit




## G4 Performance



Airflow CF	ESP in H <sub>2</sub> O	Temp EFF%	Total EFF% Winter/Summer*
122	0.70	82	74/59
149	0.65	80	72/56
168	0.50	79	70/55
176	0.40	78	69/54
186	0.30	77	68/53
192	0.20	77	68/52
200	0.10	76	67/52

\* (See HVI certification report on page 66 for complete certified rating)

## Dimensions



**EA:** Exhaust Air to outdoors  
**OA:** Outdoor Air intake  
**RA:** Room Air to be exhausted  
**FA:** Fresh Air to inside



## Specification

Ventilation Type: Static Plate, Heat and Humidity Transfer				
Typical Airflow Range: 100-200 CFM				
Number Motors: One, 0.1 hp				
V	Hz	Phase	Input Watts	FLA
120	60	Single	157 @ 181 CFM	1.5
Control Voltage: 24 VAC				
Filters: MERV 8, spun polyester media. 10 1/2" x 21 3/4" x 1"				
Weight: 70 lbs (unit), 82 lbs (in carton)				
Shipping Dimensions: 21 1/2"W x 32)L x 29"H				
Options: PTL - Percentage Timer Control PBL - Push Button Point-of-Use Controls FM - Percentage Timer Control with Furnace Interlock DH24 - Dehumidistat Control Wall Caps				

# EV300

## Indoor Unit




## G4 Performance



Airflow CF	ESP in H <sub>2</sub> O	Temp EFF%	Total EFF% Winter/Summer*
155	1.0	80	70/51
199	0.9	76	67/48
249	0.8	72	62/44
268	0.7	71	61/42
289	0.6	69	58/39
300	0.5	68	57/38
310	0.4	67	56/37

\* (See HVI certification report on page 66 for complete certified rating)

## Dimensions



**EA:** Exhaust Air to outdoors  
**OA:** Outdoor Air intake  
**RA:** Room Air to be exhausted  
**FA:** Fresh Air to inside




## Specification

Ventilation Type: Static Plate, Heat and Humidity Transfer				
Typical Airflow Range: 150-300 CF				
Number Motors: One, 0.2 hp				
V	Hz	Phase	Input Watts	FLA
120	60	Single	310 @ 293 CFM	3.3
Control Voltage: 24 VAC				
Filters: MERV 8, spun polyester media. 10 1/2" x 21 3/4" x 1"				
Weight: 72 lbs (unit), 85 lbs (in carton)				
Shipping Dimensions: 21 1/2"W x 32)L x 29"H				
Options: PTL - Percentage Timer Control PBL - Push Button Point-of-Use Controls FM - Percentage Timer Control with Furnace Interlock DH24 - Dehumidistat Control 8" Wall Caps				



# COMMERCIAL INDOOR PRODUCTS

- Horizontal and vertical configuration
- Wide range of airflow and static capacities
- AHRI certified performance data for efficiency and cross leakage
- UL tested flammability and smoke generation that meets NFPA 90A and 90B test standards for commercial applications.
- Easy installation and service.
- Ten year core warranty.

RenewAire means *Trouble-Free ERV*.




FRONT VIEW



FROM INTERIOR SPACES OR  
SCHEDULED EXHAUST, SUCH AS  
BATHROOMS OR LOCKER ROOMS.

HEAT AND/OR AC UNITARY PRODUCT  
(FURNACE, AIR HANDLER, FANCOIL,  
GEOTHERMAL HEATPUMP)

EA: Exhaust Air to outdoors  
OA: Outdoor Air intake  
RA: Room Air to be exhausted  
FA: Fresh Air to inside



# Packaged Indoor Energy Recovery Ventilators: EV450IN, HE1XIN, HE2XIN, HE3XIN, HE4XIN, HE6XIN, HE8XIN

## Part I - General

### A. Product Specification

1. Energy Recovery Ventilator (ERV) shall be a packaged unit as manufactured by RenewAire and shall transfer both heat and humidity using static plate core technology.

### B. Quality Assurance

1. The energy recovery cores used in these products shall be third party Certified by AHRI under its Standard 1060 for Energy Recovery Ventilators. AHRI published certifications shall confirm manufacturer's published performance for airflow, static pressure, temperature and total effectiveness, purge air (OACF) and exhaust air leakage (EATR). Products that are not currently AHRI Certified will not be accepted

2. Manufacturer shall be able to provide evidence of independent testing of the core by Underwriters Laboratory (UL), verifying a maximum flame spread index (FSI) of 25 and a maximum smoke developed index (SDI) of 50 thereby meeting NFPA 90A and NFPA 90B requirements for materials in a compartment handling air intended for circulation through a duct system. The method of test shall be UL Standard 723.

3. Unit shall be Listed under UL 1812 Standard for Ducted Air to Air Heat Exchangers. (Note that a few low volume product or product configurations are not U Listed.)

4. The ERV core shall be warranted to be free of manufacturing defects and to retain its functional characteristics, under circumstances of normal use, for a period of ten years from the date of purchase. The balance-of-unit shall be warranted to be free of manufacturing defects and to retain its functional characteristics, under circumstances of normal use, for a period of two years from the date of purchase.

## Part II - Performance

### A. Energy Transfer

The ERV shall be capable of transferring both sensible and latent energy between airstreams. Latent energy transfer shall be accomplished by direct water vapor transfer from one airstream to the other, without exposing transfer media in succeeding cycles directly to the exhaust air and then to the fresh air.

### B. Passive Frost Control

The ERV core shall perform without condensing or frosting under normal operating conditions (defined as outside temperatures above -10°F and inside relative humidity below 40%). Occasional more extreme conditions shall not affect the usual function, performance or durability of the core. No condensate drains will be allowed.

### C. Continuous Ventilation

Unit shall have the capacity to operate continuously without the need for bypass, recirculation, pre-heaters or defrost cycles under normal operating conditions.

### D. Positive Airstream Separation

Water vapor transfer shall be through molecular transport by hydroscopic resin and shall not be accomplished by "porous plate" mechanisms. Exhaust and fresh airstreams shall travel at all times in separate passages and airstreams shall not mix.

### E. Laminar Flow

Airflow through the ERV core shall be laminar over the products entire operating airflow range, avoiding deposition of particulates on the interior of the energy exchange plate material.

## Part III - Product

### A. Construction

1. The energy recovery component shall be of fixed-plate cross-flow construction, with no moving parts.

2. No condensate drain pans or drains shall be allowed and unit shall be capable of operating in both winter and summer conditions without generating condensate.

3. The unit case shall be constructed of G90 galvanized, 20-gauge steel, with lapped corners and zinc plated screw fasteners.

4. Access doors shall provide easy access to blowers, ERV cores and filters. Doors shall have an airtight compression seal using closed cell foam gaskets.

5. Case walls and doors shall be insulated with 1 inch, 4 pound density, foil/scrim faced, high-density fiberglass board insulation, providing a cleanable surface and eliminating the possibility of exposing the fresh air to glass fibers.

6. The ERV cores shall be protected by a MERV-8 rated, 2" nominal, pleated, disposable filter in both airstreams

7. Unit shall have single-point power connection and a single-point 24 VAC contactor control connection (except Inverter Ready units that have terminal connections for an independent inverter for each airstream).

8. Blower motors shall be EPACT compliant for energy efficiency and be thermally protected or supplied with external starters.

9. Blowers shall be quiet running, forward curve type and be either direct drive or belt drive. HE6X and HE8X units use backward incline, belt drive blower packages. Belt drive motors shall be provided with adjustable pulleys and motor mounts allowing for proper belt tensioning.

### B. Options (*Select options based on application requirements.*)

1. Provide unit and duct connection orientation per project schedule.

2. Provide double wall construction with 24-gauge galvanized steel liner.

3. Units are available single or three phase at a full range of operating voltages. See project schedule.

4. Provide motor horsepower as specified in project schedule

5. Provide "inverter-ready" units which include shielded power wiring and terminal connections for inverters (inverters provided and installed by others).

6. Provide factory installed fused disconnects.

7. Provide factory installed non-fused disconnects.

8. Provide factory installed transformer/relay package to supply a 24 VAC power source.

9. Provide factory installed filter monitors for each airstream

# EV450IN



## Indoor Unit



## G5 Performance

Airflow CFM	ESP in H <sub>2</sub> O	Watts		Temp EFF%	Total EFF% Winter/Summer*
		1P	3P		
225	1.25	335	181	81	76/66
338	1.00	420	278	77	71/61
380	0.90	470	340	75	69/59
450	0.65	550	430	73	66/56
540	0.25	640	540	70	62/52
575	0.00	690	610	69	61/51
600	-0.25	735	664	68	60/50

\*At AHRI 1060 standard conditions



(See certified data on page 67 for core components.)

## Specification

Ventilation Type: Static Plate, Heat and Humidity Transfer			
Typical Airflow Range: 200-500 CF			
AHRI 1060 Certified Core: One L8			
Airflow Rating Points (for AHRI): 450 CFM and 338 CFM			
Motors: One, 0.6 hp (Single Phase) One, 0.5hp (Three Phase)			
V	Hz	Phase	FLA
115	60	Single	7.0
208-230	60	Single	3.5
277	60	Single	2.4
208-230	60	Three	1.7-1.5
460	60	Three	0.8
Control Voltage: 24 VAC			
Filters: Two total, MERV 8, 2" pleated, 14" x 20" nominal size			
Weight: 141 lbs (unit), 160 lbs (in carton), up to 3 units on 50 lb pallet			
Shipping Dimensions: 37 1/2" W x 48" L x 17" H			
Options: 45EVHB - Hanging Bracket, Foot Kit 45EVDF - Rectangular 12" x 8" Flange Kit (2 in kit) 45EVT10 - 10" Round Transition Kit (2 in kit)			

# EV45OIN UNIT DIMENSIONS

EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside



# HE1XINH


AHRI CERTIFIED™



## Indoor Unit



## G5 Performance



\*At AHRI 1060 standard conditions  
(See certified data on page 67 for core components.)

## Specification


Ventilation Type: Static Plate, Heat and Humidity Transfer					
Typical Airflow Range: 250-925 CF					
AHRI 1060 Certified Core: One L125-0					
Airflow Rating Points (for AHRI): 750 CFM and 560 CFM					
Number Motors: Two					
V	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size
115	60	Single	8.6	19.4	25
208-230	60	Single	4.3	9.7	15
277	60	Single	2.4	5.4	15
208-230	60	Three	2.1	5.2	15
460	60	Three	1.1	2.6	15
Control Voltage: 24 VAC					
Filters: Two total, MERV 8, 2" pleated, 20" x 20" nominal size					
Weight: 211 lbs (unit), 250 lbs (shipping weight)					
Shipping Dimensions: 44" W x 56" L x 27" H					

## Airflow Performance

Motor HP Phase	External Static Pressure (Inches Water Column)						
	0.0	0.25	0.5	0.75	1.0	1.25	1.5
0.75 (Two DD) Single Phase	970 CFM 1,490 Watts	925 CFM 1,375 Watts	860 CFM 1,270 Watts	795 CFM 1,160 Watts	720 CFM 1,030 Watts	635 CFM 950 Watts	350 CFM 750 Watts
0.75 (Two DD) Three Phase	1,030 CFM 1,220 Watts	1,010 CFM 1,210 Watts	975 CFM 1,160 Watts	880 CFM 1,050 Watts	800 CFM 990 Watts	700 CFM 850 Watts	530 CFM 720 Watts

## HE1XINH UNIT DIMENSIONS

EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside




# HE1XINV


AHRI CERTIFIED™



## Indoor Unit



## G5 Performance



\*At AHRI 1060 standard conditions  
(See certified data on page 67 for core components.)

## Specification


Ventilation Type: Static Plate, Heat and Humidity Transfer					
Typical Airflow Range: 250-925 CF					
AHRI 1060 Certified Core: One L125-0					
Airflow Rating Points (for AHRI): 750 CFM and 560 CFM					
Number Motors: Two					
V	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size
115	60	Single	8.6	19.4	25
208-230	60	Single	4.3	9.7	15
277	60	Single	2.4	5.4	15
208-230	60	Three	2.1	5.2	15
460	60	Three	1.1	2.6	15
Control Voltage: 24 VAC					
Filters: Two total, MERV 8, 2" pleated, 20" x 20" nominal size					
Weight: 211 lbs (unit), 250 lbs (shipping weight)					
Shipping Dimensions: 44" W x 56" L x 27" H					

## Airflow performance


Motor HP Phase	External Static Pressure (Inches Water Column)						
	0.0	0.25	0.5	0.75	1.0	1.25	1.5
0.75 (Two DD) Single Phase	970 CFM 1,490 Watts	925 CFM 1,375 Watts	860 CFM 1,270 Watts	795 CFM 1,160 Watts	720 CFM 1,030 Watts	635 CFM 950 Watts	350 CFM 750 Watts
0.75 (Two DD) Three Phase	1,030 CFM 1,220 Watts	1,010 CFM 1,210 Watts	975 CFM 1,160 Watts	880 CFM 1,050 Watts	800 CFM 990 Watts	700 CFM 850 Watts	530 CFM 720 Watts

## HE1XINV UNIT DIMENSIONS


EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside




TOP VIEW



RIGHT VIEW



FRONT VIEW




LEFT  
VIEW


# HE2XINH



## Indoor Unit



## G5 Performance



\*At AHRI 1060 standard conditions  
(See certified data on page 67 for core components.)

## Specification

Ventilation Type: Static Plate, Heat and Humidity Transfer						
Typical Airflow Range: 500-2,000 CFM						
AHRI 1060 Certified Core: Two L125-00						
Airflow Rating Points (for AHRI): 1,500 CFM and 1,120 CFM						
Number Motors: Direct Drive (DD) Four, Belt Drive (BD) Two						
Drive HP	Volts	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size
DD 0.75	115	60	Single	8.6	36.6	45
	208-230	60	Single	4.3	18.3	20
	277	60	Single	2.4	10.2	15
	208-230	60	Three	2.1	9.8	15
	460	60	Three	1.1	4.9	15
BD 1.5	208-230	60	Single	9.3-9.0	20.9	30
	208-230	60	Three	4.8-4.8	10.8	15
	460	60	Three	2.4	5.4	15
	575	60	Three	1.8	4.1	15
BD 2	208-230	60	Single	11.3-10.5	25.4	35
	208-230	60	Three	6.2-6.2	14.0	20
	460	60	Three	3.1	7.0	15
	575	60	Three	2.3	5.2	15
Control Voltage: 24 VAC						
Filters: Four total, MERV 8, 2" pleated, 20" x 20" nominal size						
Weight: 414 lbs (unit), 420 lbs (shipping weight)						
Shipping Dimensions: 50" W x 62" L x 41" H						


## Airflow performance

Motor HP	Blower RPM Nominal	Turns Open	External Static Pressure (Inches Water Column)												
			0.0		0.25		0.5		0.75		1.0		1.25		
0.75 (Four DD) Single Phase	N/A N/A	N/A N/A	1,950 CFM 2,240 Watts	1,830 CFM 2,155 Watts	1,670 CFM 2,020 Watts	1,400 CFM 1,795 Watts	1,150 CFM 1,490 Watts	700 CFM 1,190 Watts	- -	- -	- -	- -	- -	- -	
0.75 (Four DD) Three Phase	N/A N/A	N/A N/A	1,960 CFM 2,500 Watts	1,840 CFM 2,300 Watts	1,700 CFM 2,125 Watts	1,600 CFM 1,900 Watts	1,380 CFM 1,700 Watts	1,190 CFM 1,500 Watts	800 CFM 1,260 Watts						
			CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	
1.5 (BD)	1,000	4.5	1,378 0.5	1,175 0.5	900 0.4	635 0.4	- -	- -	- -	- -	- -	- -	- -	- -	
	1,230	2	1,694 0.9	1,550 0.9	1,335 0.8	1,125 0.7	1,000 0.7	500 0.6	- -	- -	- -	- -	- -	- -	
	1,420	0	1,956 1.4	1,850 1.4	1,680 1.2	1,475 1.2	1,300 1.1	1,200 1.1	930	0.9					
2 (BD)	1,220	4.5	1,681 0.9	1,530 0.9	1,315 0.7	1,100 0.7	975 0.6	- -	- -	- -	- -	- -	- -	- -	
	1,470	2	2,025 1.6	1,925 1.5	1,750 1.4	1,575 1.3	1,375 1.2	1,275 1.2	1,125 1.1	1,475 1.0					
	1,660	0	- -	- -	2,000 2.0	1,900 1.9	1,750 1.8	1,570 1.7	1,475 1.7						

Note: Brake Horse Power (BHP) is for one blower motor package only.

## HE2XINH UNIT DIMENSIONS

EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside



# HE2XINV


AHRI CERTIFIED™



## Indoor Unit



## G5 Performance



\*At AHRI 1060 standard conditions  
(See certified data on page 67 for core components.)

## Specification

Ventilation Type: Static Plate, Heat and Humidity Transfer						
Typical Airflow Range: 500-2,000 CFM						
AHRI 1060 Certified Core: Two L125-00						
Airflow Rating Points (for AHRI): 1,500 CFM and 1,120 CFM						
Number Motors: Direct Drive (DD) Four, Belt Drive (BD) Two						
Drive HP	Volts	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size
DD 0.75	115	60	Single	8.6	36.6	45
	208-230	60	Single	4.3	18.3	20
	277	60	Single	2.4	10.2	15
	208-230	60	Three	2.1	9.8	15
	460	60	Three	1.1	4.9	15
BD 1.5	208-230	60	Single	9.3-9.0	20.9	30
	208-230	60	Three	4.8-4.8	10.8	15
	460	60	Three	2.4	5.4	15
	575	60	Three	1.8	4.1	15
	208-230	60	Single	11.3-10.5	25.4	35
BD 2	208-230	60	Three	6.2-6.2	14.0	20
	460	60	Three	3.1	7.0	15
	575	60	Three	2.3	5.2	15
Control Voltage: 24 VAC						
Filters: Four total, MERV 8, 2" pleated, 20" x 20" nominal size						
Weight: 399 lbs (unit), 420 lbs (shipping weight)						
Shipping Dimensions: 48" W x 62" L x 55" H						


## Airflow Performance

Motor HP	Blower RPM Nominal	Turns Open	External Static Pressure (Inches Water Column)							
			0.0	0.25	0.5	0.75	1.0	1.25	1.5	
0.75 (Four DD) Single Phase	N/A N/A	N/A N/A	1,870 CFM 2,160 Watts	1,720 CFM 2,070 Watts	1,520 CFM 1,900 Watts	1,290 CFM 1,715 Watts	1,080 CFM 1,505 Watts	700 CFM 1,210 Watts	- -	
0.75 (Four DD) Three Phase	N/A N/A	N/A N/A	1,870 CFM 2,500 Watts	1,720 CFM 2,300 Watts	1,540 CFM 2,125 Watts	1,350 CFM 1,950 Watts	1,240 CFM 1,730 Watts	1,030 CFM 1,490 Watts	800 CFM 1,240 Watts	
			CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP
1.5 (BD)	1,000	4.5	1,378	0.5	1,175	0.5	900	0.4	635	0.4
	1,230	2	1,694	0.9	1,550	0.9	1,335	0.8	1,125	0.7
	1,420	0	1,956	1.4	1,850	1.4	1,680	1.2	1,475	1.2
2 (BD)	1,220	4.5	1,681	0.9	1,530	0.9	1,315	0.7	1,100	0.7
	1,470	2	2,025	1.6	1,925	1.5	1,750	1.4	1,575	1.3
	1,660	0	-	-	-	-	2,000	2.0	1,900	1.9

Note: Brake Horse Power (BHP) is for one blower motor package only.


## HE2XINV UNIT DIMENSIONS

EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside




LEFT END VIEW  
BELT DRIVE

TOP VIEW and Service Area



LEFT END VIEW  
DIRECT DRIVE

Note: All duct flanges are 14" x 24".




RIGHT END VIEW  
DIRECT DRIVE


# HE3XINH



## Indoor Unit



## G5 Performance



\*At AHRI 1060 standard conditions  
(See certified data on page 67 for core components.)

## Specification



Ventilation Type: Static Plate, Heat and Humidity Transfer						
Typical Airflow Range: 750-3,300 CF						
AHRI 1060 Certified Core: Three L125-00						
Airflow Rating Points (for AHRI): 2,250 CFM and 1,690 CFM						
Number Motors: Two						
HP	Volts	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size
2	208-230 208-230 460 575	60 60 60 60	Single Three Three Three	11.3-10.5 6.2-6.2 3.1 2.3	25.4 14.0 7.0 5.2	35 20 15 15
3	208-230 208-230 460 575	60 60 60 60	Single Three Three Three	13.7 9.2-8.6 4.3 3.2	30.8 20.7 9.7 7.2	45 30 15 15
5	208-230 460 575	60 60 60	Three Three Three	14.0-13.0 6.5 5.0	31.5 14.6 11.3	45 20 15
Control Voltage: 24 VAC						
Filters: Six total, MERV 8, 2" pleated, 20" x 20" nominal size						
Weight: 675 lbs (unit), 700 lbs (shipping weight)						
Shipping Dimensions: 72" W x 84" L x 46" H						

## Airflow performance


Motor HP	Blower RPM Nominal	Turns Open	External Static Pressure (Inches Water Column)											
			0.0		0.25		0.5		0.75		1.0		1.25	
			CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP
2	1,095	4	2,040	1.3	1,760	1.3	1,370	1.2	920	1.1	-	-	-	-
	1,220	2	2,340	1.5	2,110	1.4	1,790	1.3	1,380	1.2	940	1.2	-	-
	1,340	0	2,590	1.8	2,370	1.7	2,130	1.6	1,760	1.4	1,310	1.3	980	1.2
3	1,345	4.5	2,420	2.3	2,280	2.2	2,090	2.1	1,760	2.0	1,280	1.9	860	1.9
	1,535	2	2,850	2.8	2,760	2.7	2,570	2.6	2,380	2.5	2,090	2.4	1,810	2.2
	1,685	0	-	-	-	-	-	-	2,660	2.9	2,470	2.7	2,280	2.6
5	1,495	6.5	2,850	3.1	2,710	3.0	2,520	2.9	2,280	2.8	2,040	2.7	1,620	2.5
	1,675	3.5	3,280	3.8	3,140	3.7	2,990	3.5	2,800	3.3	2,610	3.1	2,380	2.9
	1,855	0	-	-	-	-	3,470	4.9	3,330	4.7	3,140	4.5	3,040	4.4

## HE3XINH UNIT DIMENSIONS

EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside



Note: There are two 12" x 12" discharges.




# HE3XINV


AHRI CERTIFIED™



## Indoor Unit



## G5 Performance




## Specification

Ventilation Type: Static Plate, Heat and Humidity Transfer						
Typical Airflow Range: 750-3,300 CF						
AHRI 1060 Certified Core: Three L125-00						
Airflow Rating Points (for AHRI): 2,250 CFM and 1,690 CFM						
Number Motors: Two						
HP	Volts	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size
2	208-230 208-230 460 575	60 60 60 60	Single Three Three Three	11.3-10.5 6.2-6.2 3.1 2.3	25.4 14.0 7.0 5.2	35 20 15 15
3	208-230 208-230 460 575	60 60 60 60	Single Three Three Three	13.7 9.2-8.6 4.3 3.2	30.8 20.7 9.7 7.2	45 30 15 15
5	208-230 460 575	60 60 60	Three Three Three	14.0-13.0 6.5 5.0	31.5 14.6 11.3	45 20 15
Control Voltage: 24 VAC						
Filters: Six total, MERV 8, 2" pleated, 20" x 20" nominal size						
Weight: 640 lbs (unit), 675 lbs (shipping weight)						
Shipping Dimensions: 45" W x 70" L x 70" H						


## Airflow Performance

Motor HP	Blower RPM Nominal	Turns Open	External Static Pressure (Inches Water Column)											
			0.0		0.25		0.5		0.75		1.0		1.25	
			CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP
2	1,095	4	1,900	1.3	1,600	1.2	1,250	1.2	850	1.1	-	-	-	-
	1,220	2	2,200	1.5	1,960	1.4	1,610	1.3	1,240	1.3	860	1.2	-	-
	1,340	0	2,300	1.7	2,160	1.6	1,950	1.5	1,580	1.4	1,150	1.3	800	1.2
3	1,345	4.5	2,400	2.2	2,250	2.2	1,970	2.1	1,570	2.0	1,170	1.9	900	1.8
	1,535	2	2,720	2.7	2,450	2.5	2,250	2.4	1,950	2.3	1,650	2.2	1,200	2.0
	1,685	0	-	-	2,870	3.0	2,740	2.9	2,540	2.8	2,340	2.7	2,090	2.5
5	1,495	6.5	2,850	2.7	2,610	2.6	2,380	2.5	2,090	2.4	1,710	2.2	1,330	2.1
	1,675	3.5	3,230	3.7	3,090	3.5	2,850	3.3	2,610	3.1	2,380	2.9	2,090	2.7
	1,855	0	3,520	4.5	3,370	4.3	3,230	4.1	3,090	3.9	2,850	3.6	2,610	3.4


## HE3XINV UNIT DIMENSIONS




Top View



Left View



Front View




Right View

# HE4XINH


AHRI CERTIFIED™



## Indoor Unit



## G5 Performance



## Specification


Ventilation Type: Static Plate, Heat and Humidity Transfer						
Typical Airflow Range: 1,000-4,400 CF						
AHRI 1060 Certified Core: Four L125-0						
Airflow Rating Points (for AHRI): 3,000 CFM and 2,250 CFM						
Number Motors: Two						
HP	Volts	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size
2	208-230 208-230 460 575	60 60 60 60	Single Three Three Three	11.3-10.5 6.2-6.2 3.5 2.3	25.4 14.0 7.9 5.2	35 20 15 15
3	208-230 208-230 460 575	60 60 60 60	Single Three Three Three	13.7 9.2-8.6 4.3 3.2	30.8 20.7 9.7 7.2	45 30 15 15
5	208-230 460 575	60 60 60	Three Three Three	14.0-13.0 6.5 5.0	31.5 14.6 11.3	45 20 15
Control Voltage: 24 VAC						
Filters: Eight total, MERV 8, 2" pleated, 20" x 20" nominal size						
Weight: 846 lbs (unit), 900 lbs (shipping weight)						
Shipping Dimensions: 84" W x 92" L x 46" H						

## Airflow Performance

Motor HP	Blower RPM Nominal	Turns Open	External Static Pressure (Inches Water Column)											
			0.0		0.25		0.5		0.75		1.0		1.25	
			CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP
2	1,010	4.5	2,489	0.9	2,200	0.9	1,715	0.8	1,100	0.7	-	-	-	-
	1,210	2	2,995	1.6	2,290	1.5	2,430	1.4	2,005	1.3	1,540	1.2	-	-
	1,370	0	-	-	-	-	-	-	2,600	2.0	2,215	1.9	1,800	1.7
3	1,345	4.5	3,295	2.1	3,145	2.1	2,840	2.0	2,509	1.9	2,116	1.8	1,747	1.6
	1,535	2	3,832	2.9	3,682	2.9	3,480	2.8	3,170	2.6	2,839	2.4	2,449	2.3
	1,685	0	-	-	-	-	-	-	-	3,409	3.0	3,003	2.8	2,465
5	1,495	6	3,718	2.7	3,568	2.6	3,345	2.6	3,030	2.4	2,686	2.2	2,301	2.1
	1,675	3	4,223	3.8	4,083	3.7	3,943	3.6	3,659	3.4	3,364	3.2	2,994	2.9
	1,855	0	-	-	-	-	-	-	4,287	4.9	4,011	4.6	3,760	4.3

## HE4XNH UNIT DIMENSIONS

EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside




# HE4XINV


AHRI CERTIFIED™



## Indoor Unit



## G5 Performance



\*At AHRI 1060 standard conditions  
(See certified data on page 67 for core components.)

## Specification


Ventilation Type: Static Plate, Heat and Humidity Transfer						
Typical Airflow Range: 1,000-4,400 CF						
AHRI 1060 Certified Core: Four L125-0						
Airflow Rating Points (for AHRI): 3,000 CFM and 2,250 CFM						
Number Motors: Two						
HP	Volts	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size
2	208-230 208-230 460 575	60 60 60 60	Single Three Three Three	11.3-10.5 6.2-6.2 3.5 2.3	25.4 14.0 7.9 5.2	35 20 15 15
3	208-230 208-230 460 575	60 60 60 60	Single Three Three Three	13.7 9.2-8.6 4.3 3.2	30.8 20.7 9.7 7.2	45 30 15 15
5	208-230 460 575	60 60 60	Three Three Three	14.0-13.0 6.5 5.0	31.5 14.6 11.3	45 20 15
Control Voltage: 24 VAC						
Filters: Eight total, MERV 8, 2" pleated, 20" x 20" nominal size						
Weight: 815 lbs (unit), 875 lbs (shipping weight)						
Shipping Dimensions: 45" W x 90" L x 70" H						

## Airflow Performance


Motor HP	Blower RPM Nominal	Turns Open	External Static Pressure (Inches Water Column)											
			0.0		0.25		0.5		0.75		1.0		1.25	
			CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP
2	1,010	4.5	2,300	0.9	1,810	0.8	1,300	0.7	-	-	-	-	-	-
	1,210	2	2,800	1.5	2,350	1.4	1,950	1.3	1,500	1.3	1,050	1.2	-	-
	1,370	0	3,068	2.2	2,754	2.0	2,430	1.9	2,082	1.8	1,725	1.7	1,342	1.6
3	1,345	4.5	3,042	2.0	2,705	1.9	2,341	1.8	1,983	1.7	1,611	1.6	1,211	1.5
	1,535	2	3,452	2.7	3,226	2.6	2,955	2.5	2,696	2.3	2,422	2.2	2,093	2.0
	1,685	0	-	-	-	-	-	-	3,148	2.9	2,884	2.8	2,595	2.6
5	1,495	6	3,348	2.7	3,114	2.6	2,820	2.4	2,549	2.3	2,268	2.2	1,917	2.1
	1,675	3	3,896	3.9	3,688	3.7	3,466	3.6	3,232	3.4	2,972	3.2	2,694	3.0
	1,855	0	-	-	-	-	4,229	4.9	3,979	4.6	3,700	4.3	3,430	4.0

## HE4XINV UNIT DIMENSIONS


EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside




Top View



Left View



Front View



Right View


# HE6XIN

AHRI CERTIFIED™

## Indoor Unit



## G5 Performance



\*At AHRI 1060 standard conditions  
(See certified data on page 67 for core components.)

## Specification


Ventilation Type: Static Plate, Heat and Humidity Transfer						
Typical Airflow Range: 1,500-6,500 CFM						
AHRI 1060 Certified Core: Six L125-0						
Airflow Rating Points (for AHRI): 4,500 CFM and 3,375 CFM						
Number Motors: Two						
HP	Volts	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size
5	208-230 460 575	60	Three Three Three	14.2-13.0 6.5 5.0	32.6 14.9 11.3	45 20 15
7.5	208-230 460 575	60	Three Three Three	20.9-19.2 9.6 7.6	47.0 21.6 17.1	70 30 25
Control Voltage: 24 VAC						
Filters: Twelve total, MERV 8, 2" pleated, 20" x 20" nominal size						
Weight: 2,340 lbs (unit), 2,640 lbs (shipping weight)						
Shipping Dimensions: 85" W x 114" L x 85" H						

## Airflow performance

Motor HP	Blower RPM Nominal	Turns Open	External Static Pressure (Inches Water Column)											
			0.0		0.25		0.5		0.75		1.0		1.25	
			CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP
5	1,460	4.5	5,005	3.2	4,800	3.2	4,650	3.1	4,475	3.0	4,200	2.9	4,000	2.8
	1,610	2	5,550	4.2	5,375	4.2	5,250	4.1	5,100	4.1	4,900	4.0	4,650	3.9
	1,725	0	-	-	-	-	-	-	5,525	5.0	5,475	5.0	5,200	4.9
7.5	1,560	4.5	5,275	3.7	5,200	3.6	4,900	3.5	4,775	3.5	4,550	3.4	4,350	3.3
	1,740	2	5,950	5.0	5,825	5.0	5,625	4.9	5,490	4.9	5,325	4.8	5,125	4.7
	1,865	0	6,500	6.5	6,350	6.5	6,225	6.4	6,125	6.4	5,910	6.3	5,825	6.2

## HE6XIN UNIT DIMENSIONS

EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside




# HE8XIN

AHRI CERTIFIED™

## Indoor Unit



## G5 Performance



\*At AHRI 1060 standard conditions  
(See certified data on page 67 for core components.)

## Specification


Ventilation Type: Static Plate, Heat and Humidity Transfer						
Typical Airflow Range: 2,000-8,000 CFM						
AHRI 1060 Certified Core: Eight L125-0						
Airflow Rating Points (for AHRI): 6,000 CFM and 4,500 CFM						
Number Motors: Two						
HP	Volts	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size
5	208-230 460 575	60 60 60	Three Three Three	14.2-13.0 6.5 5.0	32.6 14.9 11.3	45 20 15
7.5	208-230 460 575	60 60 60	Three Three Three	20.9-19.2 9.6 7.6	47.0 21.6 17.1	70 30 25
10	208-230 460 575	60 60 60	Three Three Three	29.0-26.8 13.4 10.0	65.3 30.2 22.5	90 45 35
Control Voltage: 24 VAC						
Filters: Sixteen total, MERV 8, 2" pleated, 20" x 20" nominal size						
Weight: 2,525 lbs (unit), 2,825 lbs (shipping weight)						
Shipping Dimensions: 85" W x 114" L x 85" H						

## Airflow performance

Motor HP	Blower RPM Nominal	Turns Open	External Static Pressure (Inches Water Column)											
			0.0		0.25		0.5		0.75		1.0		1.25	
			CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP
5	1,460	4.5	5,575	3.2	5,425	3.2	5,200	3.2	5,000	3.2	4,775	3.1	4,550	3.0
	1,610	2	6,200	4.3	6,010	4.3	5,875	4.2	5,700	4.2	5,500	4.2	5,325	4.1
	1,725	0.5	6,550	5.0	6,380	5.0	6,210	5.0	6,100	5.0	5,880	4.9	5,730	4.8
7.5	1,560	4.5	6,000	3.9	5,850	3.9	5,650	3.8	5,475	3.8	5,275	3.8	5,100	3.7
	1,740	2	6,700	5.3	6,575	5.3	6,400	5.3	6,300	5.3	6,125	5.3	5,950	5.2
	1,865	0	-	-	-	-	-	-	6,800	7.5	6,675	7.5	6,500	7.5
10	1,810	4.5	7,000	6.1	6,875	6.1	6,750	6.1	6,600	6.0	6,425	6.0	6,275	6.0
	2,020	2	7,850	8.5	7,745	8.5	7,625	8.5	7,450	8.4	7,350	8.4	7,200	8.3
	2,105	1	-	-	-	-	7,950	9.6	7,800	9.6	7,725	9.6	7,600	9.5

## HE8XIN UNIT DIMENSIONS


EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside



# COMMERCIAL OUTDOOR PRODUCTS

- Many airflow orientation options
- Weatherized cabinets with hoods for outdoor applications.
- Wide range of airflow and static capacities
- Easy installation and service.
- AHRI certified performance data for efficiency and cross leakage
- UL tested flammability and smoke generation that meets NFPA 90A and 90B test standards for commercial applications.
- Ten year core warranty.

RenewAire means *Trouble-Free ERV*.



Contact RenewAire for other application schematics.

# Packaged Rooftop Energy Recovery Ventilators: EV450RT, HE1XRT, HE2XRT, HE3XRT, HE4XRT, HE6XRT & HE8XRT

## Part I - General

### A. Product Specification

1. Energy Recovery Ventilator (ERV) shall be a packaged unit as manufactured by RenewAire and shall transfer both heat and humidity using static plate core technology.

### B. Quality Assurance

1. The energy recovery cores used in these products shall be third party Certified by AHRI under its Standard 1060 for Energy Recovery Ventilators. AHRI published certifications shall confirm manufacturer's published performance for airflow, static pressure, temperature and total effectiveness, purge air (OACF) and exhaust air leakage (EATR). Products that are not currently AHRI Certified will not be accepted.

2. Manufacturer shall be able to provide evidence of independent testing of the core by Underwriters Laboratory (UL), verifying a maximum flame spread index (FSI) of 25 and a maximum smoke developed index (SDI) of 50 thereby meeting NFPA 90A and NFPA 90B requirements for materials in a compartment handling air intended for circulation through a duct system. The method of test shall be UL Standard 723.

3. Unit shall be Listed under UL 1812 Standard for Ducted Air to Air Heat Exchangers (Note that a few low volume product or product configurations are not UL Listed). Units intended for "Outdoor Use" shall be listed using the specific UL requirements for rain penetration, corrosion protection and seal durability and shall be so labeled.

4. The ERV core shall be warranted to be free of manufacturing defects and to retain its functional characteristics, under circumstances of normal use, for a period of ten years from the date of purchase. The balance-of-unit shall be warranted to be free of manufacturing defects and to retain its functional characteristics, under circumstances of normal use, for a period of two years from the date of purchase.

## Part II - Performance

### A. Energy Transfer

The ERV shall be capable of transferring both sensible and latent energy between airstreams. Latent energy transfer shall be accomplished by direct water vapor transfer from one airstream to the other, without exposing transfer media in succeeding cycles directly to the exhaust air and then to the fresh air.

### B. Passive Frost Control

The ERV core shall perform without condensing or frosting under normal operating conditions (defined as outside temperatures above -10°F and inside relative humidity below 40%). Occasional more extreme conditions shall not affect the usual function, performance or durability of the core. No condensate drains will be allowed.

### C. Continuous Ventilation

Unit shall have the capacity to operate continuously without the need for bypass, recirculation, pre-heaters or defrost cycles under normal operating conditions.

### D. Positive Airstream Separation

Water vapor transfer shall be through molecular transport by hydroscopic resin and shall not be accomplished by "porous plate" mechanisms. Exhaust and fresh airstreams shall travel at all times in separate passages, and airstreams shall not mix.

### E. Laminar Flow

Airflow through the ERV core shall be laminar over the products entire operating airflow range, avoiding deposition of particulates on the interior of the energy exchange plate material.

## Part III - Product

### A. Construction

1. The energy recovery component shall be of fixed-plate cross-flow construction, with no moving parts.

2. No condensate drain pans or drains shall be allowed and unit shall be capable of operating in both winter and summer conditions without generating condensate.

3. The unit case shall be constructed of G90 galvanized, 20-gauge steel, with lapped corners and zinc plated screw fasteners. The unit roof shall be one piece or have watertight standing seam joints and shall overlap wall panels and doors in order to positively shed water.

4. Access doors shall provide easy access to blowers, ERV cores and filters. Doors shall have an airtight compression seal using closed cell foam gaskets rated for outdoor exposure.

5. Weatherhoods shall be screened to exclude birds and animals. Inlet weatherhoods shall be sized to maintain inlet velocities below 500 fpm, and equipped with rain excluder baffles.

6. Case walls and doors shall be insulated with 1 inch, 4 pound density, foil/scrim faced, high-density fiberglass board insulation, providing a cleanable surface and eliminating the possibility of exposing the fresh air to glass fibers

7. The ERV cores shall be protected by a MERV-8 rated, 2" nominal, pleated, disposable filter in both airstreams

8. Unit shall have single-point power connection and a single-point 24 VAC contactor control connection (Except Inverter Ready units that have terminal connections for an independent inverter for each airstream).

9. Blower motors shall be EPACT compliant for energy efficiency and be thermally protected or supplied with external starters.

10. Blowers shall be quiet running, forward curve type and be either direct drive or belt drive. HE6X and HE8X units use backward incline, belt drive blower packages. Belt drive motors shall be provided with adjustable pulleys and motor mounts allowing for proper belt tensioning.

### B. Options (Select options based on application requirements)

1. Provide unit and duct connection orientation per project schedule.

2. Provide double wall construction with 24-gauge galvanized steel liner.

3. Units are available single or three phase at a full range of operating voltages. See project schedule.

4. Provide motor horsepower as specified in project schedule

5. Provide "inverter-ready" units which include shielded power wiring and terminal connections for inverters (inverters provided and installed by others).

6. Provide factory installed fused disconnects.

7. Provide factory installed non-fused disconnects.

8. Provide factory installed transformer/relay package to supply a 24VAC power source.

9. Provide factory installed filter monitors for each airstream

10. Provide 14 inch high, non-pitched roof curbs as available from the factory. Pitched curbs, vibration curbs, seismic curbs and other custom curbs are available directly from curb manufacturer.


11. RTC (RoofTop Connect) units shall have return air and fresh air ducts configured to permit direct tie-in to rooftop air handlers using factory offered transition piece. (See separate specification for factory transition availability.)

12. Provide high wind tie-down kit.

# EV450RT



## Outdoor Unit




## G5 Performance

Airflow CFM	ESP in H <sub>2</sub> O	Watts 1P	Watts 3P	Temp EFF%	Total EFF% Winter/Summer*
240	1.00	425	243	80	75/66
338	0.85	474	313	77	71/61
380	0.75	496	345	75	69/59
450	0.50	534	412	73	66/56
500	0.25	563	461	71	64/54
550	0.00	593	516	70	62/52
600	-0.25	623	572	68	60/50

\*At AHRI 1060 standard conditions  
(See certified data on page 67 for core components.)


## Dimensions




# EV450RT

## APPLICATION OPTIONS


### RTV




EV450RT WITH STANDARD ROOF CURB  
(45CURB)




TOP VIEW  
STANDARD ROOF CURB (14" HIGH)



### RTR/RTF





EV450RT WITH ADAPTER  
(45RTRF) AND CURB (45CURB)  
IN RTR CONFIGURATION



EV450RT WITH ADAPTER  
(45RTRF) AND CURB (45CURB)  
IN RTF CONFIGURATION

For horizontal connection of either the Fresh Air duct or the Return Air duct, stack the optional RTF/RTR Adapter on the Standard Roof Curb.  
Duct openings to be field cut into adapter. Opening location and size is flexible

### RTC/RTH



EV450RT WITH ADAPTER (45RTCH)

The RTH/RTC Adapter allows horizontal connection of both the Fresh Air and the Return Air ducts. It is also possible to connect the adapter directly to the return plenum of most Rooftop Units (openings must be cut into RTU). Duct openings to be field cut into adapter.  
Opening location and size is flexible.


EA: Exhaust Air to outdoors  
OA: Outdoor Air intake  
RA: Room Air to be exhausted  
FA: Fresh Air to inside

# HE1XRT


AHRI CERTIFIED™

**UL**  
LISTED  
DUCTED HEAT  
RECOVERY VENTILATOR  
89S5

## Outdoor Unit



## G5 Performance



\*At AHRI 1060 standard conditions  
(See certified data on page 67 for core components.)

## Specification

Ventilation Type: Static Plate, Heat and Humidity Transfer					
Typical Airflow Range: 250-870 CF					
AHRI 1060 Certified Core: One L125-0					
Airflow Rating Points (for AHRI): 750 CFM and 560 CFM					
Number Motors: Two					
V	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size
115	60	Single	8.6	19.4	25
208-230	60	Single	4.3	9.7	15
277	60	Single	2.4	5.4	15
208-230	60	Three	2.1	5.2	15
460	60	Three	1.1	2.6	15
Control Voltage: 24 VAC					
Filters: Two total, MERV 8, 2" pleated, 20" x 20" nominal size					
Weight: 250 lbs (unit), 330 lbs (shipping weight)					
Shipping Dimensions: 31" W x 76" L x 45" H					
Options: Controls (see pages 64 & 65) Roof curb Alternate duct connections					

## Base Type/Airflow Orientations




## Airflow Performance

Motor HP Phase	External Static Pressure (Inches Water Column)						
	0.0	0.25	0.5	0.75	1.0	1.25	1.5
0.75 (Two DD) Single Phase	950 CFM 1,630 Watts	880 CFM 1,550 Watts	820 CFM 1,475 Watts	775 CFM 1,430 Watts	730 CFM 1,385 Watts	650 CFM 1,300 Watts	540 CFM 1,200 Watts
0.75 (Two DD) Three Phase	950 CFM 1,200 Watts	880 CFM 1,100 Watts	820 CFM 1,020 Watts	760 CFM 980 Watts	660 CFM 890 Watts	560 CFM 800 Watts	450 CFM 700 Watts

# HEIXRT UNIT DIMENSIONS


EA: Exhaust Air to outdoors  
OA: Outdoor Air intake  
RA: Room Air to be exhausted  
FA: Fresh Air to inside




# HE1XRTC



## Outdoor Unit



## G5 Performance



## Specification


Ventilation Type: Static Plate, Heat and Humidity Transfer																																				
Typical Airflow Range: 500-1,000 CFM																																				
AHRI 1060 Certified Core: One L125-0																																				
Airflow Rating Points (for AHRI): 750 CFM and 560 CFM																																				
Number Motors: Two																																				
<table border="1"> <thead> <tr> <th>V</th> <th>Hz</th> <th>Phase</th> <th>FLA</th> <th>Min. Cir. Amps</th> <th>Max. Fuse Size</th> </tr> </thead> <tbody> <tr> <td>115</td> <td>60</td> <td>Single</td> <td>8.6</td> <td>19.4</td> <td>25</td> </tr> <tr> <td>208-230</td> <td>60</td> <td>Single</td> <td>4.3</td> <td>9.7</td> <td>15</td> </tr> <tr> <td>277</td> <td>60</td> <td>Single</td> <td>2.4</td> <td>5.4</td> <td>15</td> </tr> <tr> <td>208-230</td> <td>60</td> <td>Three</td> <td>2.1</td> <td>5.2</td> <td>15</td> </tr> <tr> <td>460</td> <td>60</td> <td>Three</td> <td>1.1</td> <td>2.6</td> <td>15</td> </tr> </tbody> </table>	V	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size	115	60	Single	8.6	19.4	25	208-230	60	Single	4.3	9.7	15	277	60	Single	2.4	5.4	15	208-230	60	Three	2.1	5.2	15	460	60	Three	1.1	2.6	15
V	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size																															
115	60	Single	8.6	19.4	25																															
208-230	60	Single	4.3	9.7	15																															
277	60	Single	2.4	5.4	15																															
208-230	60	Three	2.1	5.2	15																															
460	60	Three	1.1	2.6	15																															
Control Voltage: 24 VAC																																				
Filters: Two total, MERV 8, 2" pleated, 20" x 20" nominal size																																				
Weight: 300 lbs (unit), 375 lbs (shipping weight)																																				
Shipping Dimensions: 40" W x 87" L x 45" H																																				

## Airflow Performance

Damper Position	Total Watts		Static Pressure in Adjacent Air Handler (Inches Water Column)									
			-0.5		-0.25		0.0		+0.25		+0.5	
	1 Phase	3 Phase	EA	FA	EA	FA	EA	FA	EA	FA	EA	FA
100% Open	1,295	1,155	855	1,035	900	985	950	940	985	885	1,045	835
65% Open	1,285	1,140	785	980	820	945	855	900	890	855	935	810
55% Open	1,275	1,130	775	965	805	920	840	875	865	835	900	790
45% Open	1,265	1,120	750	920	775	875	805	935	830	790	860	750
35% Open	1,265	1,110	695	860	730	820	760	775	790	740	820	700
25% Open	1,265	1,100	625	780	660	750	685	715	715	680	750	650
15% Open	1,260	1,085	575	585	615	630	650	665	685	705	730	745

## HE1XRTC UNIT DIMENSIONS

EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside



# HE2XRT


AHRI CERTIFIED™



## Outdoor Unit



## G5 Performance




\*At AHRI 1060 standard conditions  
(See certified data on page 67 for core components)

## Specification

Ventilation Type: Static Plate, Heat and Humidity Transfer						
Typical Airflow Range: 500-2,000 CF						
AHRI 1060 Certified Core: Two L125-00						
Airflow Rating Points (for AHRI): 1,500 CFM and 1,120 CFM						
Number Motors: Direct Drive (DD) Four, Belt Drive (BD) Two						
Drive HP	Volts	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size
DD 0.75	115 208-230 277 208-230 460	60 60 60 60	Single Single Single Three Three	8.6 4.3 2.4 2.1 1.1	36.6 18.3 10.2 9.8 4.9	45 20 15 15 15
BD 1.5	208-230 208-230 460 575	60 60 60 60	Single Three Three Three	9.3-9.0 4.8-4.8 2.4 1.8	20.9 10.8 5.4 4.1	30 15 15 15
BD 2	208-230 208-230 460 575	60 60 60 60	Single Three Three Three	11.3-10.5 6.2-6.2 3.1 2.3	25.4 14.0 7.0 5.2	35 20 15 15
Control Voltage: 24 VAC						
Filters: Four total, MERV 8, 2" pleated, 20" x 20" nominal size						
Weight: 488 lbs (unit), 525 lbs (shipping weight)						
Shipping Dimensions: 51" W x 76" L x 45" H						

## Base Type/Airflow Orientations




## Airflow Performance

Motor HP	Blower RPM Nominal	Turns Open	External Static Pressure (Inches Water Column)								
			0.0	0.25	0.5	0.75	1.0	1.25	1.5		
0.75 (Four DD) Single Phase	N/A N/A	N/A N/A	1,770 CFM 2,220 Watts	1,680 CFM 2,145 Watts	1,555 CFM 2,015 Watts	1,375 CFM 1,825 Watts	1,110 CFM 1,560 Watts	760 CFM 1,195 Watts	- -		
0.75 (Four DD) Three Phase	N/A N/A	N/A N/A	1,760 CFM 2,300 Watts	1,670 CFM 2,200 Watts	1,550 CFM 2,050 Watts	1,375 CFM 1,825 Watts	1,120 CFM 1,530 Watts	850 CFM 1,375 Watts	500 CFM 950 Watts		
			CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	
1.5 (BD)	1,000 1,230 1,420	4.5 2 0	1,378 0.5 1,694 0.9 1,956 1.4	0.5 0.9 1.4	1,175 0.5 1,550 0.9 1,850 1.4	0.4 0.8 1.2	900 0.4 1,335 0.8 1,680 1.2	635 0.4 1,125 0.7 1,475 1.2	- - 1,000 0.7 1,300 1.1	- - 500 0.6 1,200 1.1	- - - - 930 0.9
2 (BD)	1,220 1,470 1,660	4.5 2 0	1,681 0.9 2,025 1.6 - -	0.9 1.6 - -	1,530 0.9 1,925 1.5 - -	0.7 1.4 - -	1,315 0.7 1,750 1.4 2,000 2.0	1,100 0.7 1,575 1.3 1,900 1.9	975 0.6 1,375 1.2 1,750 1.8	430 0.6 1,275 1.2 1,570 1.7	- - 1,125 1.1 1,475 1.7

Note: Brake Horse Power (BHP) is for one blower motor package only.

HE2XRT  
UNIT DIMENSIONS


EA: Exhaust Air to outdoors  
OA: Outdoor Air intake  
RA: Room Air to be exhausted  
FA: Fresh Air to inside




# HE2XRTC



## Outdoor Unit



## G5 Performance



\*At AHRI 1060 standard conditions  
(See certified data on page 67 for core components)

## Specification


Ventilation Type: Static Plate, Heat and Humidity Transfer						
Typical Airflow Range: 1,000-1,700 CF						
AHRI 1060 Certified Core: Two L125-00						
Airflow Rating Points (for AHRI): 1,500 CFM and 1,120 CFM						
Number Motors: Two, Belt Drive						
HP	Volts	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size
BD 2	208-230	60	Single	11.3-10.5	25.4	35
BD 2	208-230 460 575	60	Three	6.2-6.2 3.1 2.3	14.0 7.0 5.2	20 15 15
Control Voltage: 24 VAC						
Filters: Four total, MERV 8, 2" pleated, two 20" x 20" nominal size, and two 14" x 20" nominal size						
Weight: 538 lbs (unit), 575 lbs (shipping weight)						
Shipping Dimensions: 51" W x 76" L x 45" H						

## Airflow performance

	Blower RPM Nominal	Turns Open	Static Pressure in Adjacent Air Handler (Inches Water Column)							
			-0.5		-0.25		0.0		+0.25	
			CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP
Exhaust Air	1,420	0	1,700	1.8	1,850	1.9	-	-	-	-
	1,360	1	1,540	1.7	1,720	1.8	1,860	1.9	1,920	2.0
	1,300	2	1,375	1.5	1,600	1.7	1,740	1.8	1,800	1.8
	1,240	3	1,240	1.4	1,440	1.6	1,625	1.7	1,690	1.7
	1,180	4	1,080	1.3	1,300	1.4	1,500	1.5	1,575	1.6
Fresh Air	1,675	0	-	-	-	-	1,630	2.0	1,575	2.0
	1,595	1	1,720	2.0	1,620	2.0	1,530	1.9	1,440	1.8
	1,515	2	1,630	1.9	1,520	1.8	1,430	1.8	1,355	1.7
	1,435	3	1,530	1.8	1,430	1.7	1,320	1.7	1,250	1.6
	1,355	4	1,415	1.6	1,310	1.6	1,225	1.5	1,150	1.5

## HE2XRTC UNIT DIMENSIONS

EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside




# HE3XRT


AHRI CERTIFIED™



## Outdoor Unit



## G5 Performance




\*At AHRI 1060 standard conditions  
(See certified data on page 67 for core components)

## Specification

Ventilation Type: Static Plate, Heat and Humidity Transfer						
Typical Airflow Range: 750-3,000 CF						
AHRI 1060 Certified Core: Three L125-00						
Airflow Rating Points (for AHRI): 2,250 CFM and 1,690 CFM						
Number Motors: Two						
HP	Volts	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size
2	208-230	60	Single	11.3-10.5	25.4	35
	208-230	60	Three	6.2-6.2	14.0	20
	460	60	Three	3.1	7.0	15
	575	60	Three	2.3	5.2	15
3	208-230	60	Single	13.7	30.8	45
	208-230	60	Three	9.2-8.6	20.7	30
	460	60	Three	4.3	9.7	15
	575	60	Three	3.2	7.2	15
5	208-230	60	Three	14.0-13.0	31.5	45
	460	60	Three	6.5	14.6	20
	575	60	Three	5.0	11.3	15
Control Voltage: 24 VAC						
Filters: Six total, MERV 8, 2" pleated, 20" x 20" nominal size						
Weight: 726 lbs (unit), 755 lbs (shipping weight)						
Shipping Dimensions: 72" W x 84" L x 49" H						

## Base Type/Airflow Orientations




## Airflow Performance

Motor HP	Blower RPM Nominal	Turns Open	External Static Pressure (Inches Water Column)											
			0.0		0.25		0.5		0.75		1.0		1.25	
			CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP
2	1,095	4	2,040	1.3	1,760	1.3	1,370	1.2	920	1.1	-	-	-	-
	1,220	2	2,340	1.5	2,110	1.4	1,790	1.3	1,380	1.2	940	1.2	-	-
	1,340	0	2,590	1.8	2,370	1.7	2,130	1.6	1,760	1.4	1,310	1.3	980	1.2
3	1,345	4.5	2,420	2.3	2,280	2.2	2,090	2.1	1,760	2.0	1,280	1.9	860	1.9
	1,535	2	2,850	2.8	2,760	2.7	2,570	2.6	2,380	2.5	2,090	2.4	1,810	2.2
	1,685	0	-	-	-	-	-	-	2,660	2.9	2,470	2.7	2,280	2.6
5	1,495	6.5	2,850	3.1	2,710	3.0	2,520	2.9	2,280	2.8	2,040	2.7	1,620	2.5
	1,675	3.5	3,280	3.8	3,140	3.7	2,990	3.5	2,800	3.3	2,610	3.1	2,380	2.9
	1,855	0	-	-	-	-	3,470	4.9	3,330	4.7	3,140	4.5	3,040	4.4

HE3XRT  
UNIT DIMENSIONS


EA: Exhaust Air to outdoors  
OA: Outdoor Air intake  
RA: Room Air to be exhausted  
FA: Fresh Air to inside




# HE3XRTC



## Outdoor Unit



## G5 Performance



## Specification


Ventilation Type: Static Plate, Heat and Humidity Transfer						
Typical Airflow Range: 1,700-2,500 CF						
AHRI 1060 Certified Core: Three L125-00						
Airflow Rating Points (for AHRI): 2,250 CFM and 1,690 CFM						
Number Motors: Two						
HP	Volts	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size
3	208-230	60	Single	13.7-13.7	30.8	45
3	208-230 460 575	60	Three	9.2-8.6 4.4 3.2	20.7 9.9 7.2	30 15 15
Control Voltage: 24 VAC						
Filters: Five total, MERV 8, 2" pleated, three 20" x 20" and two 16" x 25" nominal size						
Weight: 775 lbs (unit), 830 lbs (shipping weight)						
Shipping Dimensions: 72" W x 84" L x 50" H						

## Airflow Performance

Blower RPM Nominal	Turns Open	Static Pressure in Adjacent Air Handler (Inches Water Column)									
		-0.5		-0.25		0.0		+0.25		+0.5	
		CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP
Exhaust Air	1,520	0	-	-	-	-	-	-	-	-	-
	1,465	1	2,130	2.9	-	-	-	-	-	-	-
	1,405	2	2,000	2.5	2,245	2.8	2,455	3.0	-	-	-
	1,345	3	1,915	2.3	2,135	2.6	2,345	2.7	2,475	2.8	2,575
	1,285	4	1,725	1.8	1,950	2.1	2,180	2.3	2,345	2.4	2,455
Fresh Air	1,800	0	2,565	3.0	2,385	2.9	2,225	2.8	2,065	2.7	1,830
	1,740	1	2,480	2.8	2,290	2.7	2,150	2.6	1,975	2.5	1,740
	1,680	2	2,375	2.6	2,210	2.5	2,070	2.4	1,910	2.3	1,645
	1,620	3	2,290	2.4	2,125	2.4	1,990	2.3	1,825	2.1	1,555
	1,560	4	2,200	2.1	2,040	2.1	1,910	2.0	1,725	1.9	1,450

# HE3XRTC UNIT DIMENSIONS

EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside




# HE4XRT


AHRI CERTIFIED™



## Outdoor Unit



## G5 Performance




\*At AHRI 1060 standard conditions  
(See certified data on page 67 for core components)

## Specification

Ventilation Type: Static Plate, Heat and Humidity Transfer						
Typical Airflow Range: 1,000-4,400 CFM						
AHRI 1060 Certified Core: Four L125-0						
Airflow Rating Points (for AHRI): 3,000 CFM and 2,250 CFM						
Number Motors: Two						
HP	Volts	Hz	Phase	FLA		Min. Cir. Amps
2	208-230	60	Single	11.3-10.5	25.4	35
	208-230	60	Three	6.2-6.2	14.0	20
	460	60	Three	3.5	7.9	15
	575	60	Three	2.3	5.2	15
3	208-230	60	Single	13.7	30.8	45
	208-230	60	Three	9.2-8.6	20.7	30
	460	60	Three	4.3	9.7	15
	575	60	Three	3.2	7.2	15
5	208-230	60	Three	14.0-13.0	31.5	45
	460	60	Three	6.5	14.6	20
	575	60	Three	5.0	11.3	15
Control Voltage: 24 VAC						
Filters: Eight total, MERV 8, 2" pleated, 20" x 20" nominal size						
Weight: 915 lbs (unit), 1,000 lbs (shipping weight)						
Shipping Dimensions: 84" W x 92" L x 49" H						

## Base Type/Airflow Orientations




## Airflow performance

Motor HP	Blower RPM Nominal	Turns Open	External Static Pressure (Inches Water Column)											
			0.0		0.25		0.5		0.75		1.0		1.25	
			CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP
2	1,010	4.5	2,489	0.9	2,200	0.9	1,715	0.8	1,100	0.7	-	-	-	-
	1,210	2	2,995	1.6	2,290	1.5	2,430	1.4	2,005	1.3	1,540	1.2	-	-
	1,370	0	-	-	-	-	-	-	2,600	2.0	2,215	1.9	1,800	1.7
3	1,345	4.5	3,295	2.1	3,145	2.1	2,840	2.0	2,509	1.9	2,116	1.8	1,747	1.6
	1,535	2	3,832	2.9	3,682	2.9	3,480	2.8	3,170	2.6	2,839	2.4	2,449	2.3
	1,685	0	-	-	-	-	-	-	-	-	3,409	3.0	3,003	2.8
5	1,495	6	3,718	2.7	3,568	2.6	3,345	2.6	3,030	2.4	2,686	2.2	2,301	2.1
	1,675	3	4,223	3.8	4,083	3.7	3,943	3.6	3,659	3.4	3,364	3.2	2,994	2.9
	1,855	0	-	-	-	-	-	-	4,287	4.9	4,011	4.6	3,760	4.3

# HE4XRT UNIT DIMENSIONS

EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside




# HE4XRTC


AHRI CERTIFIED™



## Outdoor Unit



## G5 Performance



\*At AHRI 1060 standard conditions  
(See certified data on page 67 for core components)

## Specification


Ventilation Type: Static Plate, Heat and Humidity Transfer						
Typical Airflow Range: 2,500-3,700 CF						
AHRI 1060 Certified Core: Four L125-0						
Airflow Rating Points (for AHRI): 3,000 CFM and 2,250 CFM						
Number Motors: Two						
HP	Volts	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size
5	208-230 460 575	60	Three Three Three	14.0-13.0 6.5 5.0	31.5 14.6 11.3	45 20 15
Control Voltage: 24 VAC						
Filters: Six total, MERV 8, 2" pleated, four 20" x 20", and two 16" x 25" nominal size						
Weight: 965 lbs (unit), 1,050 lbs (shipping weight)						
Shipping Dimensions: 84" W x 92" L x 50" H						

## Airflow performance


	Blower RPM Nominal	Turns Open	Static Pressure in Adjacent Air Handler (Inches Water Column)								
			-0.5		-0.25		0.0		+0.25		+0.5
			CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM
Exhaust Air	1,600	0	3,700	3.6	4,000	3.8	4,250	4.3	-	-	-
	1,555	1	3,575	3.5	3,900	3.6	4,220	3.9	4,325	4.3	4,380
	1,515	2	3,415	3.2	3,740	3.5	4,135	3.8	4,275	4.2	4,340
	1,470	3	3,235	2.9	3,600	3.2	4,000	3.6	4,215	4.0	4,300
	1,430	4	3,085	2.7	3,455	3.0	3,820	3.2	4,140	3.6	4,260
	1,385	5	2,980	2.5	3,280	2.7	3,640	2.9	3,985	3.2	4,170
	1,340	6	2,880	2.3	3,135	2.5	3,475	2.7	3,840	2.9	4,080
Fresh Air	1,805	1	-	-	-	-	-	-	-	-	3,210
	1,755	2	-	-	-	-	3,410	4.9	3,190	4.6	3,110
	1,705	3	3,710	5.0	3,585	4.9	3,310	4.5	3,130	4.2	3,010
	1,655	4	3,600	4.8	3,470	4.6	3,210	4.2	3,030	3.8	2,910
	1,605	5	3,510	4.3	3,335	4.1	3,110	3.7	2,920	3.4	2,800
	1,555	6	3,400	3.9	3,220	3.8	3,010	3.4	2,810	3.2	2,710

# HE4XRTC UNIT DIMENSIONS


EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside




Front View




Right View



Top View



Left View



Back View


# HE6XRT

AHRI CERTIFIED™

## Outdoor Unit



## G5 Performance



## Specification

Ventilation Type: Static Plate, Heat and Humidity Transfer							
Typical Airflow Range: 1,500-6,500 CF							
AHRI 1060 Certified Core: Six L125-0							
Airflow Rating Points (for AHRI): 4,500 CFM and 3,375 CFM							
Number Motors: Two							
HP	Volts	Hz	Phase	FLA		Min. Cir. Amps	Max. Fuse Size
5	208-230	60	Three	14.2-13.0	32.6	45	
	460	60	Three	6.5	14.9	20	
	575	60	Three	5.0	11.3	15	
7.5	208-230	60	Three	20.9-19.2	47.0	70	
	460	60	Three	9.6	21.6	30	
	575	60	Three	7.6	17.1	25	
Control Voltage: 24 VAC							
Filters: Twelve total, MERV 8, 2" pleated, 20" x 20" nominal size							
Weight: 2,340 lbs (unit), 2,640 lbs (shipping weight)							
Shipping Dimensions: 85" W x 114" L x 85" H							

## Base Type/Airflow Orientations







## Airflow Performance

Motor HP	Blower RPM Nominal	Turns Open	External Static Pressure (Inches Water Column)											
			0.0		0.25		0.5		0.75		1.0		1.25	
			CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP
5	1,460	4.5	5,005	3.2	4,800	3.2	4,650	3.1	4,475	3.0	4,200	2.9	4,000	2.8
	1,610	2	5,550	4.2	5,375	4.2	5,250	4.1	5,100	4.1	4,900	4.0	4,650	3.9
	1,725	0	-	-	-	-	-	-	5,525	5.0	5,475	5.0	5,200	4.9
7.5	1,560	4.5	5,275	3.7	5,200	3.6	4,900	3.5	4,775	3.5	4,550	3.4	4,350	3.3
	1,740	2	5,950	5.0	5,825	5.0	5,625	4.9	5,490	4.9	5,325	4.8	5,125	4.7
	1,865	0	6,500	6.5	6,350	6.5	6,225	6.4	6,125	6.4	5,910	6.3	5,825	6.2

# HE6XRT UNIT DIMENSIONS

EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside

Curb Cross Section (Typical for All)




# HE8XRT

AHRI CERTIFIED™

## Outdoor Unit



## G5 Performance




\*At AHRI 1060 standard conditions  
(See certified data on page 67 for core components)

## Specification

Ventilation Type: Static Plate, Heat and Humidity Transfer						
Typical Airflow Range: 2,000-8,000 CF						
AHRI 1060 Certified Core: Eight L125-0						
Airflow Rating Points (for AHRI): 6,000 CFM and 4,500 CFM						
Number Motors: Two						
HP	Volts	Hz	Phase	FLA	Min. Cir. Amps	Max. Fuse Size
5	208-230 460 575	60	Three Three Three	14.2-13.0 6.5 5.0	32.6 14.9 11.3	45 20 15
7.5	208-230 460 575	60	Three Three Three	20.9-19.2 9.6 7.6	47.0 21.6 17.1	70 30 25
10	208-230 460 575	60	Three Three Three	29.0-26.8 13.4 10.0	65.3 30.2 22.5	90 45 35
Control Voltage: 24 VAC						
Filters: Sixteen total, MERV 8, 2" pleated, 20" x 20" nominal size						
Weight: 2,730 lbs (unit), 3,080 lbs (shipping weight)						
Shipping Dimensions: 85" W x 114" L x 85" H						

## Base Type/Airflow Orientations



## Airflow Performance

Motor HP	Blower RPM Nominal	Turns Open	External Static Pressure (Inches Water Column)											
			0.0		0.25		0.5		0.75		1.0		1.25	
			CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP	CFM	BHP
5	1,460	4.5	5,575	3.2	5,425	3.2	5,200	3.2	5,000	3.2	4,775	3.1	4,550	3.0
	1,610	2	6,200	4.3	6,010	4.3	5,875	4.2	5,700	4.2	5,500	4.2	5,325	4.1
	1,725	0.5	6,550	5.0	6,380	5.0	6,210	5.0	6,100	5.0	5,880	4.9	5,730	4.8
7.5	1,560	4.5	6,000	3.9	5,850	3.9	5,650	3.8	5,475	3.8	5,275	3.8	5,100	3.7
	1,740	2	6,700	5.3	6,575	5.3	6,400	5.3	6,300	5.3	6,125	5.3	5,950	5.2
	1,865	0	-	-	-	-	-	-	6,800	7.5	6,675	7.5	6,500	7.5
10	1,810	4.5	7,000	6.1	6,875	6.1	6,750	6.1	6,600	6.0	6,425	6.0	6,275	6.0
	2,020	2	7,850	8.5	7,745	8.5	7,625	8.5	7,450	8.4	7,350	8.4	7,200	8.3
	2,105	1	-	-	-	-	7,950	9.6	7,800	9.6	7,725	9.6	7,600	9.5




# APPLIED PRODUCTS

- Cost effective energy recovery for virtually any air handling system.
- Field assembled into air handling systems or integrated in custom packaged air handlers.
- Unlimited airflow capacity .
- Flexible installation and easy servicing.
- AHRI certified performance data for efficiency and cross leakage
- UL tested flammability and smoke generation that meets NFPA 90A and 90B test standards for commercial applications.
- Ten year core warranty.

RenewAire means *Trouble-Free ERV*.

## Installation Example

Central Air Handler using CA4X and exhaust and make-up air blowers.  
(CA-Series provide side service access and a “side-by-side” airflow arrangement.)



Similar designs can use PA-Series arrays.  
(PA-Series provide top service access and an “over-under” airflow arrangement.)

# CA & PA Series Applied Energy Recovery Ventilators: CA2X, CA3X, CA4X, PA6X, PA9X, PA8X & PA12X

## Part I - General

### A. Product Specification

1. Energy Recovery Ventilator (ERV) shall be a packaged unit as manufactured by RenewAire and shall transfer both heat and humidity using static plate core technology.

### B. Quality Assurance

1. The energy recovery cores used in these products shall be third party Certified by AHRI under its Standard 1060 for Energy Recovery Ventilators. AHRI published certifications shall confirm manufacturer's published performance for airflow, static pressure, temperature and total effectiveness, purge air (OACF) and exhaust air leakage (EATR). Products that are not currently AHRI Certified will not be accepted.
2. The energy recovery core shall be a UL Listed Component complying to UL Standard 723. Manufacturer shall be able to provide evidence of independent testing of the core by Underwriters Laboratory (UL), verifying a maximum flame spread index (FSI) of 25 and a maximum smoke developed index (SDI) of 50 thereby meeting NFPA 90A and NFPA 90B requirements for materials in a compartment handling air intended for circulation through a duct system.

3. The ERV core shall be warranted to be free of manufacturing defects and to retain its functional characteristics, under circumstances of normal use, for a period of ten years from the date of purchase. The balance-of-unit shall be warranted to be free of manufacturing defects and to retain its functional characteristics, under circumstances of normal use, for a period of two years from the date of purchase.

## Part II - Performance

### A. Energy Transfer

The ERV shall be capable of transferring both sensible and latent energy between airstreams. Latent energy transfer shall be accomplished by direct water vapor transfer from one airstream to the other, without exposing transfer media in succeeding cycles directly to the exhaust air and then to the fresh air.

### B. Passive Frost Control

The ERV core shall perform without condensing or frosting under normal operating conditions (defined as outside temperatures above -10°F and inside relative humidity below 40%). Occasional more extreme conditions shall not affect the usual function, performance or durability of the core. No condensate drains will be allowed.

### C. Continuous Ventilation

Unit shall have the capacity to operate continuously without the need for bypass, recirculation, pre-heaters or defrost cycles under normal operating conditions.

### D. Positive Airstream Separation

Water vapor transfer shall be through molecular transport by hydroscopic resin and shall not be accomplished by "porous plate" mechanisms. Exhaust and fresh airstreams shall travel at all times in separate passages, and airstreams shall not mix.

### E. Laminar Flow

Airflow through the ERV core shall be laminar over the products entire operating airflow range, avoiding deposition of particulates on the interior of the energy exchange plate material.

## Part III - Product

### A. Construction

1. The energy recovery component shall be of fixed-plate cross-flow construction, with no moving parts.
2. No condensate drain pans or drains shall be allowed and unit shall be capable of operating in both winter and summer conditions without generating condensate.

3. The unit case shall be constructed of G90 galvanized, 20-gauge steel, with lapped corners and zinc plated screw fasteners.

4. Access doors shall provide easy access to ERV cores and filters. Doors shall have an airtight compression seal using closed cell foam gaskets.

5. Case walls and doors shall be insulated with 1 inch, 4 pound density, foil/scrim faced, high-density fiberglass board insulation, providing a cleanable surface and eliminating the possibility of exposing the fresh air to glass fibers. PA-Series bottom panels shall be insulated with  $\frac{1}{4}$  inch sheet rubber insulation.

6. The ERV cores shall be protected by a MERV-8 rated, 2" nominal, pleated, disposable filter in both airstreams

7. CA-Series cabinet construction shall allow stacking of units up to three cabinets high for larger airflow applications. Hinged and latched access doors will be provided on each end of the unit.

8. PA-Series shall use RenewAire patented modular vertical stack of cores (US Patent 5,660,228) allowing assembly of unlimited sizes of ERV systems. Latched access doors are provided on the top of each unit.

### B. Options (Select options based on application requirements)

1. Provide unit and duct connection orientation per project schedule.
2. Provide double wall construction with 24-gauge galvanized steel liner (CA-Series only).
3. CA and PA-Series units are available pre-assembled on a structural steel base.

## Part IV - Installation

### A. Unit Location

1. Locate and orient unit to provide the shortest and most straight duct connections. Provide service clearances as indicated on the plans. Locate system blowers (provided by others) distant from sound critical occupancies.

2. Provide a poured concrete equipment pad for all floor mounted units. The pad thickness, and floor plan dimensions to be determined based on the unit selected, and site structural considerations.

3. Provide a structurally suitable support for the base of any wall mounted or hung units.

### B. Vibration Isolation

1. No moving parts are allowed in the ERV modular assemblies.

### C. Duct Design

1. All ductwork shall be designed, constructed, supported and sealed in accordance with SMACNA HVAC Duct Construction Standards and pressure classifications

2. At a minimum all duct runs to the outdoors shall be thermally insulated at levels appropriate to the local climate. A continuous vapor barrier shall also be provided on warm surface of the insulation.

### D. Sound Control

1. The ERV cores shall act as flow straighteners and sound attenuators. This attribute can be used to isolate mechanical noise from blowers and other mechanical equipment from sound critical occupancies.

### E. Test and Balancing


1. Test and Balancing may not begin until 100% of the installation is complete and fully functional.

2. Follow National Comfort Institute (NCI) air test and balance procedures specific to Heat Recovery Ventilator Balancing Procedure including standard reports to the owner's representative.



# CA-SERIES

AHRI CERTIFIED™

Indoor Unit - Up to 20,000 CFM in Stacked Arrays




## G5 Performance




## Specification

Ventilation Type: Static Plate, Heat and Humidity Transfer			
Insulated sheet metal cabinets with energy exchange cores and filters			
Individual CA-Series units or stacks of units can be built into larger air handling systems.			
Blower not included and must be specified to meet job requirements			
Description	CA2X	CA3X	CA4X
Typical Airflow Range CF	500-2,200	750-3,300	1,000-4,400
AHRI 1060 Certified Cor	Two L125-00	Three L125-00	Four L125-00
Airflow Rating points (for AHRI)	1,500 and 1,120 CFM	2,250 and 1,690 CFM	3,000 and 2,250 CFM
Unit Weight	225 lbs	325 lbs	400 lbs
Shipping Weight	275 lbs	375 lbs	475 lbs
Filters: MERV 8, 2" pleated 20" x 20" nominal size	Four Total	Six Total	Eight Total
Shipping Dimensions: CA2X - 40" W x 48" L x 41" H CA3X - 40" W x 67" L x 41" H CA4X - 40" W x 87" L x 41" H			
Insulation: One inch, high density, FSK faced, fiberglass			



\*At AHRI 1060 standard conditions  
(See certified data on page 66 for core components)

## Airflow Performance




## CA-SERIES UNIT DIMENSIONS

	CA2X	CA3X	CA4X
A	42"	62"	81 5/8"
B	14"	24"	32"
C	111"	130"	149"
D	77"	96"	116"
E	5-5/8"	5-5/8"	7-5/8"
F	19 3/4"	29 5/8"	39 3/4"


### Available Options:

Double Wall Construction


EA: Exhaust Air to outdoors  
 OA: Outdoor Air intake  
 RA: Room Air to be exhausted  
 FA: Fresh Air to inside




Top View



End View



Left View



Right View

Note: Filters are provided for installation in any two of the locations shown, depending on which duct connections are selected for inlets.  
 Filters are 2" x 20" x 20" pleated disposable.



# PA-SERIES

AHRI CERTIFIED™


## Indoor Unit - Unlimited Airflow in Multiple Arrays



## G5 Performance





## Airflow performance



## Specification

Ventilation Type: Static Plate, Heat and Humidity Transfer				
Insulated sheet metal panels easily slide into receivers to enclose stacks of energy exchange cores using unique patented design, US Patent 5,660,228				
Individual PA-Series units can be joined together to provide unlimited airflow capacities for larger air handling systems.				
Blower not included and must be specified to meet job requirements				
Description	PA6X	PA8X	PA9X	PA12X
Typical Airflow Range CFM	1,500-6,600	2,000-8,800	2,250-9,900	3,000-13,200
AHRI 1060 Certified Core	Six L125-00	Eight L125-00	Nine L125-00	Twelve L125-00
Airflow Rating Points (for AHRI)	4,500 and 3,375 CFM	6,000 and 4,500 CFM	6,750 and 5,062 CFM	9,000 and 6,750 CFM
Unit Weight	565 lbs	695 lbs	800 lbs	980 lbs
Shipping Weight	650 lbs	900 lbs	990 lbs	1,180 lbs
Filters: MERV 8, 2" pleated, 20" x 20" nominal size PA6X - 12 Total                                    PA9X - 18 Total PA8X - 16 Total                                    PA12X - 24 Total				
Insulation: One inch, high density, FSK faced, fiberglass				




\*At AHRI 1060 standard conditions  
(See certified data on page 66 for core components)


## PA-SERIES UNIT DIMENSIONS

	PA6X	PA9X	PA8X	PA12X
A	73 1/4"	109 1/2"	73 1/4"	109 1/2"
D	72 3/4"	109"	72 3/4"	109"
E	28"	28"	37"	37"
F	1-1/2"	1-1/2"	3-1/8"	3-1/8"
G	66-1/4"	66-1/4"	86"	86"
APPROX. WEIGHT	565	810	700	1000


PA-6X/8X




PA-9X/12X



Top View




Side View



Available Options:  
Knockdown  
Assembled on structural  
forklift base

EA: Exhaust Air to outdoors  
OA: Outdoor Air intake  
RA: Room Air to be exhausted  
FA: Fresh Air to inside

Available Airflow Arrangements  
(Side Views)



**Performance Derating:**

Airflow arrangements 3 & 4 result in lower energy transfer.  
Reduce sensible effectiveness by 2 percentage points.  
Reduce total effectiveness by 1 percentage point.

# COMMERCIAL CONTROLS & INTERCONNECTION OPTIONS

These controls are intended to turn RenewAire commercial energy recovery ventilation systems on and off at appropriate times. Specification, installation and set-up is an easy process. RenewAire units should be ordered with the 24 volt contactor option for all controls.

It is not necessary that RenewAire controls be used to operate RenewAire units. A wide range of controls or building automation systems may be used. Make sure units are ordered with compatible contactor control voltage.

RenewAire residential units have their own line of compatible controls that are not intended to operate RenewAire commercial units.

## TC7D

### DIGITAL TIME CLOCK



- up to 8 on/off cycles per day or 56 per week
- 24 VAC power requirement
- battery back-up
- wall mount or outdoor enclosure options
- wall mount fits any 4" x 4" electrical box
- optional RenewAire transformer relay package (TR40) may be used



TC7D-W  
Wall Mount

TC7D-E Control  
In NEMA 3R Enclosures

## MC

### MOTION (OCCUPANCY) CONTROL



- passive infrared sensor
- adjustable time-off delay to 30 minutes
- 24 VAC power requirement
- ceiling mount or directable wall mount
- covers up to 1500 sq. ft. floor space
  - ceiling mount - walking motion coverage up to 22 foot radius
  - wall mount - various coverage patterns up to 90 linear feet of sensitivity
- requires the use of RenewAire transformer relay package (TR40) (ordered separately)



MC-C  
Ceiling Mount


MC-W  
Wall Mount

## CO2

### CARBON DIOXIDE CONTROL



- adjustable control from 600-2000 PPM
- digital display
- 24 VAC power requirement
- computer/BAS interface for information and control
- self calibrates during periods of low occupancy
- wall mount or add duct mount accessory
- requires the use of RenewAire transformer relay package (TR40) (ordered separately)



CO2-W  
Wall Mount

CO2-D  
Duct Mount



## DH24

### DEHUMIDISTAT CONTROL

DH24  
Wall Mount



- secondary control to time clock or other primary control
- mechanical switching of 24 VAC (or 120 VAC)
- adjustable from 0 - 100% relative humidity
- wall mount to single gang box
- Note: RenewAire ERVs are not to be used for applications where indoor relative humidity exceeds 50% RH for extended periods of time

## DS


### DISCONNECT SWITCH



- fused or non-fused
- indoor or NEMA 3R exterior enclosures - I or E
- installation voltage must be specified 115, 208-230, 46
- installed on unit and wired to unit contactor
- disconnects are configured as part of the model numbering for a unit (see page 67)

## TR40


### TRANSFORMER RELAY PACKAGE



- provides a 24 VAC, 40 VA class II power supply for unit control
- includes isolation relay with low voltage circuit breaker
- handles any RenewAire unit with one contactor
- installation voltage must be specified 115, 208-230, 46
- installed in unit electric box
- TR40 is configured as part of the model numbering for a unit (see page 67)

## IBC

### INDEPENDENT BLOWER CONTROL



- adds a second contactor to allow independent control of exhaust fan and supply fan
- may be used to provide economizer (no heat recovery operation) function
- can provide relief fan or make-up air function to benefit building pressurization
- IBC is configured as part of the model numbering guide for a unit (see page 67)

# HVI Tested/Certified


Per CSA C439



BR70/EV70 - Ventilation Performance									
Ext. Static Pressure		Net Supply Airflo		Gross Airflo					
Pa	in. wg	L/S	CFM	Supply	Exhaust	L/S	CFM	L/S	CFM
25	0.1	41	86	42	89	46	97		
50	0.2	34	73	35	75	39	84		
75	0.3	28	59	29	61	32	69		
100	0.4	21	46	22	47	25	53		

Electrical Requirements Volts 120 Amps 1.0  
Exhaust Air Transfer Ratio = 4% @ 0.2 in. wg (50 PA) and 4% @ 0.4 in. wg (100 PA)


BR70/EV70 - Energy Performance									
Supply Temperature		Net Airflo		Average Power Watts	Sensible Recovery Efficiency	Apparent Sensible Effectiveness %	Net Moisture Transfer %		
C°	F°	L/S	CFM						
<b>Heating</b>									
0°	32°	32	69	94	66	77	53		
<b>Cooling</b>									
35°	95°	30	64	94		42			



BR130/EV130 - Ventilation Performance									
Ext. Static Pressure		Net Supply Airflo		Gross Airflo					
Pa	in. wg	L/S	CFM	Supply	Exhaust	L/S	CFM	L/S	CFM
25	0.1	70	148	71	151	75	159		
50	0.2	66	141	67	143	69	147		
75	0.3	62	132	63	134	64	135		
100	0.4	53	113	54	115	56	119		
125	0.5	44	94	45	96	47	99		
150	0.6	32	69	33	70	29	62		
175	0.7	24	52	25	53	21	45		

Electrical Requirements Volts 120 Amps 1.3  
Exhaust Air Transfer Ratio = 2% @ 0.2 in. wg (50 PA) and 2% @ 0.4 in. wg (100 PA)


BR130/EV130 - Energy Performance									
Supply Temperature		Net Airflo		Average Power Watts	Sensible Recovery Efficiency	Apparent Sensible Effectiveness %	Net Moisture Transfer %		
C°	F°	L/S	CFM						
<b>Heating</b>									
0°	32°	58	124	121	72	80	55		
<b>Cooling</b>									
35°	95°	59	126	121		46			



EV200 - Ventilation Performance									
Ext. Static Pressure		Net Supply Airflo		Gross Airflo					
Pa	in. wg	L/S	CFM	Supply	Exhaust	L/S	CFM	L/S	CFM
25	0.1	97	207	100	213	109	232		
50	0.2	90	192	93	199	104	221		
75	0.3	88	186	90	192	101	216		
100	0.4	83	176	85	181	96	204		
125	0.5	79	168	81	173	88	187		
150	0.6	70	149	72	154	76	162		
175	0.7	57	122	59	126	68	145		

Electrical Requirements Volts 120 Amps 1.5  
Exhaust Air Transfer Ratio = 3% @ 0.2 in. wg (50 PA) and 3% @ 0.4 in. wg (100 PA)


EV200 - Energy Performance									
Supply Temperature		Net Airflo		Average Power Watts	Sensible Recovery Efficiency	Apparent Sensible Effectiveness %	Net Moisture Transfer %		
C°	F°	L/S	CFM						
<b>Heating</b>									
0°	32°	85	181	157	78	85	62		
<b>Cooling</b>									
35°	95°	85	180	155		52			



EV300 - Ventilation Performance									
Ext. Static Pressure		Net Supply Airflo		Gross Airflo					
Pa	in. wg	L/S	CFM	Supply	Exhaust	L/S	CFM	L/S	CFM
100	0.4	145	310	150	320	143	305		
125	0.5	141	300	145	310	138	295		
150	0.6	136	289	140	299	127	270		
175	0.7	126	268	130	276	114	242		
200	0.8	117	249	121	251	92	195		
225	0.9	94	199	97	206	79	169		
250	1.0	73	155	75	166	65	138		

Electrical Requirements Volts 120 Amps 3.3  
Exhaust Air Transfer Ratio = 4% @ 0.4 in. wg (100 PA)

EV300 - Energy Performance									
Supply Temperature		Net Airflo		Average Power Watts	Sensible Recovery Efficiency	Apparent Sensible Effectiveness %	Net Moisture Transfer %		
C°	F°	L/S	CFM						
<b>Heating</b>									
0°	32°	138	293	310	68	76	45		
<b>Cooling</b>									
35°	95°	120	272	299		38			



# AHRI 1060-2005

Certified Performance

AHRI-1060 Certified Performance - Model Number L85-G5

Type	Tilt Angle			Nominal Airflo			Pressure Drop					
Plate	N/A			100% - 450 SCFM 75% - 338 SCFM			0.6 in. H <sub>2</sub> O 0.5 in. H <sub>2</sub> O					
Leakage Ratings					Thermal Effectiveness Ratings at 0" Pressure Differential							
	Pressure Differential	EATR	OACF	Purge Angle or Setting	Nominal Airflo	Sensible	Latent	Total	Net Airflo			
Test 1	-1 in. H <sub>2</sub> O	1.0%	1.00	N/A	450 Heating CFM 46% Cooling	73% 73%	53% 46%	66% 56%	450 CFM 73%	73% 73%	53% 46%	66% 56%
Test 2	0 in. H <sub>2</sub> O	0.0%	1.02	N/A	338 Heating CFM 52% Cooling	77% 77%	60% 52%	71% 61%	338 CFM 77%	77% 77%	60% 52%	71% 61%
Test 3	1 in. H <sub>2</sub> O	0.0%	1.05	N/A								

AHRI-1060 Certified Performance - Model Number L125-G5

Type	Tilt Angle			Nominal Airflo			Pressure Drop					
Plate	N/A			100% - 750 SCFM 75% - 563 SCFM			0.65 in. H <sub>2</sub> O 0.45 in. H <sub>2</sub> O					
Leakage Ratings					Thermal Effectiveness Ratings at 0" Pressure Differential							
	Pressure Differential	EATR	OACF	Purge Angle or Setting	Nominal Airflo	Sensible	Latent	Total	Net Airflo			
Test 1	-1 in. H <sub>2</sub> O	1.0%	1.00	N/A	750 Heating CFM 71% Cooling	71% 71%	52% 43%	64% 53%	750 CFM 71%	71% 71%	52% 43%	64% 53%
Test 2	0 in. H <sub>2</sub> O	0.0%	1.02	N/A	563 Heating CFM 75% Cooling	75% 75%	59% 50%	69% 59%	563 CFM 75%	75% 75%	59% 50%	69% 59%
Test 3	1 in. H <sub>2</sub> O	0.0%	1.05	N/A								


NOTE: SCFM = Standard Cubic Feet per Minute OACF = Outdoor Air Correction Factor EATR = Exhaust Air Transfer Ratio N/A = Not Applicable

Energy recovery component certified in accordance with AHRI Standard 1060-2005.

Actual performance in packaged equipment may vary.



## MODEL NUMBERING GUIDE *Not all options are available on every model.*




### CA & PA MODELS

Think Greener. Breathe Better.

[www.proyectosrogo.com](http://www.proyectosrogo.com)

# MODEL NUMBERING GUIDE

**Note:** Not all options are available on every model.



## EV/HE MODELS

For Technical Support E-mail: [info@proyectosrogo.com](mailto:info@proyectosrogo.com)

# RENEWAIRE PRODUCT & VENTILATION COMMITMENT

*RenewAire ventilation products will give you cleaner air to breathe - letting you and your family feel better and healthier AND will do so in the most consistent, controlled, safe and energy-efficient manner possible.*



For over 30 years, RenewAire has been a pioneer in the use of plate exchangers that simultaneously transfer heat and humidity between ventilation airstreams in extreme climates. From cool-dry (Point Barrow, Alaska) to hot-humid (Puerto Rico) climates, RenewAire exceeds customer expectations for effective, reliable ventilation solutions.

**1980** First HRV and ERV installations using a variety of plate and wheel technologies.



ERV manufacturing begins using Mitsubishi "Lossnay" core.

**1983**

**1987** RenewAire model is the first listed by UL-1812 standard for E V safety.

HVI residential unit certification confirms superior heat and humidity transf .

**1996**

**1998** Introduction of first roof-top connected unit ( TC).

ARI-1060 commercial product certification of only E V with 0% cross contamination.

**2001**

**2003** Over 100 school projects shipped in one year.



G4 - 4th generation core introduced with enhanced humidity transfer.

**2004**

**2005** Introduction of *BREEZE*® easy to install residential unit.

Energy Star Qualified with energy use in the lowest 20% of comparable buildings

**2006**

**2007** New factory achieves LEED-Silver rating. 120,000<sup>th</sup> North American unit sold. 2007 sales result in 30,000 tons of CO<sub>2</sub> emission reductions!



Introduction of RD Series dedicated outdoor air system.

**2008**


**2009** Introduction of V-Series Ventilation Exhaust Fans.



G5 - 5th generation core introduced with enhanced humidity transfer.

**2010**

# FULL LINE OF VENTILATION PRODUCTS



## Residential & Small Commercial

- 5 Models
- 50 - 300 CFM
- built-in 24 V transformer/relay package




## Commercial Products

- 23 Models
- 250 - 7,950 CFM
- 1 or 3 phase multi-voltage
- 24 volt control



## Applied Products

- CA-Series (cabinet) - 500 - 20,000 CFM
- PA-Series (panelized) - 1,500 - Unlimited CFM
- *(requires blowers & manifolds by others)*



## Dedicated Outdoor Air Systems

- 4 Models
- 500 - 4400 CFM
- integrated VFD for each airstream
- coil options including DX, chilled water, hot water and combinations



## Ventilation Exhaust Fans

- 4 Models
- 50 - 150 CFM
- robust steel housing and duct collar
- the most efficient line of exhaust fan available in North America

*This piece was printed using earth-friendly soy ink on 100% post-consumer recycled paper.  
RenewAire ERVs are proudly manufactured in our LEED-Silver Certified facility using 100% wind generated electricity.*