

pipe

| yes we can

| fittings



onesteel
metalcentre



Yes,

Pipe & Fittings Data Charts

we can.



pipe

| yes we can

| fittings

www.onesteelmetalcentre.com

We understand.

With extensive experience in the steel industry, our staff can advise on ways to estimate, streamline and tailor steel solutions to deliver more cost-effective outcomes and reduce wastage on projects.

We make it easier.

Whether its accuracy, tolerance or repeatability you need, we achieve this through OneSteel Metalcentre's fully programmable machinery and the long term experience of our people.

We deliver.

Through our integrated supply chain we can add value to projects by sourcing complementary products through our industry partners and can deliver in an order that suits your schedule.

National Branch Network.



Yes,

Safety at our sites.

OneSteel does not compromise on safety, and we believe that all injuries, occupational illnesses and incidents are preventable. Achieving zero incidents is possible in all OneSteel businesses by maintaining a strong focus on the health and safety of all employees, contractors and customers. OneSteel's "Goal Zero" target aims to ensure employees can go home in the same condition that they came to work. OneSteel has implemented stringent safety policies and procedures that enable us to strive for our safety goal.

We appreciate your compliance with our safety policies when you visit our sites.



we can.

Table of Contents

| | |
|---|-------|
| American Standard Steel Pipe ASME B36.10 | 4 |
| Carbon Steel Butt weld Fittings To ASME B16.9, B16.28 & BS.1640 | 5 |
| Flanges To American Standards | 6 |
| American Standard Flanges Temperature / Pressure Ratings | 7 |
| Steel Pipe, Butt weld Fittings & Flanges To ASME Standards | 8 |
| Bolts & studs for ASME B16.5 Flanges | 9 |
| Flange Identification Chart | 10-11 |
| Australian Standard Flanges | 12 |
| I.S.O. Metric Hexagon Steel Bolts For Use With AS.2129 Flanges | 13 |
| Light/Extra Light Pipe To Australian Standards | 14 |
| Medium & Heavy Pipe To Australian Standards | 15 |
| Stainless Steel Pipes To American Standard ASME B36.19 | 16 |
| Pressure Conversion Table | 17 |
| Temperature Conversion Table | 18 |
| Conversion Factors – Imperial To Metric (Approx.) | 19 |

onesteel
metalcentre

This publication has been prepared by OneSteel Trading Pty Limited ABN 50 007 519 646. OneSteel provides the information contained in this data chart as a guide only for your information. Please note that any specifications or technical data referred to in this publication are subject to change and/or variation or improvement without notice and no warranty as to their suitability for any use is made. Users of this publication - to ensure accuracy and adequacy for their purposes - are requested to check the information provided in this publication to satisfy themselves as to its appropriateness and not to rely on the information without first doing so. In regards to Metric Conversion, many international industry groups have retained imperial measurement as their standard unit of measure. In metricating international standards we have rounded to nearest full units in certain cases. Should dimensional accuracy be critical to your requirements we suggest that reference be made to the appropriate original standards. Unless required by law, OneSteel cannot accept any responsibility for any loss, damage or consequence resulting from the use of this publication. Photographs shown are representative only of typical applications. This brochure is not an offer to trade and shall not form any part of the trading terms in any transaction. ©Copyright 2013. OneSteel Trading Pty Limited ABN 50 007 519 646. OneSteel® is a Registered Trademark of OneSteel Limited ABN 63 004 410 833.



Yes,

OneSteel Metalcentre is Australia's only truly integrated steel supplier. With over 50 locations nationwide we are uniquely positioned in every city and region to provide products to a wide range of end markets including residential, engineering, construction, manufacturing, mining and rural. We offer a comprehensive steel range, combined with supply chain efficiencies and national processing options.

we can.

pipe

| yes we can

| fittings

www.onesteelmetalcentre.com

| Nominal Size | | Outside Diameter mm | Nominal Wall Thickness & Weight for Welded & Seamless Steel Pipe ASME B36.10 | | | | | | | | | | Dimensions (mm) Weight (kg/m) | | | |
|--------------|---------|------------------------|---|----------------|-----------------|----------------|--------------------|-------------------|-----------------|-----------------|-----------------|-----------------|----------------------------------|-----------------|-----------------|-----------------|
| DN | NPS | | STD | EXTRA STRONG | XX STRONG | SCHED. 10 | SCHED. 20 | SCHED. 30 | SCHED. 40 | SCHED. 60 | SCHED. 80 | SCHED. 100 | SCHED. 120 | SCHED. 140 | SCHED. 160 | |
| 6 | 1/8 | 10.3 | 1.73 0.37 | 2.41 0.47 | - | - | - | - | - | - | - | - | - | - | - | |
| 8 | 1/4 | 13.7 | 2.24 0.63 | 3.02 0.80 | - | - | - | - | - | - | - | - | - | - | - | |
| 10 | 3/8 | 17.1 | 2.31 0.84 | 3.20 1.10 | - | - | - | - | - | - | - | - | - | - | - | |
| 15 | 1/2 | 21.3 | 2.77 1.27 | 3.73 1.62 | 7.47 2.55 | - | - | - | - | - | - | - | - | - | 4.78 1.95 | |
| 20 | 3/4 | 26.7 | 2.87 1.69 | 3.91 2.20 | 7.82 3.64 | - | - | - | - | - | - | - | - | - | 5.56 2.90 | |
| 25 | 1 | 33.4 | 3.38 2.50 | 4.55 3.24 | 9.09 5.45 | - | - | - | - | - | - | - | - | - | 6.35 4.24 | |
| 32 | 1 - 1/4 | 42.2 | 3.56 3.39 | 4.85 4.47 | 9.7 7.77 | - | - | - | - | - | - | - | - | - | 6.35 5.61 | |
| 40 | 1 - 1/2 | 48.3 | 3.68 4.05 | 5.08 5.41 | 10.15 9.56 | - | - | - | - | - | - | - | - | - | 7.14 7.25 | |
| 50 | 2 | 60.3 | 3.91 5.44 | 5.54 7.48 | 11.07 13.44 | - | - | - | - | - | - | - | - | - | 8.74 11.11 | |
| 65 | 2 - 1/2 | 73.0 | 5.16 8.63 | 7.01 11.41 | 14.02 20.39 | - | - | - | - | - | - | - | - | - | 9.53 14.92 | |
| 80 | 3 | 88.9 | 5.49 11.29 | 7.62 15.27 | 15.24 27.67 | - | - | - | - | - | - | - | - | - | 11.13 21.35 | |
| 90 | 3 - 1/2 | 101.6 | 5.74 13.57 | 8.08 18.63 | - | - | - | - | - | - | - | - | - | - | - | |
| 100 | 4 | 114.3 | 6.02 16.07 | 8.56 22.32 | 17.12 41.03 | - | - | - | - | - | - | - | 11.13 28.32 | - | 13.49 33.54 | |
| 125 | 5 | 141.3 | 6.55 21.77 | 9.53 30.97 | 19.05 57.43 | - | - | - | - | - | - | - | 12.7 40.28 | - | 15.88 49.11 | |
| 150 | 6 | 168.3 | 7.11 28.26 | 10.97 42.56 | 21.95 79.22 | - | - | - | - | - | - | - | 14.27 54.20 | - | 18.26 67.56 | |
| 200 | 8 | 219.1 | 8.18 42.55 | 12.7 64.64 | 22.23 107.92 | - | 6.35 33.31 | 7.04 36.81 | - | - | 10.31 53.08 | - | 15.09 75.92 | 18.26 90.44 | 20.62 100.92 | 23.01 111.27 |
| 250 | 10 | 273.1 | 9.27 60.31 | 12.7 81.55 | 25.4 155.15 | - | 6.35 41.77 | 7.8 51.03 | - | - | XS 81.55 | 15.09 96.01 | 18.26 114.75 | 21.44 133.06 | XXS 155.15 | 28.58 172.33 |
| 300 | 12 | 323.9 | 9.53 73.88 | 12.7 97.46 | 25.4 186.97 | - | 6.35 49.73 | 8.38 65.20 | 10.31 79.73 | 14.27 108.96 | 17.48 132.08 | 21.44 159.91 | XXS 186.97 | 28.58 208.14 | 33.32 238.76 | |
| 350 | 14 | 355.6 | 9.53 81.33 | 12.7 107.10 | - | 6.35 54.59 | 7.92 67.90 | Std.W.T. 81.33 | 11.13 94.55 | 15.09 126.70 | 19.05 158.10 | 23.83 194.96 | 27.79 224.65 | 31.75 253.56 | 35.71 281.70 | |
| 400 | 16 | 406.4 | 9.53 93.27 | 12.7 123.30 | - | 6.35 62.64 | 7.92 77.83 | Std.W.T. 93.27 | XS 123.30 | 16.66 160.12 | 21.44 203.53 | 26.19 245.56 | 30.96 286.64 | 36.53 333.19 | 40.49 365.35 | |
| 450 | 18 | 457 | 9.53 105.16 | 12.7 139.15 | - | 6.35 70.57 | 7.92 87.71 | 11.13 122.38 | 14.27 155.80 | 19.05 205.74 | 23.83 254.55 | 29.36 309.62 | 34.93 363.56 | 39.67 408.26 | 45.24 459.37 | |
| 500 | 20 | 508 | 9.53 117.15 | 12.7 155.12 | - | 6.35 78.55 | Std.W.T. 117.15 | XS 155.12 | 15.09 183.42 | 20.62 247.83 | 26.19 311.17 | 32.54 381.53 | 38.1 441.49 | 44.45 508.11 | 50.01 564.81 | |
| 550 | 22 | 559 | 9.53 129.13 | 12.7 171.09 | - | 6.35 86.54 | Std.W.T. 129.13 | XS 171.09 | - | 22.23 294.25 | 28.58 373.83 | 34.93 451.42 | 41.28 527.05 | 47.63 600.63 | 53.98 672.26 | |
| 600 | 24 | 610 | 9.53 141.12 | 12.7 187.06 | - | 6.35 94.53 | Std.W.T. 141.12 | 14.27 209.64 | 17.48 255.41 | 24.61 355.26 | 30.96 442.08 | 38.89 547.71 | 46.02 640.03 | 52.37 720.15 | 59.54 808.22 | |
| 650 | 26 | 660 | 9.53 152.87 | 12.7 202.72 | - | 7.92 127.36 | XS 202.72 | - | - | - | - | - | - | - | - | |
| 700 | 28 | 711 | 9.53 164.85 | 12.7 218.69 | - | 7.92 137.32 | XS 218.69 | 15.88 271.21 | - | - | - | - | - | - | - | |
| 750 | 30 | 762 | 9.53 176.84 | 12.7 234.67 | - | 7.92 147.28 | XS 234.67 | 15.88 292.18 | - | - | - | - | - | - | - | |
| 800 | 32 | 813 | 9.53 188.82 | 12.7 250.64 | - | 7.92 157.24 | XS 250.64 | 15.88 312.15 | 17.48 342.91 | - | - | - | - | - | - | |
| 850 | 34 | 864 | 9.53 200.31 | 12.7 266.61 | - | 7.92 167.20 | XS 266.61 | 15.88 332.12 | 17.48 364.90 | - | - | - | - | - | - | |
| 900 | 36 | 914 | 9.53 212.56 | 12.7 282.27 | - | 7.92 176.96 | XS 282.27 | 15.88 351.7 | 19.05 420.42 | - | - | - | - | - | - | |
| 1050 | 42 | 1067 | 9.53 248.52 | 12.7 330.19 | - | - | - | - | - | - | - | - | - | - | - | |

Formula used to attain approximate mass in kilograms per metre (kg/m) for Steel Round Pipe and Tubing

$m = (D - t) t \times 0.02466$


Where: m = mass to the nearest 0.01 kg/m
 D = Outside Diameter in millimetres
 (To nearest 0.1mm for OD up to 406.4mm)
 (To nearest 1.0mm for OD 457mm and above)
 t = Wall Thickness to nearest 0.01mm

EXAMPLE: [Nominal Size DN300 NPS12 OD = 323.9mm W.T. = 9.53mm] [Step 1. 323.9 - 9.53 = 314.37 Step 2. 314.37 x 9.53 = 2995.9461 Step 3. 2995.9461 x 0.024 66 = 73.88kg/m]

B16.9
LONG RADIUS WELDING ELBOWS, RETURN BENDS & CAPS




B16.28
SHORT RADIUS WELDING ELBOWS & RETURN BENDS



| Nom. Size DN | Pipe OD mm | Wall Thickness (mm) | | | | | | | | | | | | | A | B | K | D | V | E. Std. Wt. & Ex. Stg. | Nom. Size DN |
|--------------|------------|---------------------|---------|---------|----------|---------|---------|--------|---------|----------|----------|----------|----------|-----------|------|------|------|------|------|------------------------|--------------|
| | | Sch. 10 | Sch. 20 | Sch. 30 | Std. Wt. | Sch. 40 | Sch. 60 | X Stg. | Sch. 80 | Sch. 100 | Sch. 120 | Sch. 140 | Sch. 160 | X.X. Stg. | | | | | | | |
| 15 | 21.3 | - | - | - | 2.77 | - | - | 3.73 | - | - | - | 4.78 | 7.47 | 38 | 16 | 47.5 | - | - | 25.4 | 15 | |
| 20 | 26.7 | - | - | - | 2.87 | - | - | 3.91 | - | - | - | 5.56 | 7.82 | 38 | 19 | 43 | 19 | 33 | 25.4 | 20 | |
| 25 | 33.4 | - | - | - | 3.38 | - | - | 4.55 | - | - | - | 6.35 | 9.09 | 38 | 22 | 55.5 | 25.4 | 41 | 38.1 | 25 | |
| 32 | 42.2 | - | - | - | 3.56 | - | - | 4.85 | - | - | - | 6.35 | 9.70 | 47.5 | 25.4 | 70 | 32 | 52 | 38.1 | 32 | |
| 40 | 48.3 | - | - | - | 3.68 | - | - | 5.08 | - | - | - | 7.14 | 10.15 | 57 | 29 | 82.5 | 38 | 62 | 38.1 | 40 | |
| 50 | 60.3 | - | - | - | 3.91 | - | - | 5.54 | - | - | - | 8.74 | 11.07 | 76 | 35 | 106 | 51 | 81 | 38.1 | 50 | |
| 65 | 73.0 | - | - | - | 5.16 | - | - | 7.01 | - | - | - | 9.53 | 14.02 | 95 | 44.5 | 132 | 63.5 | 100 | 38.1 | 65 | |
| 80 | 88.9 | - | - | - | 5.49 | - | - | 7.62 | - | - | - | 11.13 | 15.24 | 114 | 51 | 159 | 76 | 121 | 50.8 | 80 | |
| 90 | 101.6 | - | - | - | 5.74 | - | - | 8.08 | - | - | - | - | 16.15 | 133 | 57 | 184 | 89 | 140 | 63.5 | 90 | |
| 100 | 114.3 | - | - | - | 6.02 | - | - | 8.56 | - | 11.13 | - | 13.49 | 17.12 | 152 | 63.5 | 210 | 102 | 159 | 63.5 | 100 | |
| 125 | 141.3 | - | - | - | 6.55 | - | - | 9.53 | - | 12.70 | - | 15.88 | 19.05 | 190 | 79 | 262 | 127 | 197 | 76.2 | 125 | |
| 150 | 168.3 | - | - | - | 7.11 | - | - | 10.97 | - | 14.27 | - | 18.26 | 21.95 | 229 | 95 | 313 | 152 | 237 | 88.9 | 150 | |
| 200 | 219.1 | - | 6.35 | 7.04 | 8.18 | 10.31 | 12.70 | 15.09 | 15.09 | 18.26 | 20.62 | 23.01 | 22.23 | 305 | 127 | 414 | 203 | 313 | 102 | 200 | |
| 250 | 273.1 | - | 6.35 | 7.80 | 9.27 | 12.70 | 12.70 | 15.09 | 18.26 | 21.44 | 25.40 | 28.58 | 25.40 | 381 | 159 | 517 | 254 | 390 | 127 | 250 | |
| 300 | 323.9 | - | 6.35 | 8.38 | 9.53 | 10.31 | 14.27 | 12.70 | 17.48 | 21.44 | 25.40 | 28.58 | 33.32 | 457 | 190 | 619 | 305 | 467 | 152 | 300 | |
| 350 | 355.6 | 6.35 | 7.92 | 9.53 | 9.53 | 11.13 | 15.09 | 12.70 | 19.05 | 23.83 | 27.79 | 31.75 | 35.71 | 533 | 222 | 711 | 356 | 533 | 165 | 350 | |
| 400 | 406.4 | 6.35 | 7.92 | 9.53 | 9.53 | 12.7 | 16.66 | 12.70 | 21.44 | 26.19 | 30.96 | 36.53 | 40.49 | 610 | 254 | 813 | 406 | 610 | 178 | 400 | |
| 450 | 457 | 6.35 | 7.92 | 11.13 | 9.53 | 14.27 | 19.05 | 12.70 | 23.83 | 29.36 | 34.93 | 39.67 | 45.24 | 686 | 286 | 914 | 457 | 686 | 203 | 450 | |
| 500 | 508 | 6.35 | 9.53 | 12.70 | 9.53 | 15.09 | 20.62 | 12.70 | 26.19 | 32.54 | 38.10 | 44.45 | 50.01 | 762 | 318 | 1016 | 508 | 762 | 229 | 500 | |
| 600 | 610 | 6.35 | 9.53 | 14.27 | 9.53 | 17.48 | 24.61 | 12.70 | 30.96 | 38.89 | 46.02 | 52.37 | 59.54 | 914 | 381 | 1219 | 610 | 914 | 267 | 600 | |
| 750 | 762 | 7.92 | 12.70 | 15.88 | 9.53 | - | - | 12.70 | - | - | - | - | - | 1143 | 470 | 1524 | 762 | 1143 | 267 | 750 | |
| 900 | 914 | 7.92 | 12.70 | 15.88 | 9.53 | 19.05 | - | 12.70 | - | - | - | - | - | 1372 | 565 | - | 914 | 1372 | 267 | 900 | |


STRAIGHT TEES (B16.9)



REDUCING TEES (B16.9)



CONCENTRIC & ECCENTRIC REDUCERS (B16.9)



| Nominal Size DN | C | M | H | Nominal Size DN | C | M | H | Nominal Size DN | C | M | H |
|-----------------|----|------|------|-----------------|-----|-----|------|-----------------|-----|-----|-----|
| | | | | | | | | | | | |
| 20 | 20 | 28.6 | - | 100 | 105 | - | - | 400 | 305 | - | - |
| 20 | 15 | 28.6 | 28.6 | 100 | 90 | 105 | 102 | 350 | 305 | 305 | 356 |
| 20 | 25 | 38.1 | - | 100 | 80 | 105 | 98.4 | 300 | 305 | 295 | 356 |
| 25 | 20 | 38.1 | 38.1 | 100 | 65 | 105 | 95.3 | 250 | 305 | 283 | 356 |
| 25 | 15 | 38.1 | 38.1 | 100 | 50 | 105 | 88.9 | 200 | 305 | 273 | 356 |
| 32 | 32 | 47.6 | - | 125 | 40 | 105 | 85.7 | 150 | 305 | 264 | 356 |
| 32 | 25 | 47.6 | 47.6 | 125 | 124 | - | - | 450 | 343 | - | - |
| 32 | 20 | 47.6 | 47.6 | 125 | 100 | 124 | 117 | 400 | 343 | 330 | 381 |
| 32 | 15 | 47.6 | 47.6 | 125 | 90 | 124 | 114 | 350 | 343 | 330 | 381 |
| 40 | 40 | 57.2 | - | 150 | 80 | 124 | 111 | 300 | 343 | 321 | 381 |
| 40 | 32 | 57.2 | 57.2 | 150 | 65 | 124 | 108 | 250 | 343 | 308 | 381 |
| 40 | 25 | 57.2 | 57.2 | 150 | 50 | 124 | 105 | 200 | 343 | 298 | 381 |
| 50 | 20 | 57.2 | 57.2 | 150 | 150 | 143 | - | 500 | 381 | - | - |
| 50 | 15 | 57.2 | 57.2 | 150 | 125 | 143 | 137 | 450 | 381 | 368 | 508 |
| 50 | 50 | 63.5 | - | 150 | 100 | 143 | 130 | 400 | 381 | 356 | 508 |
| 50 | 40 | 63.5 | 60.3 | 150 | 90 | 143 | 127 | 350 | 381 | 356 | 508 |
| 50 | 32 | 63.5 | 57.2 | 150 | 80 | 143 | 124 | 300 | 381 | 346 | 508 |
| 50 | 25 | 63.5 | 50.8 | 150 | 65 | 143 | 121 | 250 | 381 | 333 | 508 |
| 50 | 20 | 63.5 | 44.5 | 150 | 200 | 178 | - | 200 | 381 | 324 | 508 |
| 65 | 65 | 76.2 | - | 200 | 150 | 178 | 168 | 600 | 432 | - | - |
| 65 | 50 | 76.2 | 69.9 | 200 | 125 | 178 | 162 | 500 | 432 | 432 | 508 |
| 65 | 40 | 76.2 | 66.7 | 200 | 100 | 178 | 155 | 450 | 432 | 419 | 508 |
| 65 | 32 | 76.2 | 63.5 | 200 | 80 | 178 | 152 | 400 | 432 | 406 | 508 |
| 65 | 25 | 76.2 | 57.2 | 200 | 250 | 216 | - | 350 | 432 | 406 | 508 |
| 80 | 80 | 85.7 | - | 250 | 200 | 216 | 203 | 300 | 432 | 397 | 508 |
| 80 | 65 | 85.7 | 82.6 | 250 | 150 | 216 | 194 | 250 | 432 | 384 | 508 |
| 80 | 50 | 85.7 | 76.2 | 250 | 125 | 216 | 191 | 200 | 432 | - | - |
| 80 | 40 | 85.7 | 73.0 | 250 | 100 | 216 | 184 | 150 | 432 | - | - |
| 80 | 32 | 85.7 | 69.9 | 250 | 300 | 254 | - | 750 | 559 | - | - |
| 80 | 25 | 85.7 | 69.9 | 250 | 250 | 254 | 241 | 600 | 559 | 533 | 610 |
| 80 | 90 | 95.3 | - | 300 | 200 | 254 | 229 | 500 | 559 | 508 | 610 |
| 80 | 80 | 95.3 | 92.1 | 300 | 150 | 254 | 219 | 400 | 559 | 495 | 610 |
| 80 | 65 | 95.3 | 88.9 | 300 | 100 | 254 | 210 | 300 | 559 | 483 | 610 |
| 80 | 50 | 95.3 | 82.6 | 300 | 350 | 279 | - | 900 | 673 | - | - |
| 80 | 40 | 95.3 | 79.4 | 300 | 300 | 279 | 270 | 750 | 673 | 635 | 610 |
| 90 | 90 | 95.3 | - | 350 | 250 | 279 | 257 | 600 | 673 | 610 | 610 |
| 90 | 80 | 95.3 | 92.1 | 350 | 200 | 279 | 248 | 500 | 673 | 584 | 610 |
| 90 | 65 | 95.3 | 88.9 | 350 | 150 | 279 | 238 | 450 | 673 | 572 | 610 |

NOTE: All dimensions are in millimetres (mm)

| Temperature / Pressure Ratings | | | | | | |
|---|--|------------------|-------------------|-------------------|--------------------|--------------------|
| Carbon Steel Pipe Flanges to ANSI / ASME 16.5 - 1988 (BS 1560) Forgings to ASTM A105 and A350 - LF2 Forgings to ASTM A181 Grade II for Class 150 and 300 Only | | | | | | |
| Temperature (°C) | Maximum Working Pressure in kPa by Classes (for approximate PSI divide by 7) | | | | | |
| | Class 150 (PN20) | Class 300 (PN50) | Class 600 (PN100) | Class 900 (PN150) | Class 1500 (PN250) | Class 2500 (PN420) |
| -29 to 38 | 1960 | 5110 | 10210 | 15320 | 25530 | 42550 |
| 50 | 1920 | 5010 | 10020 | 15020 | 25040 | 41730 |
| 100 | 1770 | 4640 | 9280 | 13910 | 23190 | 38650 |
| 150 | 1580 | 4520 | 9050 | 13570 | 22610 | 37690 |
| 200 | 1400 | 4380 | 8760 | 13150 | 21910 | 36520 |
| 250 | 1210 | 4170 | 8340 | 12520 | 20860 | 34770 |
| 300 | 1020 | 3870 | 7750 | 11620 | 19370 | 32280 |
| 350 | 840 | 3700 | 7390 | 11090 | 18480 | 30800 |
| 375 | 740 | 3650 | 7290 | 10940 | 18230 | 30390 |
| 400 | 650 | 3450 | 6900 | 10350 | 17250 | 28750 |
| 425 | 560 | 2880 | 5750 | 8630 | 14380 | 23960 |
| 450 | 470 | 2000 | 4010 | 6010 | 10020 | 16690 |
| 475 | 370 | 1350 | 2710 | 4060 | 6770 | 11290 |
| 500 | 280 | 880 | 1760 | 2640 | 4400 | 7330 |
| 525 | 190 | 520 | 1040 | 1550 | 2590 | 4320 |
| 540 | 130 | 330 | 650 | 980 | 1630 | 2720 |



Flanges above 600 NPA are not included in ANSI B16.5 and the class designations in these large diameters do not imply specific temperature / pressure ratings.

| ASME B36.10 Steel Pipe Dimensions | | | | | Approximate Mass of Popular Sizes | | | | | | | | | | | |
|--------------------------------------|-----------------------|----------------|-------------|-----------------------|-----------------------------------|------------------------|---------------------------------|---------------------------|-----------------|----------------|---------------------------|--------------|----------------|----------------|----------------|---------|
| Outside Diam. mm | Inside Diam. mm | Identification | | Steel Pipe kg/m | Buttweld Fittings | | | | A.S.M.E Flanges | | | | | | | |
| | | Std. X.S | Sch. No. | | 90° L/R Elbows kg/ea | Tees Equal kg/ea | Con. & Ecc. Red. kg/ea | PN20 (150) | | | PN50 (300) | | | PN100 (600) | PN150 (900) | |
| | | | | | | | | SOW/SW Thrded kg/ea | W/N kg/ea | Blind kg/ea | SOW/SW Thrded kg/ea | W/N kg/ea | Blind kg/ea | W/N kg/ea | W/N kg/ea | |
| 15 | 21.3 | 15.8 13.9 | Std. XS | 40 80 | 1.27 1.62 | 0.08 0.10 | 0.16 0.21 | - - | 0.45 | 0.79 | 0.57 | 0.73 | 0.91 | 0.79 | 0.91 | 2.00 |
| 20 | 26.7 | 20.9 18.9 | Std. XS | 40 80 | 1.69 2.20 | 0.08 0.11 | 0.21 0.27 | 0.07 0.10 | 0.68 | 0.86 | 0.91 | 1.25 | 1.41 | 1.13 | 1.59 | 2.72 |
| 25 | 33.4 | 26.6 24.3 | Std. XS | 40 80 | 2.50 3.24 | 0.17 0.21 | 0.34 0.43 | 0.14 0.18 | 0.95 | 1.09 | 1.09 | 1.36 | 1.81 | 1.77 | 1.86 | 3.86 |
| 32 | 42.2 | 35.1 32.5 | Std. XS | 40 80 | 3.39 4.47 | 0.28 0.39 | 0.64 0.75 | 0.18 0.23 | 1.13 | 1.41 | 1.25 | 2.04 | 2.27 | 2.68 | 2.72 | 4.54 |
| 40 | 48.3 | 40.9 38.1 | Std. XS | 40 80 | 4.05 5.41 | 0.39 0.50 | 0.95 1.13 | 0.27 0.32 | 1.36 | 1.81 | 1.70 | 2.81 | 3.06 | 2.83 | 3.74 | 6.35 |
| 50 | 60.3 | 52.5 49.2 | Std. XS | 40 80 | 5.44 7.48 | 0.68 1.00 | 1.45 1.72 | 0.41 0.54 | 2.22 | 2.83 | 2.77 | 3.13 | 3.74 | 3.52 | 4.65 | 10.89 |
| 65 | 73.0 | 62.7 59.0 | Std. XS | 40 80 | 8.63 11.41 | 1.39 1.82 | 2.45 2.95 | 0.68 0.91 | 3.82 | 4.42 | 4.04 | 4.54 | 5.56 | 5.44 | 6.44 | 16.33 |
| 80 | 88.9 | 77.9 73.7 | Std. XS | 40 80 | 11.29 15.27 | 2.18 2.86 | 3.45 4.30 | 0.91 1.27 | 4.08 | 5.22 | 5.44 | 6.12 | 7.37 | 7.26 | 8.50 | 14.51 |
| 90 | 101.6 | 90.1 85.4 | Std. XS | 40 80 | 13.57 18.63 | 3.05 4.1 | 4.5 5.9 | 1.36 1.81 | 4.99 | 5.44 | 6.35 | 7.71 | 9.53 | 9.98 | 12.25 | -- |
| 100 | 114.3 | 102.3 97.2 | Std. XS | 40 80 | 16.07 22.32 | 4.2 5.7 | 5.7 7.3 | 1.59 2.18 | 5.94 | 7.48 | 7.37 | 9.53 | 11.79 | 11.79 | 17.24 | 23.13 |
| 125 | 141.3 | 128.2 122.3 | Std. XS | 40 80 | 21.77 30.97 | 6.8 10.0 | 9.1 11.8 | 2.7 3.8 | 6.12 | 9.53 | 9.07 | 12.70 | 15.42 | 15.88 | 30.84 | 39.01 |
| 150 | 168.3 | 154.1 146.3 | Std. XS | 40 80 | 28.26 42.56 | 10.9 16.3 | 13.6 19.0 | 3.9 5.4 | 8.16 | 11.34 | 12.70 | 16.33 | 19.96 | 20.87 | 34.02 | 49.90 |
| 200 | 219.1 | 202.7 193.7 | Std. XS | 40 80 | 42.55 64.64 | 21.8 33.1 | 25 33.5 | 5.9 8.6 | 12.70 | 19.05 | 21.77 | 25.40 | 32.21 | 38.10 | 52.16 | 84.82 |
| 250 | 273.1 | 254.5 247.7 | Std. XS | 40 60 | 60.31 81.55 | 38.6 52 | 41 54 | 10 14 | 17.24 | 25.40 | 31.75 | 35.38 | 44.00 | 53.34 | 90.36 | 121.56 |
| 300 | 323.9 | 304.8 298.5 | Std. XS | - - | 73.88 97.46 | 57 75 | 57 77 | 15 20 | 27.22 | 38.10 | 45.36 | 50.80 | 64.41 | 86.18 | 101.60 | 168.74 |
| 350 | 355.6 | 336.6 330.2 | Std. XS | 30 - | 81.33 107.39 | 73 97 | 73 93 | 28 37 | 35.38 | 51.26 | 58.97 | 74.39 | 84.37 | 107.05 | 157.40 | 254.92 |
| 400 | 406.4 | 387.4 381.0 | Std. XS | 30 40 | 93.27 123.30 | 98 130 | 91 120 | 35 46 | 42.18 | 63.50 | 77.11 | 101.60 | 111.58 | 145.15 | 209.11 | 310.71 |
| 450 | 457 | 438.2 431.8 | Std. XS | - - | 105.16 139.15 | 120 165 | 135 190 | 40 53 | 52.62 | 68.04 | 102.51 | 126.10 | 138.35 | 181.89 | 217.27 | 419.12 |
| 500 | 508 | 489.0 482.6 | Std. XS | 20 30 | 117.15 155.12 | 150 200 | 168 245 | 61 82 | 65.32 | 81.65 | 123.38 | 149.69 | 174.63 | 231.33 | 312.98 | 527.98 |
| 600 | 610 | 590.6 584.2 | Std. XS | 20 - | 141.12 187.06 | 220 280 | 240 350 | 77 95 | 91.63 | 118.84 | 203.21 | 222.26 | 247.21 | 342.92 | 443.16 | 680.39 |
| 750 | 762 | 743.0 736.6 | Std. XS | - 20 | 176.84 234.67 | 332 440 | 388 484 | 107 143 | 142.88 | 163.29 | 326.59 | 367.41 | 421.84 | 680.39 | 589.67 | 975.22 |
| 900 | 914 | 895.4 889.0 | Std. XS | - 20 | 212.56 282.27 | 481 638 | 588 731 | 129 172 | 217.72 | 235.87 | 510.29 | 544.31 | 589.67 | 1031.92 | 793.79 | 1564.89 |

APPROXIMATE MASS PER UNIT FOR AUSTENITIC STAINLESS STEEL PIPE AND FITTINGS CAN BE OBTAINED BY APPLYING A FACTOR OF 1.015

BOLTING

To suit R.F. Flange sizes DN 15 to 600 to ASME – B16.5 (BS. 1560) and DN 750 & 900 to BS. 3293



Diameter of Bolts is shown in inches. For nominal diameters 1 inch and smaller, threads are U.N.C.; nominal diameters 1 - 1/8 inch and larger threads are 8 U.N. (8 T.P.I.).

Length of Bolts (L) is shown in millimetres rounded to the nearest 5mm. Stud Bolt lengths (L*) do not include the height of points. Machine Bolt lengths (L) include the height of point. The length shown includes the height of the Raised Face in all cases.

| Nom Flge Size DN | PN 20 (Class 150) | | | | PN 50 (Class 300) | | | | PN 100 (Class 600) | | | PN 150 (Class 900) | | | PN 250 (Class 1500) | | | PN 420 (Class 2500) | | | Nom Flge Size DN | |
|------------------|-------------------|-----------------|-----|-----|-------------------|-----------------|-----|-----|--------------------|-----------------|---------------|--|-----------------|---------------|---------------------|-----------------|---------------|---------------------|-----------------|---------------|------------------|-----|
| | No. Bolts | Dia. Bolts ins. | L | | No. Bolts | Dia. Bolts ins. | L | | No. Bolts | Dia. Bolts ins. | Stud Bolts mm | No. Bolts | Dia. Bolts ins. | Stud Bolts mm | No. Bolts | Dia. Bolts ins. | Stud Bolts mm | No. Bolts | Dia. Bolts ins. | Stud Bolts mm | | |
| 15 | 4 | 1/2 | 60 | 45 | 4 | 1/2 | 65 | 55 | 4 | 1/2 | 80 | USE PN250 DIMENSIONS IN THESE SIZES | | | 4 | 3/4 | 105 | 4 | 3/4 | 125 | 15 | |
| 20 | 4 | 1/2 | 65 | 50 | 4 | 5/8 | 75 | 60 | 4 | 5/8 | 90 | | | | 4 | 3/4 | 115 | 4 | 3/4 | 125 | 20 | |
| 25 | 4 | 1/2 | 65 | 55 | 4 | 5/8 | 80 | 65 | 4 | 5/8 | 90 | | | | 4 | 7/8 | 125 | 4 | 7/8 | 140 | 25 | |
| 32 | 4 | 1/2 | 70 | 55 | 4 | 5/8 | 80 | 65 | 4 | 5/8 | 100 | | | | 4 | 7/8 | 125 | 4 | 1 | 150 | 32 | |
| 40 | 4 | 1/2 | 70 | 60 | 4 | 3/4 | 90 | 75 | 4 | 3/4 | 105 | | | | 4 | 1 | 140 | 4 | 1 1/8 | 170 | 40 | |
| 50 | 4 | 5/8 | 80 | 65 | 8 | 5/8 | 90 | 75 | 8 | 5/8 | 105 | | | | 8 | 7/8 | 145 | 8 | 1 | 175 | 50 | |
| 65 | 4 | 5/8 | 90 | 75 | 8 | 3/4 | 100 | 85 | 8 | 3/4 | 120 | | | | 8 | 1 | 160 | 8 | 1 1/8 | 195 | 65 | |
| 80 | 4 | 5/8 | 90 | 75 | 8 | 3/4 | 110 | 90 | 8 | 3/4 | 125 | 8 | 7/8 | 145 | 8 | 1 1/8 | 180 | 8 | 1 1/4 | 220 | 80 | |
| 90 | 8 | 5/8 | 90 | 75 | 8 | 3/4 | 110 | 95 | 8 | 7/8 | 140 | - | - | - | - | - | - | - | - | - | 90 | |
| 100 | 8 | 5/8 | 90 | 75 | 8 | 3/4 | 110 | 95 | 8 | 7/8 | 145 | 8 | 1 1/8 | 170 | 8 | 1 1/4 | 195 | 8 | 1 1/2 | 255 | 100 | |
| 125 | 8 | 3/4 | 90 | 80 | 8 | 3/4 | 120 | 100 | 8 | 1 | 165 | 8 | 1 1/4 | 190 | 8 | 1 1/2 | 250 | 8 | 1 3/4 | 300 | 125 | |
| 150 | 8 | 3/4 | 100 | 85 | 12 | 3/4 | 125 | 105 | 12 | 1 | 170 | 12 | 1 1/8 | 195 | 12 | 1 3/8 | 260 | 8 | 2 | 345 | 150 | |
| 200 | 8 | 3/4 | 110 | 90 | 12 | 7/8 | 140 | 110 | 12 | 1 1/8 | 195 | 12 | 1 3/8 | 220 | 12 | 1 5/8 | 290 | 12 | 2 | 380 | 200 | |
| 250 | 12 | 7/8 | 115 | 95 | 16 | 1 | 155 | 130 | 16 | 1 1/4 | 215 | 16 | 1 3/8 | 235 | 12 | 1 7/8 | 335 | 12 | 2 1/2 | 485 | 250 | |
| 300 | 12 | 7/8 | 120 | 100 | 16 | 1 1/8 | 170 | 145 | 20 | 1 1/4 | 220 | 20 | 1 3/8 | 255 | 16 | 2 | 375 | 12 | 2 3/4 | 540 | 300 | |
| 350 | 12 | 1 | 130 | 110 | 20 | 1 1/8 | 175 | 150 | 20 | 1 3/8 | 235 | 20 | 1 1/2 | 275 | 16 | 2 1/4 | 405 | | | | 350 | |
| 400 | 16 | 1 | 135 | 115 | 20 | 1 1/4 | 190 | 160 | 20 | 1 1/2 | 255 | 20 | 1 5/8 | 285 | 16 | 2 1/2 | 445 | | | | 400 | |
| 450 | 16 | 1 1/8 | 150 | 125 | 24 | 1 1/4 | 195 | 170 | 20 | 1 5/8 | 275 | 20 | 1 7/8 | 325 | 16 | 2 3/4 | 495 | | | | 450 | |
| 500 | 20 | 1 1/8 | 160 | 135 | 24 | 1 1/4 | 205 | 180 | 24 | 1 5/8 | 290 | 20 | 2 | 345 | 16 | 3 | 540 | | | | 500 | |
| 600 | 20 | 1 1/4 | 175 | 145 | 24 | 1 1/2 | 230 | 195 | 24 | 1 7/8 | 330 | 20 | 2 1/2 | 435 | 16 | 3 1/2 | 615 | | | | 600 | |
| 750 | 28 | 1 1/4 | 190 | 160 | 28 | 1 3/4 | 290 | 250 | 28 | 2 | 355 | PN150, 250 & 420 - NOT LISTED IN BS 3293 | | | | | | | | | | 750 |
| 900 | 32 | 1 1/2 | 215 | 180 | 32 | 2 | 325 | 280 | 28 | 2 1/2 | 400 | | | | | | | | | | | 900 |

Raised Face height of 2 mm for PN20 & 50 and 7 mm for PN100, 150, 250 & 420 is included in dimension L (Bolt Length).

MATERIAL SPECIFICATIONS

- ASTM A193 Grade B7** Standard specification for alloy steel and stainless steel bolting materials for high temperature service.
- ASTM A194 Grade 2H** Standard specification for carbon and alloy steel nuts for bolts for high pressure and high temperature service.
- ASTM A320** Standard specification for alloy steel bolting materials for low temperature service.
Grade L7 covers alloy steel stud bolts.
Grade L4 covers alloy steel nuts to suit Grade L7 stud bolts.

| Inch/ Metric Bolting interchangeable for ASME B16.5 flanges as below | |
|--|-----|
| FOR | USE |
| 1/2" | M14 |
| 5/8" | M16 |
| 3/4" | M20 |
| 7/8" | M24 |
| 1" | M27 |
| 1 1/8" | M30 |
| 1 1/4" | M33 |
| 1 3/8" | M36 |
| 1 1/2" | M39 |
| 1 5/8" | M42 |
| 1 3/4" | M45 |
| 1 7/8" | M48 |
| 2" | M52 |
| 2 1/4" | M56 |
| 2 1/2" | M64 |
| 2 3/4" | M72 |

FLANGE IDENTIFICATION CHART

A guide to the key dimensions of popular steel flange types

| Size (mm) | Table / Class | Diam. of Flange | Bolt Circle Diam. | No. of Bolts | Diam. / Length Bolts / Studs Steel Flanges | Diam. Holes | Flange Thickness Cast / Forged Steel |
|-----------|---------------|-----------------|-------------------|--------------|--|-------------|--------------------------------------|
| 15 | Table D | 95 | 67 | 4 | M12 x 45 | 14 | 5* |
| | Table E | 95 | 67 | 4 | M12 x 45 | 14 | 6* |
| | Table H | 115 | 83 | 4 | M16 x 60 | 18 | 13 |
| | ANSI 150 | 89 | 60.3 | 4 | 1/2 x 60 | 16 | 11.5 |
| | ANSI 300 | 95 | 66.7 | 4 | 1/2 x 65 | 16 | 14.5 |
| | ANSI 600 | 95 | 66.7 | 4 | 1/2 x 80 | 16 | 14.5 |
| PN 16 | 95 | 65 | 4 | -- | 14 | -- | |
| 20 | Table D | 100 | 73 | 4 | M12 x 45 | 14 | 5* |
| | Table E | 100 | 73 | 4 | M12 x 45 | 14 | 6* |
| | Table H | 115 | 83 | 4 | M16 x 60 | 18 | 13 |
| | ANSI 150 | 98 | 69.8 | 4 | 1/2 x 65 | 16 | 14 |
| | ANSI 300 | 117 | 82.5 | 4 | 5/8 x 75 | 20 | 16 |
| | ANSI 600 | 117 | 82.5 | 4 | 5/8 x 90 | 20 | 16 |
| PN 16 | 105 | 75 | 4 | -- | 14 | -- | |
| 25 | Table D | 115 | 83 | 4 | M12 x 45 | 14 | 5* |
| | Table E | 115 | 83 | 4 | M12 x 45 | 14 | 7* |
| | Table H | 120 | 87 | 4 | M16 x 60 | 18 | 14 |
| | ANSI 150 | 108 | 79.4 | 4 | 1/2 x 65 | 16 | 14 |
| | ANSI 300 | 124 | 88.9 | 4 | 5/8 x 80 | 20 | 18 |
| | ANSI 600 | 124 | 88.9 | 4 | 5/8 x 105 | 20 | 18 |
| PN 16 | 115 | 85 | 4 | -- | 14 | -- | |
| 32 | Table D | 120 | 87 | 4 | M12 x 50 | 14 | 6* |
| | Table E | 120 | 87 | 4 | M12 x 50 | 14 | 8* |
| | Table H | 135 | 98 | 4 | M16 x 65 | 18 | 17 |
| | ANSI 150 | 117 | 88.9 | 4 | 1/2 x 70 | 16 | 16 |
| | ANSI 300 | 133 | 98.4 | 4 | 5/8 x 80 | 20 | 22 |
| | ANSI 600 | 133 | 98.4 | 4 | 5/8 x 100 | 20 | 22 |
| PN 16 | 140 | 100 | 4 | -- | 18 | -- | |
| 40 | Table D | 135 | 98 | 4 | M12 x 50 | 14 | 6* |
| | Table E | 135 | 98 | 4 | M12 x 50 | 14 | 9* |
| | Table H | 140 | 105 | 4 | M16 x 65 | 18 | 17 |
| | ANSI 150 | 127 | 98.4 | 4 | 1/2 x 70 | 16 | 17 |
| | ANSI 300 | 156 | 114.3 | 4 | 3/4 x 90 | 23 | 22 |
| | ANSI 600 | 156 | 114.3 | 4 | 3/4 x 105 | 23 | 22 |
| PN 16 | 150 | 110 | 4 | -- | 18 | -- | |
| 50 | Table D | 150 | 114 | 4 | M16 x 60 | 18 | 8* |
| | Table E | 150 | 114 | 4 | M16 x 60 | 18 | 10* |
| | Table H | 165 | 127 | 4 | M16 x 75 | 18 | 19 |
| | ANSI 150 | 152 | 120.6 | 4 | 5/8 x 80 | 20 | 20 |
| | ANSI 300 | 165 | 127 | 8 | 5/8 x 90 | 20 | 22 |
| | ANSI 600 | 165 | 127 | 8 | 5/8 x 105 | 20 | 26 |
| PN 16 | 165 | 125 | 4 | -- | 16 | -- | |
| 65 | Table D | 165 | 127 | 4 | M16 x 60 | 18 | 8* |
| | Table E | 165 | 127 | 4 | M16 x 60 | 18 | 10* |
| | Table H | 185 | 146 | 8 | M16 x 75 | 18 | 19 |
| | ANSI 150 | 178 | 139.7 | 4 | 5/8 x 90 | 20 | 23 |
| | ANSI 300 | 191 | 149.2 | 8 | 3/4 x 100 | 23 | 26 |
| | ANSI 600 | 191 | 149.2 | 8 | 3/4 x 120 | 23 | 30 |
| PN 16 | 185 | 145 | 4 | -- | 18 | -- | |
| 80 | Table D | 185 | 146 | 4 | M16 x 60 | 18 | 10* |
| | Table E | 185 | 146 | 4 | M16 x 60 | 18 | 11* |
| | Table H | 205 | 165 | 8 | M16 x 75 | 18 | 22 |
| | ANSI 150 | 191 | 152.4 | 4 | 5/8 x 90 | 20 | 24 |
| | ANSI 300 | 210 | 168.3 | 8 | 3/4 x 110 | 23 | 32 |
| | ANSI 600 | 210 | 168.3 | 8 | 3/4 x 125 | 23 | 32 |
| PN 16 | 200 | 160 | 8 | -- | 18 | -- | |
| 100 | Table D | 215 | 178 | 4 | M16 x 65 | 18 | 10* |
| | Table E | 215 | 178 | 8 | M16 x 65 | 18 | 13 |
| | Table H | 230 | 191 | 8 | M16 x 85 | 18 | 25 |
| | ANSI 150 | 229 | 190.5 | 8 | 5/8 x 90 | 20 | 24 |
| | ANSI 300 | 254 | 200 | 8 | 3/4 x 110 | 23 | 32 |
| | ANSI 600 | 273 | 215.9 | 8 | 7/8 x 145 | 26 | 38 |
| PN 16 | 220 | 180 | 8 | -- | 18 | -- | |


*It is impractical to use thickness less than 12.00mm for plate flanges.

Dimensions AS 2129 - ANSI/ASME B16.5


FLANGE IDENTIFICATION CHART

| Size (mm) | Table / Class | Diam. of Flange | Bolt Circle Diam. | No. of Bolts | Diam. / Length Bolts / Studs Steel Flanges | Diam. Holes | Flange Thickness Cast / Forged Steel | |
|-----------|---------------|-----------------|-------------------|--------------|--|-------------|--------------------------------------|----|
| 125 | Table D | 255 | 210 | 8 | M16 x 65 | 18 | 22 | |
| | Table E | 255 | 210 | 8 | M16 x 65 | 18 | 14 | |
| | Table H | 280 | 235 | 8 | M20 x 95 | 22 | 29 | |
| | ANSI 150 | 254 | 215.9 | 8 | 3/4 x 90 | 23 | 24 | |
| | ANSI 300 | 279 | 234.9 | 8 | 3/4 x 120 | 23 | 35 | |
| | ANSI 600 | 330 | 266.7 | 8 | 1 x 165 | 29 | 45 | |
| | PN 16 | 250 | 210 | 8 | -- | 18 | -- | |
| 150 | Table D | 280 | 235 | 8 | M16 x 65 | 18 | 13 | |
| | Table E | 280 | 235 | 8 | M20x 65 | 22 | 17 | |
| | Table H | 305 | 260 | 12 | M20 x 95 | 22 | 29 | |
| | ANSI 150 | 279 | 241.3 | 8 | 3/4 x 100 | 23 | 26 | |
| | ANSI 300 | 318 | 269.9 | 12 | 3/4 x 125 | 23 | 37 | |
| | ANSI 600 | 356 | 292.1 | 12 | 1 x 170 | 29 | 48 | |
| | PN 16 | 285 | 240 | 8 | -- | 22 | -- | |
| 200 | Table D | 335 | 292 | 8 | M16 x 65 | 18 | 13 | |
| | Table E | 335 | 292 | 8 | M20 x 65 | 22 | 19 | |
| | Table H | 370 | 324 | 12 | M20 x 100 | 22 | 32 | |
| | ANSI 150 | 343 | 298.4 | 8 | 3/4 x 110 | 23 | 29 | |
| | ANSI 300 | 381 | 330.2 | 12 | 7/8 x 140 | 26 | 41 | |
| | ANSI 600 | 419 | 349.2 | 12 | 1 1/8 x 195 | 32 | 56 | |
| | | PN 10 | 340 | 295 | 8 | -- | 22 | -- |
| | | PN 16 | 340 | 280 | 12 | -- | 22 | -- |
| 250 | Table D | 405 | 356 | 8 | M20 x 75 | 22 | -- | |
| | Table E | 405 | 356 | 12 | M20 x 75 | 22 | 22 | |
| | Table H | 430 | 381 | 12 | M24 x 120 | 26 | 35 | |
| | ANSI 150 | 406 | 361.9 | 12 | 7/8 x 115 | 29 | 30 | |
| | ANSI 600 | 510 | 431.8 | 16 | 1 1/4 x 215 | 35 | 64 | |
| | | PN 10 | 395 | 350 | 8 | -- | 22 | -- |
| | | PN 16 | 405 | 350 | 12 | -- | 22 | -- |
| 300 | Table D | 455 | 406 | 12 | M20 x 85 | 22 | 22 | |
| | Table E | 455 | 406 | 12 | M24 x 85 | 26 | 25 | |
| | Table H | 490 | 438 | 16 | M24 x 110 | 26 | 41 | |
| | ANSI 150 | 483 | 431.8 | 12 | 7/8 x 120 | 26 | 32 | |
| | ANSI 300 | 520 | 450.8 | 16 | 1 1/8 x 170 | 32 | 51 | |
| | | PN 10 | 445 | 400 | 12 | -- | 22 | -- |
| | | PN 16 | 450 | 410 | 12 | -- | 25 | -- |
| 350 | Table D | 525 | 470 | 12 | M24 x 95 | 26 | 25 | |
| | Table E | 525 | 470 | 12 | M24 x 95 | 26 | 29 | |
| | Table H | 550 | 495 | 16 | M27 x 130 | 30 | 48 | |
| | ANSI 150 | 535 | 476.2 | 12 | 1 x 130 | 29 | 35 | |
| | ANSI 300 | 585 | 514.3 | 20 | 1 1/8 x 175 | 32 | 54 | |
| 375 | Table D | 550 | 495 | 12 | M24 x 95 | 26 | 22 | |
| | Table E | 550 | 495 | 12 | M24 x 95 | 26 | 32 | |
| 400 | Table D | 580 | 521 | 12 | M24 x 95 | 26 | 22 | |
| | Table E | 580 | 521 | 12 | M24 x 100 | 26 | 32 | |
| | Table H | 610 | 552 | 20 | M27 x 140 | 30 | 54 | |
| | ANSI 150 | 597 | 539.7 | 16 | 1 x 130 | 29 | 37 | |
| | ANSI 300 | 650 | 571.5 | 20 | 1 1/4 x 190 | 35 | 57 | |
| 450 | Table D | 640 | 584 | 12 | M24 x 95 | 26 | 25 | |
| | Table E | 640 | 584 | 16 | M24 x 120 | 26 | 35 | |
| | Table H | 675 | 610 | 20 | M30 x 160 | 33 | 60 | |
| | ANSI 150 | 635 | 577.8 | 16 | 1 1/8 x 150 | 32 | 40 | |
| | ANSI 300 | 710 | 628.6 | 24 | 1 1/4 x 195 | 35 | 60 | |
| 500 | Table D | 705 | 641 | 16 | M24 x 110 | 26 | 29 | |
| | Table E | 705 | 641 | 16 | M24 x 110 | 26 | 38 | |
| | Table H | 735 | 673 | 24 | M30 x 170 | 33 | 67 | |
| | ANSI 150 | 700 | 635 | 20 | 1 1/8 x 160 | 32 | 43 | |
| | ANSI 300 | 775 | 685.8 | 24 | 1 1/4 x 205 | 35 | 64 | |
| 600 | Table D | 825 | 756 | 16 | M27 x 120 | 30 | 32 | |
| | Table E | 825 | 756 | 16 | M30 x 140 | 33 | 48 | |
| | Table H | 850 | 781 | 24 | M33 x 200 | 36 | 76 | |
| | ANSI 150 | 815 | 749.3 | 20 | 1 1/4 x 175 | 35 | 48 | |
| | ANSI 300 | 915 | 812.8 | 24 | 1 1/2 x 230 | 42 | 70 | |

*It is impractical to use thickness less than 12.00mm for plate flanges.
Dimensions AS 2129 - ANSI/ASME B16.5



BLANK OR BLIND FLANGE



BOSS FLANGE - SLIP ON WELD OR SCR. B.S.P.

DIMENSIONS FOR LOOSE FLANGES




PLATE FLANGE SLIP ON WELD

WELD NECK FLANGE

COPPER ALLOY
 T.3 - Plate or Boss or Blank
 T.10 - Plate or Boss
 T.11 - Blank

FORGED OR PLATE STEEL
 T.6 - Plate or Boss or Blank, or Weldneck (except for valves)
 T.18 - Plate or Blank or Weldneck (except for valves)

| Nominal Size DN | Table D | | | | | | Table E | | | | | | Table F | | | | | | Nominal Size DN | | |
|-----------------|---------|-----------|----|---------------------|--------------|------------------|---------|-----------|----------|---------------------|--------------|------------------|---------|-----------|--------|---------------------|--------------|------------------|-----------------|-----|------|
| | Flange | | | Drilling | | | Flange | | | Drilling | | | Flange | | | Drilling | | | | | |
| | OD mm | Thickness | | Bolt Circle Dia. mm | No. of Bolts | Dia. of Bolts mm | OD mm | Thickness | | Bolt Circle Dia. mm | No. of Bolts | Dia. of Bolts mm | OD mm | Thickness | | Bolt Circle Dia. mm | No. of Bolts | Dia. of Bolts mm | | | |
| | T3 mm | ** T6 mm | | | | | T10 mm | T11 mm | ** T6 mm | | | | | T10 mm | T11 mm | ** T6 mm | | | | | |
| 15 | 95 | 6 | 5 | 67 | 4 | M12 | 95 | 6 | 6 | 6 | 67 | 4 | M12 | 95 | 8 | 8 | 10 | 67 | 4 | M12 | 15 |
| 20 | 100 | 6 | 5 | 73 | 4 | M12 | 100 | 6 | 6 | 6 | 73 | 4 | M12 | 100 | 8 | 8 | 10 | 73 | 4 | M12 | 20 |
| 25 | 115 | 8 | 5 | 83 | 4 | M12 | 115 | 8 | 8 | 7 | 83 | 4 | M12 | 120 | 10 | 10 | 10 | 87 | 4 | M16 | 25 |
| 32 | 120 | 8 | 6 | 87 | 4 | M12 | 120 | 8 | 8 | 8 | 87 | 4 | M12 | 135 | 10 | 10 | 13 | 98 | 4 | M16 | 32 |
| 40 | 135 | 10 | 6 | 98 | 4 | M12 | 135 | 10 | 10 | 9 | 98 | 4 | M12 | 140 | 11 | 11 | 13 | 105 | 4 | M16 | 40 |
| 50 | 150 | 10 | 8 | 114 | 4 | M16 | 150 | 10 | 10 | 10 | 114 | 4 | M16 | 165 | 11 | 12 | 16 | 127 | 4 | M16 | 50 |
| 65 | 165 | 11 | 8 | 127 | 4 | M16 | 165 | 11 | 11 | 10 | 127 | 4 | M16 | 185 | 13 | 13 | 16 | 146 | 8 | M16 | 65 |
| 80 | 185 | 13 | 10 | 146 | 4 | M16 | 185 | 13 | 13 | 11 | 146 | 4 | M16 | 205 | 14 | 15 | 16 | 165 | 8 | M16 | 80 |
| 100 | 215 | 16 | 10 | 178 | 4 | M16 | 215 | 16 | 16 | 13 | 178 | 8 | M16 | 230 | 17 | 17 | 19 | 191 | 8 | M16 | 100 |
| 125 | 255 | 17 | 13 | 210 | 8 | M16 | 255 | 17 | 17 | 14 | 210 | 8 | M16 | 280 | 19 | 20 | 22 | 235 | 8 | M20 | 125 |
| 150 | 280 | 17 | 13 | 235 | 8 | M16 | 280 | 17 | 17 | 17 | 235 | 8 | M20 | 305 | 22 | 23 | 22 | 260 | 12 | M20 | 150 |
| 200 | 335 | 19 | 13 | 292 | 8 | M16 | 335 | 19 | 20 | 19 | 292 | 8 | M20 | 370 | 25 | 28 | 25 | 324 | 12 | M20 | 200 |
| 250 | 405 | 19 | 16 | 356 | 8 | M20 | 405 | 22 | 25 | 22 | 356 | 12 | M20 | 430 | 25 | 32 | 29 | 381 | 12 | M24 | 250 |
| 300 | 455 | 22 | 19 | 406 | 12 | M20 | 455 | 25 | 28 | 25 | 406 | 12 | M24 | 490 | 29 | 37 | 32 | 438 | 16 | M24 | 300 |
| 350 | 525 | 25 | 22 | 470 | 12 | M24 | 525 | 25 | 32 | 29 | 470 | 12 | M24 | 550 | 32 | 42 | 35 | 495 | 16 | M27 | 350 |
| 400 | 580 | 25 | 22 | 521 | 12 | M24 | 580 | 25 | 36 | 32 | 521 | 12 | M24 | 610 | 32 | 47 | 41 | 552 | 20 | M27 | 400 |
| 450 | 640 | 29 | 25 | 584 | 12 | M24 | 640 | 29 | 41 | 35 | 584 | 16 | M24 | 675 | 35 | 52 | 44 | 610 | 20 | M30 | 450 |
| 500 | 705 | 32 | 29 | 641 | 16 | M24 | 705 | 32 | 46 | 38 | 641 | 16 | M24 | 735 | 38 | 57 | 51 | 673 | 24 | M30 | 500 |
| 600 | 825 | 35 | 32 | 756 | 16 | M27 | 825 | 38 | - | 48 | 756 | 16 | M30 | 850 | 41 | 68 | 57 | 781 | 24 | M33 | 600 |
| 700 | 910 | - | 35 | 845 | 20 | M27 | 910 | - | - | 51 | 845 | 20 | M30 | 935 | - | - | 60 | 857 | 24 | M33 | 700 |
| 750 | 995 | - | 41 | 927 | 20 | M30 | 995 | - | - | 54 | 927 | 20 | M33 | 1015 | - | - | 67 | 940 | 28 | M33 | 750 |
| 800 | 1060 | - | 41 | 984 | 20 | M33 | 1060 | - | - | 54 | 984 | 20 | M33 | 1060 | - | - | 68 | 984 | 28 | M33 | 800 |
| 900 | 1175 | - | 48 | 1092 | 24 | M33 | 1175 | - | - | 64 | 1092 | 24 | M33 | 1185 | - | - | 76 | 1105 | 32 | M36 | 900 |
| 1000 | 1255 | - | 51 | 1175 | 24 | M33 | 1255 | - | - | 67 | 1175 | 24 | M36 | 1275 | - | - | 83 | 1194 | 36 | M36 | 1000 |
| 1200 | 1490 | - | 60 | 1410 | 32 | M33 | 1490 | - | - | 79 | 1410 | 32 | M36 | 1530 | - | - | 95 | 1441 | 40 | M39 | 1200 |

| Nominal Size DN | Table H | | | | | | | | Table J | | | | | | Table R | | | | | | Nominal Size DN |
|-----------------|---------|-----------|---------|----|---------------|---------------------|--------------|------------------|---------|-------------------|-------------|---------------------|--------------|------------------|---------|--------------------|-------------|---------------------|--------------|------------------|-----------------|
| | Flange | | | | Drilling | | | | Flange | | | Drilling | | | Flange | | | Drilling | | | |
| | OD mm | Thickness | | | † Dia. R/F mm | Bolt Circle Dia. mm | No. of Bolts | Dia. of Bolts mm | OD mm | Thickness * T6 mm | Dia. R/F mm | Bolt Circle Dia. mm | No. of Bolts | Dia. of Bolts mm | OD mm | Thickness * T18 mm | Dia. R/F mm | Bolt Circle Dia. mm | No. of Bolts | Dia. of Bolts mm | |
| | T10 mm | T11 mm | * T6 mm | | | | | | | | | | | | | | | | | | |
| 15 | 115 | 10 | 11 | 13 | 57 | 83 | 4 | M16 | 115 | 16 | 57 | 83 | 4 | M16 | 115 | 19 | 64 | 83 | 4 | M16 | 15 |
| 20 | 115 | 10 | 11 | 13 | 57 | 83 | 4 | M16 | 115 | 16 | 57 | 83 | 4 | M16 | 115 | 19 | 64 | 83 | 4 | M16 | 20 |
| 25 | 120 | 11 | 12 | 14 | 64 | 87 | 4 | M16 | 120 | 19 | 64 | 87 | 4 | M16 | 125 | 22 | 76 | 95 | 4 | M16 | 25 |
| 32 | 135 | 11 | 13 | 17 | 76 | 98 | 4 | M16 | 135 | 19 | 76 | 98 | 4 | M16 | 135 | 22 | 76 | 98 | 4 | M16 | 32 |
| 40 | 140 | 13 | 14 | 17 | 83 | 105 | 4 | M16 | 140 | 22 | 83 | 105 | 4 | M16 | 150 | 25 | 89 | 114 | 4 | M20 | 40 |
| 50 | 165 | 13 | 16 | 19 | 102 | 127 | 4 | M16 | 165 | 25 | 102 | 127 | 4 | M20 | 165 | 25 | 102 | 127 | 8 | M16 | 50 |
| 65 | 185 | 14 | 17 | 19 | 114 | 146 | 8 | M16 | 185 | 25 | 114 | 146 | 8 | M20 | 185 | 29 | 114 | 146 | 8 | M20 | 65 |
| 80 | 205 | 16 | 19 | 22 | 127 | 165 | 8 | M16 | 205 | 32 | 127 | 165 | 8 | M20 | 205 | 32 | 127 | 165 | 8 | M20 | 80 |
| 100 | 230 | 19 | 23 | 25 | 152 | 191 | 8 | M16 | 230 | 35 | 152 | 191 | 8 | M20 | 240 | 35 | 152 | 197 | 8 | M24 | 100 |
| 125 | 280 | 22 | 27 | 29 | 178 | 235 | 8 | M20 | 280 | 38 | 178 | 235 | 8 | M24 | 280 | 41 | 178 | 235 | 12 | M24 | 125 |
| 150 | 305 | 25 | 30 | 29 | 210 | 260 | 12 | M20 | 305 | 38 | 210 | 260 | 12 | M24 | 305 | 44 | 210 | 260 | 12 | M24 | 150 |
| 200 | 370 | 32 | 39 | 32 | 260 | 324 | 12 | M20 | 370 | 41 | 260 | 324 | 12 | M24 | 370 | 51 | 260 | 324 | 12 | M27 | 200 |
| 250 | 430 | 35 | 45 | 35 | 311 | 381 | 12 | M24 | 430 | 48 | 311 | 381 | 12 | M27 | 430 | 60 | 311 | 387 | 16 | M27 | 250 |
| 300 | 490 | 38 | 52 | 41 | 362 | 438 | 16 | M24 | 490 | 51 | 362 | 438 | 16 | M27 | 510 | 70 | 362 | 457 | 16 | M30 | 300 |
| 350 | 550 | 41 | 58 | 48 | 419 | 495 | 16 | M27 | 550 | 57 | 419 | 495 | 16 | M30 | 585 | 79 | 419 | 527 | 16 | M33 | 350 |
| 400 | 610 | 44 | 64 | 54 | 483 | 552 | 20 | M27 | 610 | 64 | 483 | 552 | 20 | M30 | 640 | 89 | 483 | 584 | 20 | M33 | 400 |
| 450 | 675 | 48 | 71 | 60 | 533 | 610 | 20 | M30 | 675 | 70 | 533 | 610 | 20 | M33 | 735 | 98 | 572 | 673 | 20 | M36 | 450 |
| 500 | 735 | 51 | 78 | 67 | 597 | 673 | 24 | M30 | 735 | 79 | 597 | 673 | 24 | M33 | 805 | 105 | 622 | 730 | 20 | M39 | 500 |
| 600 | 850 | 57 | 92 | 76 | 699 | 781 | 24 | M33 | 850 | 92 | 699 | 781 | 24 | M36 | - | - | - | - | - | - | - |

NOTES:

- (1) All dimensions are in millimetres (mm).
- (2) Only metric preferred sizes listed, except for DN 750 which is a Non-preferred size.
- ** (3) It is impractical to use flange thickness less than 12mm for Steel Plate Flanges.
- * (4) Thickness includes 1.6mm height for the Raised Face.
- † (5) The Raised Face is non-preferred for Table "H".
- (6) It is normal practice to supply Steel Flanges to Tables A, D, C, E, F and H. - Flat Faced.
- (7) All copper alloy flanges shall be Flat Faced.
- (8) All flanges shall be drilled to Standard Tables unless otherwise specified. (For Bolt dimensions see separate page).


IMPORTANT: For DN 150 and DN 200 Flanges, the O.D. of pipe being used must be specified. Dimensions for Flange Tables A, C, K, S and T on application.

Steel hexagon Bolts and Nuts (XOX) are recommended for use within a temperature range of -50°C to +300°C. Outside of this temperature range, Stud Bolts should be used as recommended in AS.2528.

A quick reference chart for sizing bolts and nuts for a range of regularly used standard flanges is given below:

APPLICABLE TO PLATE & FORGED STEEL LOOSE FLANGES ONLY

Note: Integral valve flanges quite often differ in thickness to equivalent loose flanges. When integral flanges are involved due allowance should be made to bolt lengths.



| Nominal Flange Size DN | Table D | | Table E | | Table F | | Table H | |
|------------------------|----------------------|----------------------------|----------------------|----------------------------|----------------------|----------------------------|----------------------|----------------------------|
| | No. Bolts Per Flange | XOX Bolt & Nut dia. x lgth | No. Bolts Per Flange | XOX Bolt & Nut dia. x lgth | No. Bolts Per Flange | XOX Bolt & Nut dia. x lgth | No. Bolts Per Flange | XOX Bolt & Nut dia. x lgth |
| 15 | 4 | M12 x 40mm* | 4 | M12 x 40mm* | 4 | M12 X 40mm* | 4 | M16 x 45mm* |
| 20 | 4 | M12 x 40mm* | 4 | M12 x 40mm* | 4 | M12 X 40mm* | 4 | M16 x 45mm* |
| 25 | 4 | M12 x 40mm* | 4 | M12 x 40mm* | 4 | M16 X 45mm* | 4 | M16 x 50mm* |
| 32 | 4 | M12 x 40mm* | 4 | M12 x 40mm* | 4 | M16 X 45mm* | 4 | M16 x 55mm* |
| 40 | 4 | M12 x 40mm* | 4 | M12 x 40mm* | 4 | M16 X 45mm* | 4 | M16 x 55mm* |
| 50 | 4 | M16 x 45mm* | 4 | M16 x 45mm* | 4 | M16 X 50mm* | 4 | M16 x 60mm* |
| 65 | 4 | M16 x 45mm* | 4 | M16 x 45mm* | 8 | M16 X 50mm* | 8 | M16 x 60mm* |
| 80 | 4 | M16 x 45mm* | 4 | M16 x 45mm* | 8 | M16 X 50mm* | 8 | M16 x 65mm* |
| 100 | 4 | M16 x 45mm* | 8 | M16 x 45mm* | 8 | M16 X 60mm* | 8 | M16 x 70mm* |
| 125 | 8 | M16 x 45mm* | 8 | M16 x 50mm* | 8 | M20 X 70mm* | 8 | M20 x 80mm* |
| 150 | 8 | M16 x 45mm* | 8 | M20 x 60mm* | 12 | M20 X 70mm* | 12 | M20 x 80mm* |
| 200 | 8 | M16 x 45mm* | 8 | M20 x 60mm* | 12 | M20 X 75mm* | 12 | M20 x 90mm* |
| 250 | 8 | M20 x 55mm* | 12 | M20 x 70mm* | 12 | M24 X 85mm* | 12 | M24 x 100mm* |
| 300 | 12 | M20 x 60mm* | 12 | M24 x 80mm* | 16 | M24 X 100mm* | 16 | M24 x 110mm* |
| 350 | 12 | M24 x 75mm* | 12 | M24 x 85mm* | 16 | M27 X 100mm* | 16 | M27 x 130mm* |
| 400 | 12 | M24 x 75mm* | 12 | M24 x 100mm* | 20 | M27 X 120mm* | 20 | M27 x 140mm* |
| 450 | 12 | M24 x 80mm* | 16 | M24 x 100mm* | 20 | M30 X 130mm* | 20 | M30 x 160mm* |
| 500 | 16 | M24 x 85mm* | 16 | M24 x 110mm* | 24 | M30 X 140mm* | 24 | M30 x 170mm* |
| 600 | 16 | M27 x 100mm* | 16 | M30 x 130mm* | 24 | M33 X 150mm* | 24 | M33 x 190mm* |
| 700 | 20 | M27 x 100mm* | 20 | M30 x 140mm* | 24 | M33 X 160mm* | | |
| 750 | 20 | M30 x 120mm* | 20 | M33 x 150mm* | 28 | M33 X 170mm* | | |
| 800 | 20 | M33 x 120mm* | 20 | M33 x 150mm* | 28 | M33 X 180mm* | | |
| 900 | 24 | M33 x 140mm* | 24 | M33 x 170mm* | 32 | M36 X 200mm* | | |
| 1000 | 24 | M33 x 140mm* | 24 | M36 x 180mm* | 36 | M36 X 220mm* | | |
| 1200 | 32 | M33 x 160mm* | 32 | M36 x 200mm* | 40 | M39 X 240mm* | | |

- Notes
- All dimensions are in millimetres (mm).
 - High strength structural bolts to AS 1252 may be substituted for property class 8.8 bolts if agreed to by the purchaser.
 - Bolts to AS 1252 are heavy hexagon series and the selection of such bolts would be subject to space being available on the relevant flange.

| Temp in °C | Temperature / Pressure Ratings for Carbon Steel Flanges | | | |
|------------------------------------|---|------|------|------|
| | Maximum Allowable Pressure in kPa by Flange Tables (For approximate PSI divide by 7) | | | |
| | D | E | F | H |
| -50 to 232 | 700 | 1400 | 2100 | 3500 |
| 250 | 650 | 1300 | 2000 | 3300 |
| 275 | 600 | 1200 | 1800 | 3100 |
| 300 | 570 | 1100 | 1700 | 2900 |
| 325 | 550 | 1000 | 1600 | 2600 |
| 350 | 500 | 950 | 1400 | 2400 |
| 375 | 450 | 900 | 1300 | 2200 |
| 400 | 400 | 800 | 1200 | 2000 |
| 425 | 350 | 700 | 1000 | 1700 |
| 450 | | | | 1300 |
| 475 | | | | 900 |
| Max. Hydrostatic Test Pressure kPa | 1050 | 2100 | 3150 | 5250 |

Bolt lengths listed apply to flat-faced or 1.6mm raised face flanges with allowance for 1.6mm gasket thickness.

*For approximate Stud Bolt Lengths take the XOX Bolt Length and add the metric diameter in mm rounded to the nearest 5mm increment up.

Note: (This does not include length of point)

This chart shows bolt diameters as recommended in AS.2129. Some of these are Non-preferred sizes e.g. (M27), (M33) and (M39) which are not readily available in Australia.

Stud Bolts should be used as alternatives to bolts where the size is greater than M24 and it is therefore suggested that Stud Bolts as specified in AS.2528 or BS.4882 should be used.

Inch series bolts interchangeable as follows:

| FOR | USE | FOR | USE |
|-------|-----|--------|-------|
| 1/4" | M6 | 7/8" | M24 |
| 5/16" | M8 | 1" | (M27) |
| 3/8" | M10 | 1 1/8" | M30 |
| 1/2" | M12 | 1 1/4" | (M33) |
| 5/8" | M16 | 1 3/8" | M36 |
| 3/4" | M20 | 1 1/2" | (M39) |

BOLT HOLE DIAMETERS

For bolts to M24, clearance hole 2mm larger.

Above M24, clearance hole 3mm larger.

XOX BOLTS & NUTS

XOX is the trade term used for H.R.H. commercial steel bolts and nuts.

H.R.H. denotes Hexagon Head x Round Shank x Hexagon Nut.

| XOX Bolting | | |
|------------------------------|----------------------------------|--------------|
| Temp. Range: -50°C to +300°C | | |
| Flange Specifications | | |
| Table | Bolts | Nuts |
| D, E, F | AS 1110 Gr.4.6 or AS 1111 Gr.4.6 | AS 1112 Gr.5 |
| H | AS 1110 Gr.8.8 | AS 1112 Gr.8 |

Grade C350 pipe is a lightweight, high strength pipe for general mechanical and structural applications.

C350 is manufactured by cold-forming and high frequency electric resistance welding.

C350 is available in black, ILG and galvanized finishes.

Also available with one or both ends swaged as follows:

| NB | XL | L |
|----|----|---|
| 20 | ✓ | X |
| 25 | ✓ | ✓ |
| 32 | ✓ | ✓ |
| 40 | ✓ | ✓ |
| 50 | ✓ | X |

SPECIFICATION

Grade C350 pipe is manufactured and tested to meet the requirement of the following specifications:

- AS 1163 Structural Steel Hollow Sections (Grade C350, C350L0).
- AS/NZ 4792 Hot dip galvanized (zinc) coatings on ferrous hollow sections by a continuous or a specialised process.

MECHANICAL PROPERTIES

| | |
|--------------------------------|--------|
| Minimum Yield Strength | 350MPa |
| Minimum Tensile Strength | 450MPa |
| Minimum Elongation in 5.65 √So | 20% |

SUPPLY CONDITIONS

| | |
|---------------------|---------------------------------|
| Surface Finish | Black/ILG/Galvanized |
| Straightness |] Refer to Australian Standards |
| Thickness Tolerance | |
| Dimension Tolerance | |

| | |
|------------------|------------|
| Standard Length | 6.5m |
| Length Tolerance | +50mm/-0mm |

GALVANIZING

Grade C350 pipe is manufactured and tested to meet the requirement of AS 4792 Galvanized Coatings.

Min. Ave Coating Mass 300g/m²

The coating adherence of the galvanizing is satisfactory for the pipe to be bent to a radius 6 times the diameter of the pipe.

WELDING

The following consumables are recommended by AS 1554.1 when welding C350 sections.

Manual metal-arc (MMAW) E41XX, E48XX

Gas metal-arc (MIG) (GMAW) W50X

Mass and Bundling Data - Calculated in accordance with AS 1163

| Dimensions | | Bundling | | | Mass | | | | | | |
|-------------------------------|------|--------------------|----------------------------|-----------------------|----------------------|--------------|-------|---------|-------|-----------------|-------|
| Designation d _o | t | Nominal Size DN | Bundle Dimensions mm | Lengths Per Bundle | Metres Per Bundle | Nominal Mass | | | | Mass per Bundle | |
| | | | | | | kg/m | | m/tonne | | tonnes | |
| (mm) | (mm) | (mm) | W x H | 6.5m | m | Black | Galv. | Black | Galv. | Black | Galv. |
| 26.9 x 2.0 CHS | | 20 XL | 350 306 | 127 | 825.5 | 1.23 | 1.29 | 814 | 767 | 1.010 | 1.070 |
| 2.3 CHS | | 20 LT | 350 306 | 127 | 825.5 | 1.40 | 1.46 | 717 | 680 | 1.150 | 1.200 |
| 33.7 x 2.0 CHS | | 25 XL | 372 327 | 91 | 591.5 | 1.56 | 1.64 | 640 | 602 | 0.920 | 0.970 |
| 2.6 CHS | | 25 LT | 372 327 | 91 | 591.5 | 1.99 | 2.07 | 501 | 497 | 1.180 | 1.230 |
| 42.4 x 2.0 CHS | | 32 XL | 383 337 | 61 | 396.5 | 1.99 | 2.10 | 502 | 473 | 0.790 | 0.830 |
| 2.6 CHS | | 32 LT | 383 337 | 61 | 396.5 | 2.55 | 2.65 | 392 | 374 | 1.010 | 1.050 |
| 48.3 x 2.3 CHS | | 40 XL | 436 384 | 61 | 396.5 | 2.61 | 2.73 | 383 | 364 | 1.030 | 1.080 |
| 2.9 CHS | | 40 LT | 436 384 | 61 | 396.5 | 3.25 | 3.36 | 308 | 295 | 1.290 | 1.330 |
| 60.3 x 2.3 CHS | | 50 XL | 422 374 | 37 | 240.5 | 3.29 | 3.44 | 304 | 288 | 0.790 | 0.830 |
| 2.9 CHS | | 50 LT | 422 374 | 37 | 240.5 | 4.11 | 4.25 | 244 | 234 | 0.990 | 1.020 |
| 76.1 x 2.3 CHS | | 65 XL | 533 472 | 37 | 240.5 | 4.19 | 4.33 | 239 | 231 | 1.007 | 1.040 |
| 3.2 CHS | | 65 LT | 533 472 | 37 | 240.5 | 5.75 | 5.94 | 174 | 167 | 1.380 | 1.430 |
| 88.9 x 2.6 CHS | | 80 XL | 445 397 | 19 | 123.5 | 5.53 | 5.75 | 181 | 174 | 0.683 | 0.710 |
| 3.2 CHS | | 80 LT | 445 397 | 19 | 123.5 | 6.76 | 6.98 | 148 | 143 | 0.840 | 0.860 |
| 101.6 x 2.6 CHS | | 90 XL | 508 454 | 19 | 123.5 | 6.35 | 6.60 | 158 | 152 | 0.784 | 0.815 |
| 3.2 CHS | | 90 LT | 508 454 | 19 | 123.5 | 7.70 | 8.04 | 129 | 124 | 0.960 | 0.990 |
| 114.3 x 3.2 CHS | | 100 XL | 572 510 | 19 | 123.5 | 8.77 | 9.05 | 114 | 110 | 1.083 | 1.118 |
| 3.6 CHS | | 100 LT | 572 510 | 19 | 123.5 | 9.83 | 10.11 | 102 | 98.6 | 1.214 | 1.249 |
| 139.7 x 3.0 CHS | | 125 XL | 698 382 | 13 | 84.5 | 10.11 | 10.50 | 98.9 | 95.2 | 0.855 | 0.887 |
| 3.5 CHS | | 125 LT | 698 382 | 13 | 84.5 | 11.76 | 12.10 | 85.1 | 82.4 | 0.993 | 1.022 |
| 165.1 x 3.5 CHS | | 150 LT | 660 451 | 10 | 65 | 13.95 | 14.40 | 71.7 | 69.4 | 0.907 | 0.936 |

Notes:

LT = Light, XL = Extra Light

The term "tube" is synonymous with the term "pipe".

SPECIFICATION

C250 pipe is manufactured and tested to meet the requirement of the following specifications:

- AS 1074 Steel tubes and tubulars for ordinary service.
- AS 1163 Structural steel hollow sections (Grade C250, C250L0).

WORKING PRESSURES - WELDED JOINTS

Where AS 1074 pipe is used in pressure piping covered by AS 4041, the maximum pressure shall not exceed 1210 kPa for AS 1074 pipe up to and including DN 100 and 1030 kPa for AS 1074 pipe exceeding DN 100.

END PROCESSING OPTIONS

- Plain End
- Shouldered
- Roll Grooved
- Threaded

THREADED PIPE

Screwed on one or both ends in accordance with AS 1074. The tapered Whitworth thread used complies with the requirements of AS 1722, Part 1 and is suitable for both parallel and taper threaded sockets.

MECHANICAL PROPERTIES

| | |
|--------------------------------|--------|
| Minimum Yield Strength | 250MPa |
| Minimum Tensile Strength | 320MPa |
| Minimum Elongation in 5.65 √So | 20% |

SUPPLY CONDITIONS

| | |
|---------------------|---------------------------------|
| Surface Finish | Black/Painted/Galvanized/ILG |
| Straightness |] Refer to Australian Standards |
| Thickness Tolerance | |
| Dimension Tolerance | |
| Standard Length | 6.5m |
| Length Tolerance | +50mm/-0mm |

WORKING PRESSURES - THREADED JOINTS TAPER/PARALLEL THREAD

| Nom. Size DN | Type of Service | | | | | | | | | | |
|--------------|-------------------|-------|--------------|-------------------|-----|------------------|-----|---|-----|------------------|-----|
| | Water & Inert Oil | | LPG | Fuel Oil | | | | Other Applications (including Steam & Compressed Air) | | | |
| | Med. | Heavy | Med. & Heavy | Medium Press Temp | | Heavy Press Temp | | Medium Press Temp | | Heavy Press Temp | |
| (mm) | kPa | kPa | kPa | kPa | °C | kPa | °C | kPa | °C | kPa | °C |
| 25 | 2070 | 2410 | 140 | 1030 | 100 | 1210 | 192 | 1210 | 100 | 1210 | 192 |
| 32 | 1720 | 2070 | 140 | 1030 | 100 | 1030 | 192 | 1030 | 100 | 1030 | 192 |
| 40 | 1720 | 2070 | 140 | 1030 | 100 | 1030 | 192 | 1030 | 100 | 1030 | 192 |
| 50 | 1380 | 1720 | 140 | 860 | 100 | 860 | 192 | 860 | 100 | 860 | 192 |
| 65 | 1380 | 1720 | - | 860 | 100 | 860 | 192 | 860 | 100 | 860 | 192 |
| 80 | 1380 | 1720 | - | 860 | 100 | 860 | 192 | 860 | 100 | 860 | 192 |
| 100 | 1030 | 1380 | - | 690 | 100 | 850 | 192 | 690 | 100 | 690 | 192 |
| 125 | 1030 | 1380 | - | - | - | - | - | - | - | - | - |
| 150 | 860 | 1030 | - | - | - | - | - | - | - | - | - |

| CHS Grade C250 | | | | | | | | | | | Mass and Bundling Data - Calculated in accordance with AS 1163 | | | | | | | | | | |
|---------------------------------|--------------------|----------------------------|-----------------------|----------------------|--------------|-------|---------|-------|-----------------|-------|--|--|--|--|--|--|--|--|--|--|--|
| Dimensions | | Bundling | | | Mass | | | | | | | | | | | | | | | | |
| Designation d _o t | Nominal Size DN | Bundle Dimensions mm | Lengths Per Bundle | Metres Per Bundle | Nominal Mass | | | | Mass per Bundle | | | | | | | | | | | | |
| | | | | | kg/m | | m/tonne | | tonnes | | | | | | | | | | | | |
| (mm) | (mm) | W x H | 6.5m | m | Black | Galv. | Black | Galv. | Black | Galv. | | | | | | | | | | | |
| 26.9 x 2.6 CHS | 20 M | 350 306 | 127 | 825.5 | 1.56 | 1.62 | 642 | 613 | 1.29 | 1.32 | | | | | | | | | | | |
| 3.2 CHS | 20 H | 350 306 | 127 | 825.5 | 1.87 | 1.93 | 535 | 522 | 1.54 | 1.59 | | | | | | | | | | | |
| 33.7 x 3.2 CHS | 25 M | 372 327 | 91 | 591.5 | 2.41 | 2.49 | 415 | 406 | 1.43 | 1.47 | | | | | | | | | | | |
| 4.0 CHS | 25 H | 372 327 | 91 | 591.5 | 2.94 | 3.02 | 340 | 330 | 1.74 | 1.78 | | | | | | | | | | | |
| 42.4 x 3.2 CHS | 32 M | 383 337 | 61 | 396.5 | 3.10 | 3.20 | 322 | 310 | 1.23 | 1.27 | | | | | | | | | | | |
| 4.0 CHS | 32 H | 383 337 | 61 | 396.5 | 3.80 | 3.90 | 263 | 255 | 1.51 | 1.54 | | | | | | | | | | | |
| 48.3 x 3.2 CHS | 40 M | 436 384 | 61 | 396.5 | 3.57 | 3.68 | 280 | 270 | 1.41 | 1.46 | | | | | | | | | | | |
| 4.0 CHS | 40 H | 436 384 | 61 | 396.5 | 4.38 | 4.49 | 228 | 221 | 1.74 | 1.78 | | | | | | | | | | | |
| 60.3 x 3.6 CHS | 50 M | 422 374 | 37 | 240.5 | 5.03 | 5.18 | 199 | 192 | 1.21 | 1.25 | | | | | | | | | | | |
| 4.5 CHS | 50 H | 422 374 | 37 | 240.5 | 6.19 | 6.33 | 161 | 157 | 1.49 | 1.52 | | | | | | | | | | | |
| 76.1 x 3.6 CHS | 65 M | 533 472 | 37 | 240.5 | 6.43 | 6.61 | 156 | 150 | 1.55 | 1.59 | | | | | | | | | | | |
| 4.5 CHS | 65 H | 533 472 | 37 | 240.5 | 7.93 | 8.12 | 126 | 123 | 1.91 | 1.95 | | | | | | | | | | | |
| 88.9 x 4 CHS | 80 M | 445 397 | 19 | 123.5 | 8.37 | 8.58 | 120 | 116 | 1.03 | 1.06 | | | | | | | | | | | |
| 4.9 CHS | 80 H | 445 397 | 19 | 123.5 | 10.3 | 10.5 | 96.8 | 94.4 | 1.28 | 1.30 | | | | | | | | | | | |
| 101.6 x 4.0 CHS | 90 M | 508 454 | 19 | 123.5 | 9.63 | 9.88 | 104 | 100 | 1.19 | 1.22 | | | | | | | | | | | |
| 4.9 CHS | 90 H | 508 454 | 19 | 123.5 | 11.9 | 12.2 | 84 | 81.7 | 1.47 | 1.5 | | | | | | | | | | | |
| 114.3 x 4.5 CHS | 100 M | 571 509 | 19 | 123.5 | 12.2 | 12.4 | 82.2 | 79.8 | 1.5 | 1.54 | | | | | | | | | | | |
| 5.4 CHS | 100 H | 571 509 | 19 | 123.5 | 14.5 | 14.3 | 69.1 | 67.4 | 1.79 | 1.82 | | | | | | | | | | | |
| 139.7 x 5.0 CHS | 125 M | 698 382 | 13 | 84.5 | 16.6 | 16.9 | 60.2 | 58.6 | 1.4 | 1.43 | | | | | | | | | | | |
| 5.4 CHS | 125 H | 698 382 | 13 | 84.5 | 17.9 | 18.2 | 55.9 | 54.6 | 1.51 | 1.54 | | | | | | | | | | | |
| 165.1 x 5.0 CHS | 150 M | 660 451 | 10 | 65 | 19.7 | 20.1 | 50.7 | 49.3 | 1.28 | 1.31 | | | | | | | | | | | |
| 5.4 CHS | 150 H | 660 451 | 10 | 65 | 21.7 | 21.57 | 45.9 | 46 | 1.38 | 1.41 | | | | | | | | | | | |

M = Medium, H = Heavy

| Nominal Size DN | Outside Diameter (mm) | Nominal Wall Thickness & Inside Diameter (mm) | | | | | | | |
|-----------------|-----------------------|---|-----------------|----------------|-----------------|----------------|-----------------|----------------|-----------------|
| | | Schedule 5S | | Schedule 10S | | Schedule 40S | | Schedule 80S | |
| | | Wall Thickness | Inside Diameter | Wall Thickness | Inside Diameter | Wall Thickness | Inside Diameter | Wall Thickness | Inside Diameter |
| 6 | 10.29 | - | - | 1.24 | 7.81 | 1.73 | 6.83 | 2.41 | 5.47 |
| 8 | 13.72 | - | - | 1.65 | 10.42 | 2.24 | 9.24 | 3.02 | 7.68 |
| 10 | 17.15 | - | - | 1.65 | 13.85 | 2.31 | 12.53 | 3.20 | 10.75 |
| 15 | 21.34 | 1.65 | 18.04 | 2.11 | 17.12 | 2.77 | 15.80 | 3.73 | 13.88 |
| 20 | 26.67 | 1.65 | 23.37 | 2.11 | 22.45 | 2.87 | 20.93 | 3.91 | 18.85 |
| 25 | 33.40 | 1.65 | 30.10 | 2.77 | 27.86 | 3.38 | 26.64 | 4.55 | 24.30 |
| 32 | 42.16 | 1.65 | 38.86 | 2.77 | 36.62 | 3.56 | 35.04 | 4.85 | 32.46 |
| 40 | 48.26 | 1.65 | 44.96 | 2.77 | 42.72 | 3.68 | 40.90 | 5.08 | 38.10 |
| 50 | 60.33 | 1.65 | 57.03 | 2.77 | 54.79 | 3.91 | 52.51 | 5.54 | 49.25 |
| 65 | 73.03 | 2.11 | 68.81 | 3.05 | 66.93 | 5.16 | 62.71 | 7.01 | 59.01 |
| 80 | 88.90 | 2.11 | 84.68 | 3.05 | 82.80 | 5.49 | 77.92 | 7.62 | 73.66 |
| 100 | 114.30 | 2.11 | 110.08 | 3.05 | 108.20 | 6.02 | 102.26 | 8.56 | 97.18 |
| 125 | 141.30 | 2.77 | 135.76 | 3.40 | 134.50 | 6.55 | 128.19 | 9.52 | 122.25 |
| 150 | 168.28 | 2.77 | 162.74 | 3.40 | 161.47 | 7.11 | 154.05 | 10.97 | 146.33 |
| 200 | 219.08 | 2.77 | 213.54 | 3.76 | 211.56 | 8.18 | 202.72 | 12.70 | 193.68 |
| 250 | 273.05 | 3.40 | 266.24 | 4.19 | 264.67 | 9.27 | 254.51 | 12.70 | 247.65 |
| 300 | 323.85 | 3.96 | 315.93 | 4.57 | 314.71 | 9.52 | 304.08 | 12.70 | 298.45 |
| 350 | 355.60 | 3.96 | 347.68 | 4.78 | 346.05 | - | - | - | - |
| 400 | 406.40 | 4.19 | 398.02 | 4.78 | 396.85 | - | - | - | - |
| 450 | 457.20 | 4.19 | 448.82 | 4.78 | 447.65 | - | - | - | - |
| 500 | 508.00 | 4.78 | 498.45 | 5.54 | 496.93 | - | - | - | - |
| 600 | 609.60 | 5.54 | 598.53 | 6.35 | 596.90 | - | - | - | - |
| 750 | 762.00 | 6.35 | 749.30 | 7.92 | 746.16 | - | - | - | - |

PRESSURE CONVERSION TABLE

The SI unit of pressure and stress is the NEWTON PER SQUARE METRE which has been given the special name PASCAL - Symbol Pa. The pascal is too small for most normal uses and suitable multiple units preferred for Australia are:

kilopascal: Symbol - kPa (= 1000 Pa) **megapascal:** Symbol - MPa (= 1,000,000 Pa)
 (1 N/m² = 0.000145 lbf/in² = 1Pa) (1 N/mm² = 145 lbf/in² = 1MPa)

PSI (lbf/in²) to kPa • PRESSURE - STRESS CONVERSION CHART

- (A) To use, locate "given pressure" in "given pressure" column (coloured blue) whether lbf/in² or kPa.
- (B) If "given pressure" is in pounds force per square inch (lbf/in²), read kilopascals (kPa) in right hand column.
- (C) If "given pressure" is in kilopascals (kPa), read pounds force per square inch (lbf/in²) in left hand column.
- (D) Example: (i) Given pressure is 100 lbf/in² = 689 kPa from right hand column
 (ii) Given pressure is 100kPa = 14.50 lbf/in² from left hand column

| 1 to 35 | | | 36 to 70 | | | 71 to 125 | | | 130 to 80,000 | | | | |
|---------------------|----------------|--------|---------------------|----------------|--------|---------------------|----------------|-----|---------------------|----------------|---------|---|-------|
| lbf/in ² | Given Pressure | kPa | lbf/in ² | Given Pressure | kPa | lbf/in ² | Given Pressure | kPa | lbf/in ² | Given Pressure | kPa | = | MPa |
| 0.15 | 1 | 6.89 | 5.22 | 36 | 248.21 | 10.30 | 71 | 490 | 18.85 | 130 | 896 | = | 0.90 |
| 0.29 | 2 | 13.79 | 5.37 | 37 | 255.11 | 10.44 | 72 | 496 | 19.58 | 135 | 931 | = | 0.93 |
| 0.44 | 3 | 20.68 | 5.51 | 38 | 262.00 | 10.59 | 73 | 503 | 20.31 | 140 | 965 | = | 0.97 |
| 0.58 | 4 | 27.58 | 5.66 | 39 | 268.9 | 10.73 | 74 | 510 | 21.03 | 145 | 1000 | = | 1.00 |
| 0.73 | 5 | 34.47 | 5.80 | 40 | 275.79 | 10.88 | 75 | 517 | 21.76 | 150 | 1034 | = | 1.03 |
| 0.87 | 6 | 41.37 | 5.95 | 41 | 282.69 | 11.02 | 76 | 524 | 22.48 | 155 | 1069 | = | 1.07 |
| 1.02 | 7 | 48.26 | 6.09 | 42 | 289.58 | 11.17 | 77 | 531 | 23.21 | 160 | 1103 | = | 1.10 |
| 1.16 | 8 | 55.16 | 6.24 | 43 | 296.48 | 11.31 | 78 | 538 | 23.93 | 165 | 1138 | = | 1.14 |
| 1.31 | 9 | 62.05 | 6.38 | 44 | 303.37 | 11.46 | 79 | 545 | 24.61 | 170 | 1172 | = | 1.17 |
| 1.45 | 10 | 68.95 | 6.53 | 45 | 310.26 | 11.60 | 80 | 552 | 25.38 | 175 | 1207 | = | 1.21 |
| 1.60 | 11 | 75.84 | 6.67 | 46 | 317.16 | 11.75 | 81 | 558 | 26.11 | 180 | 1241 | = | 1.24 |
| 1.74 | 12 | 82.74 | 6.82 | 47 | 324.05 | 11.89 | 82 | 565 | 26.83 | 185 | 1276 | = | 1.28 |
| 1.89 | 13 | 89.63 | 6.96 | 48 | 330.95 | 12.04 | 83 | 572 | 27.56 | 190 | 1310 | = | 1.31 |
| 2.03 | 14 | 96.53 | 7.11 | 49 | 337.84 | 12.18 | 84 | 579 | 28.28 | 195 | 1344 | = | 1.34 |
| 2.18 | 15 | 103.42 | 7.25 | 50 | 344.74 | 12.33 | 85 | 586 | 29.01 | 200 | 1379 | = | 1.38 |
| 2.32 | 16 | 110.32 | 7.40 | 51 | 351.63 | 12.47 | 86 | 593 | 36.26 | 250 | 1724 | = | 1.73 |
| 2.47 | 17 | 117.21 | 7.54 | 52 | 358.53 | 12.62 | 87 | 600 | 43.51 | 300 | 2068 | = | 2.07 |
| 2.61 | 18 | 124.11 | 7.69 | 53 | 365.42 | 12.70 | 88 | 607 | 58.02 | 400 | 2758 | = | 2.76 |
| 2.76 | 19 | 131.00 | 7.83 | 54 | 372.32 | 12.91 | 89 | 614 | 72.52 | 500 | 3447 | = | 3.45 |
| 2.90 | 20 | 137.90 | 7.98 | 55 | 379.21 | 13.05 | 90 | 621 | 108.78 | 750 | 5171 | = | 5.17 |
| 3.05 | 21 | 144.79 | 8.12 | 56 | 386.11 | 13.20 | 91 | 627 | 145.04 | 1000 | 6894 | = | 6.89 |
| 3.19 | 22 | 151.69 | 8.27 | 57 | 393.00 | 13.34 | 92 | 634 | 217.56 | 1500 | 10,342 | = | 10.34 |
| 3.34 | 23 | 158.58 | 8.41 | 58 | 399.90 | 13.49 | 93 | 641 | 290.08 | 2000 | 13,790 | = | 13.79 |
| 3.48 | 24 | 165.47 | 8.56 | 59 | 406.79 | 13.63 | 94 | 648 | 435.11 | 3000 | 20,684 | = | 20.68 |
| 3.63 | 25 | 172.37 | 8.70 | 60 | 413.69 | 13.78 | 95 | 655 | 580.15 | 4000 | 27,579 | = | 27.58 |
| 3.77 | 26 | 179.26 | 8.85 | 61 | 420.58 | 13.92 | 96 | 662 | 725.19 | 5000 | 34,473 | = | 34.47 |
| 3.92 | 27 | 186.16 | 8.99 | 62 | 427.48 | 14.07 | 97 | 669 | 1,450.38 | 10,000 | 68,948 | = | 68.95 |
| 4.06 | 28 | 193.05 | 9.14 | 63 | 434.37 | 14.21 | 98 | 676 | 2,175.57 | 15,000 | 103,421 | = | 103.4 |
| 4.21 | 29 | 199.95 | 9.28 | 64 | 441.26 | 14.34 | 99 | 683 | 2,900.76 | 20,000 | 137,895 | = | 137.9 |
| 4.35 | 30 | 206.84 | 9.43 | 65 | 448.16 | 14.50 | 100 | 689 | 4,351.14 | 30,000 | 206,843 | = | 206.8 |
| 4.50 | 31 | 213.74 | 9.57 | 66 | 455.05 | 15.23 | 105 | 724 | 5,801.52 | 40,000 | 275,790 | = | 275.8 |
| 4.64 | 32 | 220.63 | 9.72 | 67 | 461.95 | 15.95 | 110 | 758 | 7,251.90 | 50,000 | 344,738 | = | 344.7 |
| 4.79 | 33 | 227.53 | 9.86 | 68 | 468.84 | 16.68 | 115 | 793 | 8,702.28 | 60,000 | 413,686 | = | 413.7 |
| 4.93 | 34 | 234.42 | 10.01 | 69 | 475.74 | 17.40 | 120 | 827 | 10,152.70 | 70,000 | 482,633 | = | 482.6 |
| 5.08 | 35 | 241.32 | 10.15 | 70 | 482.63 | 18.13 | 125 | 862 | 11,603.00 | 80,000 | 551,581 | = | 551.6 |

NOTE: IT IS USUAL FOR PRESSURES IN EXCESS OF 1000 kPa TO BE EXPRESSED IN MEGAPASCALS - MPa
 1 megapascal (MPa) = 1000 kilopascals (kPa) = 1 newton per mm² (N/mm²) = 145 lbf/in²

USEFUL CONVERSION FACTORS - APPROXIMATE

| MULTIPLY | BY | TO OBTAIN |
|----------------------|---------|-----------------------|
| TO OBTAIN | BY | DIVIDE |
| Bars | 1.0197 | kg f/cm ² |
| | 100.0 | kPa |
| | 14.504 | lbf/in ² |
| | 0.1 | MPa |
| kg f/cm ² | 14.223 | lbf/in ² |
| | 98.07 | kPa |
| | 0.09807 | MPa |
| kg f/mm ² | 1422.33 | lbf/in ² |
| | 9.807 | MPa |
| | 0.635 | ton f/in ² |

| MULTIPLY | BY | TO OBTAIN |
|--|---------|-----------|
| TO OBTAIN | BY | DIVIDE |
| lb f/in ² (PSI) | 6.895 | kPa |
| | 0.00689 | MPa |
| | 15.444 | MPa |
| APPROXIMATE EQUIVALENTS | | |
| 1 Atmosphere (atm) = 14.696 lbf/in ² | | |
| 1 bar = 14.50 lbf/in ² | | |
| 1 kg f/cm ² = 14.22 lbf/in ² | | |
| 100 kPa (1 bar) = 14.50 lbf/in ² | | |

NOTE: lbf/in² (pounds force per square inch) is often expressed as PSI (pounds per square inch)

TEMPERATURE CONVERSION TABLE

The SI Unit of thermodynamic temperature is the KELVIN - Symbol K. For most practical purposes of temperature measurement and most calculations involving temperatures, DEGREE CELSIUS, symbol °C will be used. The name CELSIUS was adopted internationally in 1948 instead of Centigrade, to avoid possible confusion with the identically named unit of angle used in some European countries.

TEMPERATURE CONVERSION CHART

- (A) To use, locate "given temperature" in "given temperature" column (coloured blue) whether °C or °F.
- (B) If "given temperature" is in degrees Celsius (°C), read degrees Fahrenheit (°F) in right hand column.
- (C) If "given temperature" is in degrees Fahrenheit (°F), read degrees Celsius (°C) in left hand column.
- (D) Example: (i) Given temperature is 35°C = 95°F from right hand column
 (ii) Given temperature is 35°F = 1.7°C from left hand column

| -320 to 27 | | | 28 to 77 | | | 78 to 235 | | | 240 to 485 | | | 490 to 2400 | | |
|------------|-------------|------|----------|-------------|-------|-----------|-------------|-------|------------|-------------|-----|-------------|-------------|------|
| °C | Given Temp. | °F | °C | Given Temp. | °F | °C | Given Temp. | °F | °C | Given Temp. | °F | °C | Given Temp. | °F |
| -196 | -320 | -- | -2.2 | 28 | 82.4 | 25.6 | 78 | 172.4 | 116 | 240 | 464 | 254 | 490 | 914 |
| -184 | -300 | -- | -1.7 | 29 | 84.2 | 26.1 | 79 | 174.2 | 118 | 245 | 473 | 257 | 495 | 923 |
| -173 | -280 | -- | -1.1 | 30 | 86.0 | 26.7 | 80 | 176.0 | 121 | 250 | 482 | 260 | 500 | 932 |
| -162 | -260 | -436 | -0.6 | 31 | 87.8 | 27.2 | 81 | 177.8 | 124 | 255 | 491 | 266 | 510 | 950 |
| -151 | -240 | -400 | 0.0 | 32 | 89.6 | 27.8 | 82 | 179.6 | 127 | 260 | 500 | 271 | 520 | 968 |
| -140 | -220 | -364 | 0.6 | 33 | 91.4 | 28.3 | 83 | 181.4 | 129 | 265 | 509 | 277 | 530 | 986 |
| -129 | -200 | -328 | 1.1 | 34 | 93.2 | 28.9 | 84 | 183.2 | 132 | 270 | 518 | 282 | 540 | 1004 |
| -115 | -175 | -283 | 1.7 | 35 | 95.0 | 29.4 | 85 | 185.0 | 135 | 275 | 527 | 288 | 550 | 1022 |
| -101 | -150 | -238 | 2.2 | 36 | 96.8 | 30.0 | 86 | 186.8 | 138 | 280 | 536 | 293 | 560 | 1040 |
| -90 | -130 | -202 | 2.8 | 37 | 98.6 | 30.6 | 87 | 188.6 | 141 | 285 | 545 | 299 | 570 | 1058 |
| -84 | -120 | -184 | 3.3 | 38 | 100.4 | 31.1 | 88 | 190.4 | 143 | 290 | 554 | 304 | 580 | 1076 |
| -79 | -110 | -166 | 3.9 | 39 | 102.2 | 31.7 | 89 | 192.2 | 146 | 295 | 563 | 310 | 590 | 1094 |
| -73 | -100 | -148 | 4.4 | 40 | 104.0 | 32.2 | 90 | 194.0 | 149 | 300 | 572 | 316 | 600 | 1112 |
| -68 | -90 | -130 | 5.0 | 41 | 105.8 | 32.8 | 91 | 195.8 | 152 | 305 | 581 | 321 | 610 | 1130 |
| -62 | -80 | -112 | 5.6 | 42 | 107.6 | 33.3 | 92 | 197.6 | 154 | 310 | 590 | 327 | 620 | 1148 |
| -57 | -70 | -94 | 6.1 | 43 | 109.4 | 33.9 | 93 | 199.4 | 157 | 315 | 599 | 332 | 630 | 1166 |
| -51 | -60 | -76 | 6.7 | 44 | 111.2 | 34.4 | 94 | 201.2 | 160 | 320 | 608 | 338 | 640 | 1184 |
| -46 | -50 | -58 | 7.2 | 45 | 113.0 | 35.0 | 95 | 203.0 | 163 | 325 | 617 | 343 | 650 | 1202 |
| -40 | -40 | -40 | 7.8 | 46 | 114.8 | 35.6 | 96 | 204.8 | 166 | 330 | 626 | 349 | 660 | 1220 |
| -34 | -30 | -22 | 8.3 | 47 | 116.6 | 36.1 | 97 | 206.6 | 168 | 335 | 635 | 354 | 670 | 1238 |
| -29 | -20 | -4 | 8.9 | 48 | 118.4 | 36.7 | 98 | 208.4 | 171 | 340 | 644 | 360 | 680 | 1256 |
| -23 | -10 | 14 | 9.4 | 49 | 120.2 | 37.2 | 99 | 210.2 | 174 | 345 | 653 | 366 | 690 | 1274 |
| -17.8 | 0 | 32 | 10.0 | 50 | 122.0 | 37.8 | 100 | 212.0 | 177 | 350 | 662 | 371 | 700 | 1292 |
| -17.2 | 1 | 33.8 | 10.6 | 51 | 123.8 | 41 | 105 | 221 | 179 | 355 | 671 | 377 | 710 | 1310 |
| -16.7 | 2 | 35.6 | 11.1 | 52 | 125.6 | 43 | 110 | 230 | 182 | 360 | 680 | 382 | 720 | 1328 |
| -16.1 | 3 | 37.4 | 11.7 | 53 | 127.4 | 46 | 115 | 239 | 185 | 365 | 689 | 388 | 730 | 1346 |
| -15.6 | 4 | 39.2 | 12.2 | 54 | 129.2 | 49 | 120 | 248 | 188 | 370 | 698 | 393 | 740 | 1364 |
| -15.0 | 5 | 41.0 | 12.8 | 55 | 131.0 | 52 | 125 | 257 | 191 | 375 | 707 | 399 | 750 | 1382 |
| -14.4 | 6 | 42.8 | 13.3 | 56 | 132.8 | 54 | 130 | 266 | 193 | 380 | 716 | 404 | 760 | 1400 |
| -13.9 | 7 | 44.6 | 13.9 | 57 | 134.6 | 57 | 135 | 275 | 196 | 385 | 725 | 410 | 770 | 1418 |
| -13.3 | 8 | 46.4 | 14.4 | 58 | 136.4 | 60 | 140 | 284 | 199 | 390 | 734 | 416 | 780 | 1436 |
| -12.8 | 9 | 48.2 | 15.0 | 59 | 138.2 | 63 | 145 | 293 | 202 | 395 | 743 | 421 | 790 | 1454 |
| -12.2 | 10 | 50.0 | 15.6 | 60 | 140.0 | 66 | 150 | 302 | 204 | 400 | 752 | 427 | 800 | 1472 |
| -11.7 | 11 | 51.8 | 16.1 | 61 | 141.8 | 68 | 155 | 311 | 207 | 405 | 761 | 432 | 810 | 1490 |
| -11.1 | 12 | 53.6 | 16.7 | 62 | 143.6 | 71 | 160 | 320 | 210 | 410 | 770 | 438 | 820 | 1508 |
| -10.6 | 13 | 55.4 | 17.2 | 63 | 145.4 | 74 | 165 | 329 | 213 | 415 | 779 | 443 | 830 | 1526 |
| -10.0 | 14 | 57.2 | 17.8 | 64 | 147.2 | 77 | 170 | 338 | 216 | 420 | 788 | 454 | 850 | 1562 |
| -9.4 | 15 | 59.0 | 18.3 | 65 | 149.0 | 79 | 175 | 347 | 218 | 425 | 797 | 468 | 875 | 1607 |
| -8.9 | 16 | 60.8 | 18.9 | 66 | 150.8 | 82 | 180 | 356 | 221 | 430 | 806 | 482 | 900 | 1652 |
| -8.3 | 17 | 62.6 | 19.4 | 67 | 152.6 | 85 | 185 | 365 | 224 | 435 | 815 | 510 | 950 | 1742 |
| -7.8 | 18 | 64.4 | 20.0 | 68 | 154.4 | 88 | 190 | 374 | 227 | 440 | 824 | 538 | 1000 | 1832 |
| -7.2 | 19 | 66.2 | 20.6 | 69 | 156.2 | 91 | 195 | 383 | 229 | 445 | 833 | 566 | 1050 | 1922 |
| -6.7 | 20 | 68.0 | 21.1 | 70 | 158.0 | 93 | 200 | 392 | 232 | 450 | 842 | 593 | 1100 | 2012 |
| -6.1 | 21 | 69.8 | 21.7 | 71 | 159.8 | 96 | 205 | 401 | 235 | 455 | 851 | 621 | 1150 | 2102 |
| -5.6 | 22 | 71.6 | 22.2 | 72 | 161.6 | 99 | 210 | 410 | 238 | 460 | 860 | 649 | 1200 | 2192 |
| -5.0 | 23 | 73.4 | 22.8 | 73 | 163.4 | 102 | 215 | 419 | 241 | 465 | 869 | 704 | 1300 | 2372 |
| -4.4 | 24 | 75.2 | 23.3 | 74 | 165.2 | 104 | 220 | 428 | 243 | 470 | 878 | 760 | 1400 | 2552 |
| -3.9 | 25 | 77.0 | 23.9 | 75 | 167.0 | 107 | 225 | 437 | 246 | 475 | 887 | 816 | 1500 | 2732 |
| -3.3 | 26 | 78.8 | 24.4 | 76 | 168.8 | 110 | 230 | 446 | 249 | 480 | 896 | 1093 | 2000 | 3632 |
| -2.8 | 27 | 80.6 | 25.0 | 77 | 170.6 | 113 | 235 | 455 | 252 | 485 | 905 | 1316 | 2400 | 4352 |

CONVERSION FACTORS

DEGREES FAHRENHEIT TO CELSIUS
 $(°F - 32) \times 5/9 = °C$

DEGREES CELSIUS TO FAHRENHEIT
 $(°C \times 9/5) + 32 = °F$

CONVERSION FACTORS - IMPERIAL TO METRIC (Approx.)

“SI” denotes the International System of Metric Units adopted in Australia

This table may be used in two ways: (1) Multiply Column A by Column B to obtain Column C; or (2) Divide Column C by Column B to obtain Column A.

| Remarks | A Multiply | B By | To C Obtain |
|---|--|---|---|
| AREA: Symbol m² The SI unit of AREA is the SQUARE METRE. | Square Inches Square Feet Square Yards Acre Hectare (ha) | 645.16 0.929 0.836 4047 10000 | mm ² m ² m ² m ² m ² |
| DENSITY: Symbol kg/m³ The SI unit of DENSITY is the kilogram per cubic metre. | lb/in ³ lb/ft ³ lb/yd ³ | 27.68 16.02 0.5933 | t/m ³ kg/m ³ kg/m ³ |
| ENERGY: Symbol J The SI unit of ENERGY is the JOULE. 1 J = 1 N.m A joule is the energy expended or the work done when a force of one newton moves the point of application a distance of one metre in the direction of that force. | 1. ELECTRICAL ENERGY kilowatt hour (kW.h) | 3.6 | MJ |
| | 2. HEAT ENERGY British thermal unit (Btu) Btu/gal Btu/ft ³ | 1.055 0.2321 37.26 | kJ kJ/L †† kJ/m ³ |
| | 3. MECHANICAL ENERGY foot poundal (ft.pdl) inch pound-force (in.lbf) foot pound-force (ft.lbf) foot ton force (ft.tonf) Metre kilogram force (m.kgf) | .04214 0.1130 1.356 3.037 9.807 | J J J kJ J |
| FORCE: Symbol N (NEWTON) The SI unit of FORCE (kg.m/s ²) has been given the special name - NEWTON. The newton is the force which when applied to a body having a mass of one kilogram, causes an acceleration of one metre per second in the direction of application of the force. | Poundal (pdl) | 0.1383 | N |
| | Pound-force (lbf) | 4.448 | N |
| | ton-force (tonf) | 9.964 | kN |
| | *kilogram-force (kgf) *also known as kilopond (kp) | 9.807 | N |
| FORCE PER UNIT LENGTH: The SI unit is NEWTON PER METRE: Symbol N/m | pounds-force per inch lbf/in | 175.1 | N/m |
| | pounds-force per foot lbf/ft | 14.59 | N/m |
| | ton-force per foot ton/ft | 32.69 | kN/m |
| LENGTH: Symbol m The SI unit of LENGTH is the METRE. | inches | 25.4 | millimetres (mm) |
| | feet | 0.3048 | metres (m) |
| | yards | 0.9144 | metres (m) |
| | chain | 20.12 | metres (m) |
| | mile | 1609 | metres (m) |
| | mile | 1.609 | kilometres (km) |
| MASS: Symbol kg The SI unit of MASS is the KILOGRAM. | ounce | 28.35 | grams (g) |
| | pound | 0.4536 | kilograms (kg) |
| | slug | 14.59 | kg |
| | ton (2240 lb) | 1016.05 | kg |
| | short ton (2000 lb) | 907.2 | kg |
| | ton (2240 lb) | 1.016 | tonne (t) |
| | pounds per foot (lb/ft) pounds per yard (lb/yd) | 1.488 0.4961 | kg/m kg/m |
| POWER: Symbol W The SI unit of POWER is the WATT. | Btu per hour (Btu/hr) | 0.2931 | W |
| | horsepower (hp) | 0.7457 | kW |
| | ton of refrigeration | 3.517 | kW |

| Remarks | A Multiply | B By | To C Obtain | |
|---|---|-------------------------|--|-----|
| PRESSURE: Symbol Pa The SI unit of PRESSURE or stress is the NEWTON PER SQUARE METRE which has been given the name PASCAL. 1 N/m ² = 1Pa = 0.000145lbf/in ² A pascal is the pressure or stress which arises when a force of one newton is applied uniformly over an area of one square metre. | lbf/in ² | 6.895 | kPa | |
| | kip/in ² (1000 psi) | 6.895 | MPa | |
| | lbf/ft ² | 47.88 | Pa | |
| | kgf/cm ² | 98.07 | kPa | |
| | bar | 100 | kPa | |
| | Vertical column (head) of water. (H ₂ O at 20°C) | | | |
| | metres of water | 9.79 | kPa | |
| | feet of water | 2.984 | kPa | |
| | torr (vacuum) | 0.1333 | kPa | |
| | 1mm Hg. (mercury) | 0.1333 | kPa | |
| TORQUE: Symbol N.m (Moment of force) The SI unit of TORQUE is the NEWTON METRE. The newton metre is the work done when a force of one newton moves the point of application a distance of one metre in the direction of that force. 1 N.m = 1 J | Poundal-foot pdl.ft | 0.04214 | N.m | |
| | pound-force inch lbf.inch | 0.1130 | N.m | |
| | lbf.inch | 1.152 | kgf.cm | |
| | pound-force feet lbf.ft | 1.356 | N.m | |
| | lbf.ft | 13.83 | kgf.cm | |
| | ton-force feet ton.ft | 3.037 | kN.m | |
| | kilogram-force kgf.m | 9.807 | N.m | |
| | kgf.cm | 0.09807 | N.m | |
| | VELOCITY: Symbol m/s The SI unit of VELOCITY is the METRE PER SECOND. | ft. per second (ft/s) | 0.3048 | m/s |
| | | ft. per minute (ft/min) | 0.00508 | m/s |
| miles per hour | | 0.4470 | m/s | |
| miles per hour | | 1.609 | km/h | |
| VOLUME: CAPACITY: Symbol m³ The SI unit of VOLUME is the CUBIC METRE. NOTE: †† Capital “L” is now the legal preferred symbol for litre in Australia. | DRY: cubic inch (in ³) | 16387 | mm ³ | |
| | cubic foot (ft ³) | 0.02832 | m ³ | |
| | cubic yard (yd ³) | 0.7646 | m ³ | |
| | litre (L) †† | 1 000 000 | mm ³ | |
| | litre (L) †† | 0.001 | m ³ | |
| | gallons (Imp.) | 0.004546 | m ³ | |
| | IMPERIAL LIQUID fluid ounce | 28.41 | millilitre (ml) | |
| | pint (20 fl. oz) | 568.3 | millilitre (ml) | |
| | quart (2 pints) | 1.137 | litre (L) †† | |
| | gallon (Imp.) | 4.546 | litre (L) †† | |
| gallon (US) | 3.785 | litre (L) †† | | |
| litre (water 4°C) | 1.000 | kilogram (kg) | | |
| Imp. gallons (water 20°C) | 4.536 | kilogram (kg) | | |
| VOLUME: RATE OF FLOW Symbol m³/s The SI unit of VOLUME RATE OF FLOW is the CUBIC METRE PER SECOND. | Imp. gal. per minute (gal/min) | 0.0000758 | m ³ /s | |
| | Imp. gal. per minute | 0.272765 | m ³ /hr | |
| | Imp. gal. per minute | 0.0758 | litre per second (L/s) | |
| | cubic ft. per minute | 0.000472 | m ³ /s | |
| | cubic ft. per minute | 0.472 | litre per second (L/s) 1 m ³ = 1 kL | |
| | | | | |
| SUNDRY ITEMS: | miles per gallon | 0.3540 | km per litre | |
| | gallons per mile | 2.825 | litres per km | |

TEMPERATURE

The SI unit of TEMPERATURE is the KELVIN - Symbol K

For most practical purposes of temperature measurement and most calculations involving temperatures, degrees Celsius, symbol °C will be used.

DEGREES FAHRENHEIT TO CELSIUS: (°F - 32) x 5/9 = °C

DEGREES CELSIUS TO FAHRENHEIT: (°C x 9/5) + 32 = °F

OneSteel Metalcentre Branch Network

New South Wales

| | | | |
|----------------|----------------------------------|-------------------------|--------------|
| Albury | 242 Kiewa Street | Albury NSW 2640 | 02 6021 6011 |
| Coffs Harbour | Cnr Isles Drive & Elswick Street | Coffs Harbour NSW 2450 | 02 6652 3744 |
| Dubbo | 30 Cobbora Road | Dubbo NSW 2830 | 02 6882 6655 |
| Inverell | 235 Byron Street | Inverell NSW 2360 | 02 6722 5382 |
| Lake Macquarie | Unit 1 88 Munibung Road | Lake Macquarie NSW 2285 | 02 4954 0455 |
| Leeton | Canal Street & Market Road | Leeton NSW 2705 | 02 6953 2833 |
| Lismore | 39-41 Habib Drive | Lismore NSW 2480 | 02 6621 8722 |
| Moree | 41-45 Greenbah Road | Moree NSW 2400 | 02 6752 2627 |
| Nepean | 50-58 Jack Williams Drive | Penrith NSW 2750 | 02 4729 1797 |
| Orange | Stephen Place | Orange NSW 2800 | 02 6362 4211 |
| Parkes | 1a East Street | Parkes NSW 2870 | 02 6862 3011 |
| Silverwater | 62-70 Silverwater Road | Silverwater NSW 2128 | 02 9748 2487 |
| Tamworth | 26-30 Goonan Street | Tamworth NSW 2340 | 02 6765 4044 |
| Taree | 8 Elizabeth Avenue | Taree NSW 2430 | 02 6552 4899 |
| Wagga Wagga | 11 Saxon Street | Wagga Wagga NSW 2650 | 02 6925 1109 |
| Newcastle | Industrial Drive | Mayfield NSW 2304 | 02 4967 0900 |
| Wetherill Park | 374 Victoria Street | Wetherill Park NSW 2164 | 02 9203 2222 |
| Wollongong | 187-189 Five Islands Road | Unanderra NSW 2526 | 02 4271 1788 |

Australian Capital Territory

| | | | |
|----------|--------------|---------------|--------------|
| Canberra | John's Place | Hume NSW 2620 | 02 6260 1249 |
|----------|--------------|---------------|--------------|

Victoria

| | | | |
|------------|-------------------------------|---------------------|--------------|
| Bendigo | 22 Craig Street | Long Gully VIC 3550 | 03 5442 2288 |
| Horsham | 68 Hamilton Road | Horsham VIC 3400 | 03 5382 4411 |
| Mildura | 436-444 Benetook Avenue | Mildura VIC 3502 | 03 5023 5944 |
| Shepparton | 74-80 Florence Street | Shepparton VIC 3630 | 03 5821 7300 |
| Geelong | Cnr Broderick & Heales Roads | Corio VIC 3215 | 03 5274 1414 |
| Melbourne | 1257-1259 Ferntree Gully Road | Scoresby VIC 3179 | 03 9212 7837 |

Tasmania

| | | | |
|--------------|-----------------------------------|---------------------|--------------|
| Burnie | 12 Fairlands Drive & Bass Highway | Somerset TAS 7322 | 03 6435 1500 |
| Hobart | 67 Lampton Avenue | Moonah TAS 7009 | 03 6272 6931 |
| Launceston | 345 Hobart Road | Launceston TAS 7249 | 03 6344 5311 |
| Derwent Park | 61 Sunderland Street | Moonah TAS 7009 | 03 6272 2877 |

South Australia

| | | | |
|---------------|----------------------|-----------------------|--------------|
| Mount Gambier | Jubilee Highway West | Mt Gambier SA 5290 | 08 8725 7500 |
| Port Lincoln | 6-8 Verran Terrace | Port Lincoln SA 5606 | 08 8682 3377 |
| Whyalla | 172 Lacey Street | Whyalla SA 5600 | 08 8645 0633 |
| Port Adelaide | 13 Webb Street | Port Adelaide SA 5015 | 08 8300 3333 |

Queensland

| | | | |
|----------------|--|-------------------------|--------------|
| Brendale | 40 Kremzow Road | Brendale QLD 4500 | 07 3889 7575 |
| Bundaberg | 79 Princess Street | Bundaberg QLD 4670 | 07 4132 8888 |
| Cairns | Cnr Buchan & Kenny Streets | Cairns QLD 4870 | 07 4035 4677 |
| Dalby | Warrego Highway | Dalby QLD 4405 | 07 4669 8133 |
| Emerald | 10 Hicks Street | Emerald QLD 4720 | 07 4982 2488 |
| Gladstone | Bensted Street Clinton Industrial Estate | Gladstone QLD 4680 | 07 4972 8033 |
| Gold Coast | 2 Distribution Avenue | Molendinar QLD 4214 | 07 5597 6822 |
| Mount Isa | 45 Commercial Road | Mount Isa QLD 4825 | 07 4743 4089 |
| Rockhampton | 1-17 Knight Street | Rockhampton QLD 4701 | 07 4936 9555 |
| Toowoomba | Cnr Anzac Avenue & Canning Streets | Toowoomba QLD 4350 | 07 4637 7222 |
| Yatala | 5 Business Street | Yatala QLD 4207 | 07 3382 7111 |
| Brisbane | 692 Boundary Road | Coopers Plains QLD 4108 | 07 3275 8400 |
| Sunshine Coast | 62 Enterprise Street | Kunda Park QLD 4556 | 07 5476 5366 |
| Townsville | 387-399 Bayswater Road | Townsville QLD 4814 | 07 4775 6111 |
| North Mackay | Cnr Harbour Road & Spiller Avenue | North Mackay QLD 4740 | 07 4955 1555 |
| Mackay (Paget) | 52 Central Park Drive | Mackay QLD 4740 | 07 4952 4642 |

Western Australia

| | | | |
|--------------|---|----------------------|--------------|
| Bunbury | 7 Richter Road | Bunbury WA 6230 | 08 9725 4199 |
| Kalgoorlie | Cnr Great Eastern Highway & Atbara Street | Kalgoorlie WA 6430 | 08 9021 4488 |
| Geraldton | 89 Flores Road | Geraldton WA 6530 | 08 9921 4533 |
| Karratha | Cnr Cowle & Coolawanyah Roads | Karratha WA 6714 | 08 9144 0111 |
| Port Hedland | Lot 5271 Munda Way | Port Hedland WA 6721 | 08 9140 2822 |
| Perth | 1 Howson Way | Spearwood WA 6163 | 08 9418 9877 |

Northern Territory

| | | | |
|---------------|--------------------|-----------------------|--------------|
| Alice Springs | 40 Smith Street | Alice Springs NT 0870 | 08 8952 3222 |
| Darwin | 889 Stuart Highway | Berrimah NT 0828 | 08 8935 0350 |

onesteel
metalcentre

Yes,

we can.

tubular | beams | channels | columns | angles | bar | plate | reinforcing

www.onesteelmetalcentre.com