



KUBOTA ZERO-TURN MOWER Z122R

The ultimate residential zero turn mower combining style, comfort and performance.



Introducing the ALL-NEW Z122R with 42"deck.



Introducing the all-new Z122R with 42" deck. Manoeuvre in and out of intricate spaces smoothly and with ease while delivering the power you need to get the job done quickly. The Z122R offers unmatched ergonomics and comfort to keep you working efficiently all day long.









COMFORT / CONVENIENCE / STYLE

HIGH BACK SEAT

Soft and roomy, the high back seat will keep you comfortable even on those extra-long mowing jobs.



WIDE FOOT PAN

There's plenty of legroom up front, thanks to a wide foot pan. It also makes entry and exit a snap.



CUP HOLDER

Keep your drink handy in the integrated cup holder.



EASY OPERATION

1/4" INCREMENT CUTTING HEIGHT ADJUSTMENT

A simple twist of a dial lets you adjust the cutting height in precise 1/4" increments.



ERGONOMIC CONTROL LAYOUT

All controls are neatly placed for quick, easy, user-friendly access.



MAINTENANCE

NO GREASE UP POINTS

Removal of grease ports means simpler maintenance and increased user-friendliness.

EASY ENGINE MAINTENANCE

Easy access to engine oil and filter is provided without removing the cover.

WASH PORT

Just connect your hosepipe to wash off wet grass.



WHEN PERFORMANCE COUNTS...

Kubota Z122R delivers. The powerful engine, rugged transmission and strong frame let you take on the toughest jobs with confidence and ease.





finer mulch and sends it straight back into the turf.

Specifications

Model			Z122R
Engine	Brand		Kawasaki
	Туре		Petrol, air-cooled V-Twin
	Horsepower (Net)	kW	14.1
	· · · · · ·		726
	Total displacement	CC	12.2
	Fuel tank capacity	ℓ	
Dimensions	Overall length	mm	1890
	Overall width w/o discharge deflector		1075
	Overall height	mm	1650
	Wheelbase	mm	1235
	Weight	kg	282
Tyre	Front		11 x 4 - 5 Smooth
	Rear		18 x 7.5 - 10 Turf
Travel speed	Forward	km/h	0–10.5
	Reverse	km/h	0-6.4
Transmission	Туре		Independent T/M
	Supplier and model		Hydro Gear EZT®(ZT-2200)
	T/M drive system		Belt Drive
	Speed control		2 hand levers with height and angle adjustment
	Parking brake system		Cog Lock / Hand Lever
Mower deck	Cutting width	cm / inch	107 / 42
	Discharge		Side (Mulching kit available as option)
	Cutting height ranges	mm / inch	38 - 108 / 1.50 - 4.25
	Cutting height increments	mm / inch	6 / 0.25
	Deck pan depth	mm / inch	114 / 4.5
	Deck pan thickness	Ga. / mm	11 / 3.0
	Deck construction		Fabricated
	Mower location		Mid mount
	Mounting method		Parallel linkages
	Adjustment of cutting height		Dial adjustment system
	Mower deck lifting method		Mechanical Foot Lift Pedal
	Driving method		Belt Drive
	Number of Blades		2
	Washport		1
Fuel gauge	·		Sight Window type
Seat			18inch Deluxe High Back Seat
ROPS			Standard. ISO21299
PTO clutch			Electric
Cup holder			Standard
Hour meter			Standard
Warranty			4 years / 300 hours
-	erves the right to change the above s		

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional, and not standard equipment.

Please contact your local Kubota dealer for warranty, safety or product information.

Option kit









Arm rest kit

• Hitch kit

• Mulching kit

©2017 Kubota Corporation



KUBOTA (U.K.) LIMITED

Dormer Road Thame, Oxfordshire, OX9 3UN. Phone (01844) 268000 Fax (08702) 429677

Web site: http://www.kubota.co.uk